

KOP-COAT INC -- TT-E-529F, TY 1, VOC COMPLAINT 27038 BLACK -- 8010-00-297-0591

=====
Product Identification
=====

Product ID:TT-E-529F, TY 1, VOC COMPLAINT 27038 BLACK

MSDS Date:08/01/1989

FSC:8010

NIIN:00-297-0591

MSDS Number: BNWLB

=== Responsible Party ===

Company Name:KOP-COAT INC

Address:436 7TH AVENUE

City:PITTSBURGH

State:PA

ZIP:15219

Country:US

Info Phone Num:800-547-2468

Emergency Phone

Num:800-548-0489/800-424-9300 CHEMTREC

Preparer's Name:C A HOPE

CAGE:00297

=== Contractor Identification ===

Company Name:KOP-COAT INC

Address:436 7TH AVENUE

City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

Phone:800-553-5631, CHEMTREC 800-424-9300

CAGE:00297

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL PROPYL KETONE

CAS:107-87-9

RTECS #:SA7875000

Fraction by Wt: 5-10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/250 PPM STEL

ACGIH TLV:200 PPM/2

50 PPM STEL

Ingred Name:1,1,1-TRICHLOROETHANE

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 15-20%

Other REC Limits:NONE SPECIFIED

OSHA PEL:350 PPM/450 PPM STEL

ACGIH TLV:350 PPM/450 PPM STEL

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ozone Depleting Chemical:1

Ingred Name:METHYL ETHYL KETONE (SARA 313)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 1-5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/300 PPM STEL

ACGIH TLV:200 PPM/300 PPM STEL

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred

Name:TALC

CAS:14807-96-6

RTECS #:WW2710000

Fraction by Wt: 10-15%

Other REC Limits:NONE SPECIFIED

OSHA PEL:2 MG/M3 RESP DUST

ACGIH TLV:2 MG/M3 RESP DUST

Ingred Name:MINERAL SPIRITS (EXPOS LIMITS ARE FOR STODDARD SOLVENT)

(NIOSH EXPOS LIMIT: 350 MG/M3 10 HR TWA;1800 MG/M3 15 MIN CEIL)

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 1-5%

Other REC Limits:NIOSH LIMITS ABOVE

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:XYLENE (SARA 313) (NIOSH EXPOSURE LIMIT: 100 PPM 10 HR TWA;

20

0 PPM 10 MIN CEILING)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: .9-.1%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/150 PPM STEL

ACGIH TLV:100 PPM/150 PPM STEL

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOAMYL KETONE

CAS:110-12-3

RTECS #:MP3850000

Fraction by Wt: 5-10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

Ingred Name:CRYSTALLINE SILLICON DIOXIDE (NIOSH EXPOSURE LIMIT: 50
MICROGRAMS/M3 [10 HR TWA RESPIRABLE FREE SILICA])

CAS:14

808-60-7

RTECS #:VV7330000

Fraction by Wt: 5-10%

Other REC Limits:NIOSH LIMIT ABOVE

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: 1-5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3

Ingred Name:LEAD (SARA 313)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: .3-.4%

Other REC Limits:NIOSH1

Spec Gravity:10.0+/- .2LB/GAL

Viscosity:67-77 KU

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK

VISCOUS LIQUID WITH A TYPICAL SOLVENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID OXIDIZING AGENTS, HEAT, SPARKS AND OPEN FLAMES.

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE UPON THERMAL DECOMPOSITION.

===== Disposal Considerations =====

Waste Disposal Methods: THIS PRODUCT IS A US EPA DEFINED IGNITABLE HAZARDOUS WASTE. DISPOSE OF AS AN IGNITABLE HAZARDOUS WASTE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.