View NSN Online: https://aerobasegroup.kr/nsn/3040-00-528-1997 JAY AUTOMOTIVE SPECIALTIES INC -- 6B0187 -- 3040-00-528-1997 ============= Product Identification ======================== Product ID:6B0187 MSDS Date:10/05/1992 FSC:3040 NIIN:00-528-1997 MSDS Number: BNWMH === Responsible Party === Company Name: JAY AUTOMOTIVE SPECIALTIES INC Address:701 NORTH ST City:BERLIN State:PA ZIP:15530 Country:US Info Phone Num:814-267-4151 Emergency Phone Num:814-267-4151 Preparer's Name: HMIS TECHN **ICIAN** CAGE:1AV08 === Contractor Identification === Company Name: JAY AUTOMOTIVE SPECIALTIES INC Address:701 NORTH ST Box:City:BERLIN State:PA ZIP:15530 Country:US Phone:814-267-4151 CAGE:1AV08 ======= Composition/Information on Ingredients ======== Ingred Name: ASBESTOS, CHRYSOTILE CAS:12001-29-5 RTECS #:CI6478500 Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.2 FIBERS/CC

ACGIH TLV:2 FIBERS/CC; A1;9192

======== Hazards Identification ===========

Routes of En

try: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:ACUTE:MINOR EYS/SKIN IRRITATION.
INGESTION- IRRITATION OF GI TRACT. INHALATION-IRRITATION OF
RESPIRATORY TRACT. CHRONIC: ASBESTOSIS, LUNG CANCER, &
MESOTHELIOMA, ALL OF WHICH ARE DISABLING AND FATAL D ISEASES OF THE
LUNG. INHALATION AND INGESTION OF ASBESTOS FIBERS MAY CAUSE CANCER
OF THE BOWEL.

Explanation of Carcinogenicity: ASBESTOS IS A KNOW N HUMAN CARCINOGEN.

Effects of Overexposure:INHALATION: FATIGUE AND SHORTNESS OF BREATH THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING. EYES: IRRITATION. SKIN: IRRITATION. INGESTION: MILD STOMACH DISTRESS. DIARRHEA, VOMITING, AND NA USEA.

Medical Cond Aggravated by Exposure: ASTHMA, EMPHYSEMA, AND TUBERCULOSIS ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

First Aid:INHALATION: REMOVE

TO FRESH AIR. SEE DOCTOR. EYES: RINSE

THOROUGHLY WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEE DOCTOR. INGESTION: DIL UTE WITH WATER. DO NOT INDUCE VOMITING.SEE DOCTOR.

========== Fire Fighting Measures ================

Flash Point: NOT REQUIRED

Extinguishing Media: USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL F

ACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard: COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

======== Accidental Release Measures ===========

Spill Release Procedures:VACUUM THE MATERIAL WITH A HEPA FILTERED VACUUM. THE EQUIPMENT SHALL BE USED & EMPTIED SO AS TO MINIMIZE THE RE-ENTRY OF ASBESTOS INTO THE WORKPLACE. OTHERWISE, WET THE MATERIAL WITH WATER & SURFACTAN T AND THEN SHOVEL OR MOP UP C

======================================
Handling and Storage Precautions:LINING IS NONFRIABLE & WILL NOT SHED FIBERS IN NORMAL USE AND STORAGE. USED LINING SHALL BE WETTED BEFORE, DURING & AFTER DISASSEMBLY FROM AN ENGINE. Other Precautions:IF IT IS NECESSARY TO CUT OR IMPACT THE LINING WHILE INSTALLING IT, WEAR A RESPIRATOR AND PROTECTIVE CLOTHING. USED LININGS SHALL BE IDENTIFIED AND DISPOSED OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:WEAR A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF REQUIRED. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES. Ventilation:LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTICULATE EMISSIONS. HEPA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN. Protective Gloves:COTTON OR LEATHER Eye Protection:SAFETY GLASSES OR GOGGLES Other Protective Eq uipment:USE COVERALLS OR DISPOSABLE CLOTHING. Work Hygienic Practices:WET WORK TO THE DEGREE POSSIBLE. WASH HANDS AFTER HANDLING LINING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE Supplemental Safety and Health MSDS GENERATED BY HMIS TECHNICIAN, MSDS NOT AVAILABLE FROM MFR.
======================================
HCC:T6 Solubility in Water:INSOLUBLE Appearance and Odor:MOLDED CLUTHCH DISC LINING Percent Volatiles by Volume:0
========= Stability and R eactivity Data ==================================
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, AND STRONG ALKALIS Stability Condition to Avoid:ACCUMULATIONS OF DUST Hazardous Decomposition Products:ASBESTOS DUST ===================================

ONTAMINATION.

Waste Disposal Methods:WET THE MATERIAL WITH WATER AND SURFACTANT. PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS INTO ANOTHER POLY BAG OR A SAFE PLACE UNTIL IT CA

N BE SHIPPED TO AN APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING LABEL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

assume responsibility for the suitability of this information to their particular situation.