

CSD INC. -- THINNER, AIRCRAFT COATING -- 8010-01-200-2637

=====  
Product Identification  
=====

Product ID:THINNER, AIRCRAFT COATING

MSDS Date:04/01/1992

FSC:8010

NIIN:01-200-2637

MSDS Number: BNWVJ

=== Responsible Party ===

Company Name:CSD INC.

Address:5 HACKBERRY LANE

City:CONROE

State:TX

ZIP:77303

Country:US

Info Phone Num:409-756-1065 M-F 8:00AM-4:30PM CST

Emergency Phone Num:800-424-9300(CHEM  
TREC)

Preparer's Name:DAVID SHIPP

CAGE:JO933

=== Contractor Identification ===

Company Name:CSD INC.

Address:5 HACKBERRY LANE

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:409-756-1065

CAGE:JO933

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION\_INGREDIENT

=====  
Hazards Identification  
=====

Health Hazards Acute and Chronic:EYE: MODERATE IRRITATION, REDNESS,  
TEARING. SKIN: SLIGHT

IRRITATION. INHAL:NASAL/RESP IRRIT, CNTRL NERV

SYS EFFECTS(DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS). INGESTION: GASTROIN TESTINAL IRRIT, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION INTO LUNGS CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

Effects of Overexposure:CHRONIC OVEREXPOS: (HUMANS) CARDIAC ABNORMALITY AND LIVER ABNORMALITIES. (ANIMALS) ANEMIA, LIVER ABNORMALITIES, KIDNEY, EYE, SPLEEN, BRAIN, AND LUNG DAMAGE. MINOR EMBRYOTOXIC/FETOTOXIC EFF

ECTS (LEVELS >1000 PPM FOR MOST OF GESTATION PERIOD). MAY SHORTEN TIME OF ONSET OF PERIPHERAL NEUROPATHY.

=====  
===== First Aid Measures =====

First Aid:EYE: IF IRRIT/RED, FLUSH W/WATER HOLD EYELIDS APART, 15 MIN. GET MED AID. SKIN: REMOVE CONTAM SHOES/CLOTHS. FLUSH W/WATER. IF SKIN BROKEN, APPLY CLEAN DRESSING, GET MED AID OR WASH W/SOAP & WATER. IF IRRIT/RED, GET MED AID. INHAL/INGEST: ASPIRATION HZD. DONT INDUCE VOMIT. NOTHING BY MOUT  
H TO UNCONSCIOUS/DROWSY PERSON,  
PLACE ON LEFT SIDE W/ HEAD DOWN. KEEP WARM/QUITE. GET MED AID. DONT LEAVE ALONE.

=====  
===== Fire Fighting Measures =====

Flash Point:32.0F,0.0C

Lower Limits:1.7

Upper Limits:11.8

Extinguishing Media:DRY CHEMICAL, CO2, UNIVERSAL TYPE FOAM, WATER FOG OR DRY CHEMICAL. NON-CORROSIVE @20C

Fire Fighting Procedures:PROTECT EQUIP INCLUDING RESP PROTECT. STOP SPILL IF W/O RISK. MOVE UNDAMAGED CNTNRS. USE WTR SPRAY (COOL/DI

SPERSE VAPORS). AVOID SPREAD BURN LIQ W/WTR FOR COOL.

Unusual Fire/Explosion Hazard:FLAMMABLE. GROUND/BOND 5 GAL &/+ WHEN TRANSFER. VAPOR HEAVIER THAN AIR, TRAVEL DIST TO IGNIT SOURCE, FLASHBCK/ EXPLOD. COOL CONTNR TO PREVENT EXPLOSION W/HEAT.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:KEEP IGNT/HOT SRFACES FROM SPILL. STAY UPWIND/LIMIT ENTRY. STOP SPILL W/O RISK. WEAR PROTECT EQUIP W/RESPIRATORY PROTECT PER COND. PREVENT ENTERI

NG WATER SYSTEMS.

DIKE. USE ABSORB MATERIAL. NOTIFY FIRE, FED, STATE, LCL AGENCIES.

IMMED CLEANUP RECOMM#

Neutralizing Agent:N/K #IF> RQ NOTIFY NRC (800)424-8802) RQ 5000LB

(METHYL ETHYL/ISOBUTYL KETONE.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED, COOL, DRY AND AWAY FROM ALL SOURCES OF IGNITION. USE AND STORE WITH ADEQUATE VENTILLATION.

Other Precautions:AVOID INHAL OF VAPORS/CONTACT.

BOND/GROUND EQUIP WHEN

TRANSFERRING TO ANOTHER CNTNR. EMPTY CNTNR RETAIN RESIDUE (LIQUID/VAPOR). CAN BE DANGEROUS. DONT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE CNTNR TO HEAT/IGNIT SOURCE.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED, NIOSH/MSHA AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS (NEGATIVE

PRESSURE TYPE) UNDER SPECIFIED COND-SEE SFTY EQUIP SUPPLIER.

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLVS.

Protective Gloves:WEAR RESISTANT GLOVES SUCH AS NEOPRENE.

Eye Protection:CHEM SPLSH GOGGLES/OTHER SFTY GLASSES.##

Other Protective Equipment:TO PREVENT PROLONGED OR REPEATED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.

Supplemental Safety and Health

##IN COMPLIANCE WITH OSHA REGULATIONS ARE ADVISED.

OSHA REGULATIONS

ALSO PERMIT OTHER TYPES OF SAFETY GLASSES (CONSULT YOUR EQUIPMENT SUPPLIER).

=====  
===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:175F,79C

Melt/Freeze Pt:M.P/F.P Text:-20F,-29C

Vapor Pres:49.1 @20C

Vapor Density:3.4@20C

Spec Gravity:0.839@20C

pH:\*

Evaporation Rate & Reference:2.6(NBAC=1.00)

Solubility in Water:MODERATE

Appearance and Odor:CLEAR, LITTLE IF ANY COLOR - CHARACTERISTIC

Percent Volatiles by Volume:100

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

THIS PRODUCT IS INCAPATIBLE WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: THIS PRODUCT FORMS COMBUSTIBLE AND/OR  
EXPLOSIVE MIXTURES WITH AIR AND/OR OXYGEN.

Hazardous Decomposition Products: THERMAL DECOMPOSITION IN THE PRESENCE  
OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:

DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL,  
COUNTY, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
a

assume responsibility for the suitability of this information to their  
particular situation.