

FISKE BROTHERS REFINING CO -- LUBRIPLATE NO 105 -- 9150-00-076-1584

=====  
Product Identification  
=====

Product ID:LUBRIPLATE NO 105

MSDS Date:05/01/1987

FSC:9150

NIIN:00-076-1584

MSDS Number: BPBHW

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150

Emergency Phone Num:201-589-9150

Pre

parer's Name:ROBERT J. SIBILIA

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NON HAZARDOUS INGREDIENTS

=====  
Hazards I

dentification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING EYES MAY CAUSE IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED. THIS PRODUCT HA

S A LOW ORDER OR ACUTE ORAL TOXICITY, BUT MINUTE (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:HLTH HAZ:AMOUNTS ASPIRATED INTO LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES:FLUSH W/CLEAR WATER FOR AT LEAST 15 MIN/UNTIL IRRIT SUBSIDES. IF IRRIT PERSISTS, CONSULT MD. SKIN:REM

OVE ANY CONTAM

CLTHG & WASH W/SOAP & WARM WATER. IF INJECTED BY HIGH PRESS UNDER SKIN, REGARDL ESS OF APPEARANCE/ITS SIZE, CONT MD IMMED. DELAY MAY CAUSE LOSS OF AFFECTED PART OF BODY. INHAL:VAP PRESS IS VERY LOW & INHAL AT ROOM TEMP IS NOT A PROBLEM. IF OVERCOME BY VAPS FROM HOT PROD, (SUPDAT)

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>360F,>182C

Lower Limits:0.9%

Upper Limits:7.0%

Extinguishing Media:FOAM, DRY

CHEMICAL, CARBON DIOXIDE, WATER SPRAY (FOG).

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT . COOL EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND OR WELD, AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE. WASH REMAINER WITH SUITABLE PETROLEUM SO

LVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWER AND WATER COURSES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====

=== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED. USE NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:USE LOCAL EXHAUST TO CAPTURE FUMES AND VAPORS.

Protective Gloves:USE OIL-RESISTANT GLOVES IF NEEDED.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:USE OIL RESISTANT APRON IF NEEDED.

Work Hygienic Practices:REMOVE OIL SOAKED CLOTHING AND LAUNDRER BEFORE REUSE. CLEANSE SKIN THOROUGHLY

AFTER CONTACT.

Supplemental Safety and Health

SPEC GRAV:0.945-0.965 (H\*2O = 1). FIRST AID PROC:IMMEDIATELY REMOVE FROM EXPOSURE AND CALL MD. INGEST:CALL MD IMMEDIATELY. DO NOT INDUCE VOMITING.

=====  
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>550F,>288C

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5

Spec Gravity:SUPDAT

Evaporation Rate & Reference: