View NSN Online: https://aerobasegroup.kr/nsn/3439-00-900-2856

TWECO PRODUCTS INC -- ARC METAL REMOVAL -- 3439-00-900-2856

Product ID:ARC METAL REMOVAL MSDS Date:10/31/1990 FSC:3439 NIIN:00-900-2856 **MSDS Number: BPBNS** === Responsible Party === **Company Name: TWECO PRODUCTS INC** Address:4200 W HARRY STREET Box:12250 City:WICHITA State:KS ZIP:67277 Country:US Info Phone Num:316-942-1421 Emergency Phone Num:316-942-1421 Preparer's Name: DENNIS WILSON CAGE:89381 === Contractor Identification === Company Name: LAND M WELDING SUPPLY INC Address:568 WESTERN DR Box:City:MOBILE State:AL ZIP:36607-1420 Country:US Phone:334-470-9997 CAGE:1HJ95 Company Name: TWECO PRODUCTS, INC. Address:4200 WEST HARRY ST. Box:12250 City:WICHITA State:KS ZIP:67277 Country:US Phone:316-946-8308;316-942-1421 CAGE:89381

======= Composition/Information on Ingredients ==========

Ingred Name:GRAPHITE, SYNTHETIC CAS:7440-44-0 RTECS #:FF525010 0 Fraction by Wt: 20-90% Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:2 MG/M3 TDUST; 9293

Ingred Name:GRAPHITE, NATURAL CAS:7782-42-5 RTECS #:MD9659600 Fraction by Wt: 20-90% Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MPPCF RDUST ACGIH TLV:2 MG/M3 RDUST; 9293

Ingred Name:COPPER (SARA III) CAS:7440-50-8 RTECS #:GL5325000 Fraction by Wt: 10-30% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.1MG/M3 FUME/1 DUST ACGIH TLV:0.2MG/M3 FUME; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty :5000 LBS

Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Other REC Limits:NONE RECOMMENDED OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9293

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CUTTING CONSUMABLES ARE NON-REACTIVE, NON-FLAMMABLE, NON-EXPLOSIVE, AND ESSENTIALLY NON-HAZARDOUS UNTIL USED IN A CUTTING OPERATION. C
UTTING HAZARDS INCLUDE INHALATION OF FUMES, THERMAL BURNS, RADIAT ION BURNS AND ELECTRIC SHOCK.
Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.
Effects of Overexposure:EXPOSURE TO CUTTING FUMES MAY CAUSE METAL FUME FEVER RESULTING IN DIZZINESS, NAUSEA, FEVER AND/OR IRRITATION OF NOSE, THROAT AND EYES. TOXIC GASES CAN BE FATAL.
Medical Cond Aggravated by Exposure:PRE-EXISTING

RESPIRATORY DISFUNCTION MAY BE AGGRAVATED BY FUME INHALATION.

First Aid:FUME INHALATION:REMOVE FROM EXPOSURE. GET MEDICAL ATTENTION. THERMAL BURN:USE NORMAL FIRST AID. ULTRAVIOLET EXPOSURE:SKIN;TREAT AS SUNBURN. EYE; GET MEDICAL ATTENTION. ELECTRIC SHOCK:TURN OFF POWER. R EMOVE AND RESTORE BREATHING IF NECESSARY. GET MEDICAL ATTENTION.

Flash Point:NONE

Autoignition Temp:Autoignition Temp Text:NONE

Extinguishing Media:NONCOMBUSTIBLE. USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE CONDITIONS.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:SWEEP OR PICKUP. BE ALER T TO "HOT ENDS". Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions:STORE IN A DRY AREA. ELECTRODES EXPOSED TO MOISTURE MAY EXPLODE VIOLENTLY IF USED. DRY MOIST RODS BY BAKING AT 300F FOR TEN HOURS.
Other Precautions:SEE ANSI STANDARD Z49.1-1983. READ "SAFETY IN WELDING AND CUTTING" FROM AMERICAN WELDING ASSOCIATION, 550 N.W. JEUNE RD., MIAMI,FL 33135.

Respiratory Protection:USE NIOSH/MSHA WELD FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN CUTTING IN A CONFINED SPACE OR WHERE LOCAL EXHAUST OR GENERAL VENTILATION DOES NOT KEEP EXPOSURE BELOW PEL/TLV.

Ventilation: USE LOCAL VENTILATION WHEN CUTTING TO KEEP THE DUST, FUMES & GASES FROM THE WORKERS BREATHING ZONE.

Protective Gloves:WELDERS LEATHER GLOVES

Eye Protection: FACE SHIELD OR WELDERS HELMET W/#12 LENS

Other Protective Equipment: FLAME RETARDANT CLO

THING WHEN CUTTING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING. Work Hygienic Practices: USE GOOD INDUSTRIAL HYGIENE. WASH THOROUGHLY BEFORE EATING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health HOT CUTTING FUMES & GASES CANNOT BE CLASSIFIED SIMPLY. THEIR COMPOSITION AND QUANTITY ARE DEPENDENT ON THE METAL BEING CUT, THE PROCEDURES. PROCESSES AND THE TYPE OF WIRE OR ELECTRODES USED. OTHER INF LUENCING FACTORS ARE THE PRESENCE O F CONTAMINANTS. CHLORINATED SOLVENTS MAY DECOMPOSE TO TOXIC GASES. HCC:N1 Solubility in Water:NEGLIGIBLE Appearance and Odor: COPPER COATED BLACK ROD. NO ODOR Percent Volatiles by Volume:0 Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, TRACES OF COPPER FUME.

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.