

OCTAGON PROCESS INC. -- MIL-L-6085B; LUBRICATING OIL, AIRCRAFT, INS -- 9150-00-223-4129

=====
Product Identification
=====

Product ID:MIL-L-6085B; LUBRICATING OIL, AIRCRAFT, INS

MSDS Date:09/16/1991

FSC:9150

NIIN:00-223-4129

MSDS Number: BPBSN

=== Responsible Party ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Info Phone Num:201-945

-9400

Emergency Phone Num:201-945-9400

Preparer's Name:SIGNATURE NOT CLEAR

CAGE:82925

=== Contractor Identification ===

Company Name:AMERICAN INK AND OIL CORP

Address:33 ENDICOTT STREET

Box:City:NORWOOD

State:MA

ZIP:02062-3006

Country:US

Phone:781-762-0026 / FAX: 781-762-1617

CAGE:82956

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

=====
Composition/Information on Ingredients
=====

Ingre

d Name:NON HAZARDOUS INGREDIENT

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY
CAUSE MILD IRRITATION. HEATED OIL MIST MAY BE IRRITATING TO
RESPIRATORY TRACT.

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.

Effects of

Overexposure:REDNESS OR DRYING EFFECT ON SKIN.

Medical Cond Aggravated by Exposure:NO DATA AVAILIABLE.

===== First Aid Measures =====

First Aid:SKIN/EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. IF
IRRITATION PERSISTS, GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:435F,224C

Lower Limits:N.D.

Upper Limits:N.D.

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE.

Fire

Fighting Procedures:KEEP FIRE EXPOSED CONTAINERS COOL WITH WATER
SPRAY. WEAR PROTECTIVE CLOTHING. WATER OR FOAM MAY CAUSE FROTHING.
SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:CARBON DIOXIDE AND MONOXIDE.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LIQUID. ADD ABSORBENT TO SPILL
AREA. KEEP PETROLEUM PRODUCTS OUT OF DRAINS, SEWERS & WATERCOURSES
BY DIKING OR IMPOUNDING. ADVISE AUTHORITIES IF PROD
UCT ENTERS OR

MAY ENTER SEWERS, WATERC OURSES OR EXTENSIVE LAND AREAS.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY PLACE. KEEP AWAY
FROM STRONG OXIDANTS. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:AVOID BREATHING OIL-MIST. DISCARD OIL-SOAKED SHOES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED. U

SE SUPPLIED AIR

RESPIRATORY PROTECTION IN CONFINED OR ENCLOSED SPACES.

Ventilation:LOCAL EXHAUST-USE FOR CAPTURING FUMES/VAPORS.

SPECIAL-PROVIDE > THAN 60 RPM HOOD OR FACE VELOCITY FOR CONFINED AREAS.

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:CHEMICAL SAFETY GOGGLES/FACE SHIELD.

Other Protective Equipment:CHEMICAL RESISTANT APRON OR OTHER CLOTHING IF NEEDED. EYE WASH FOUNTAIN.

Work Hygienic Practices:WASH HANDS AND FACE AFTER USING. LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE.

ORE RE-USE.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:385F,196C

Melt/Freeze Pt:M.P/F.P Text:-80F,-62C

Decomp Temp:Decomp Text:N.D.

Vapor Pres:N.D.

Vapor Density:N.D.

Spec Gravity:0.92

pH:N.D.

Evaporation Rate & Reference:N.D.

Solubility in Water:NEGLIGIBLE

Appearance and Odor:PALE YELLOW TO AMBER COLORED LIQUID, ESTER-LIKE ODOR.

Percent Volatiles by Volume:N.D.

Corrosion Rate:N.D.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CARBON MONOXIDE, SULFUR OXIDES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This i

Information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.