

BATTENFELD GREASE AND OIL CORP OF NEW YORK INC -- VV-C-846A TYPE I -- 9150-00-252-6380
===== Product Identification =====

Product ID:VV-C-846A TYPE I

MSDS Date:12/01/1990

FSC:9150

NIIN:00-252-6380

MSDS Number: BPBTM

=== Responsible Party ===

Company Name:BATTENFELD GREASE AND OIL CORP OF NEW YORK INC

Address:1174 ERIE AVE

Box:728

City:NORTH TONAWANDA

State:NY

ZIP:14120-3036

Country:US

Info Phone

Num:716-695-2100

Emergency Phone Num:716-695-2100

Preparer's Name:THOMAS G. MUSILLI

CAGE:EO110

=== Contractor Identification ===

Company Name:BATTENFELD AMERICA INC

Address:1575 CLINTON ST

Box:City:BUFFALO

State:NY

ZIP:14206

Country:US

Phone:716-822-8410

CAGE:61808

Company Name:BATTENFELD GREASE AND OIL CORP OF NEW YORK INC

Address:1174 ERIE AVE

Box:728

City:NORTH TONAWANDA

State:NY

ZIP:14120-3036

Country:US

Phone:716-695-2100

CAGE:60226

Company Name:BATTENFELD GREASE AND OIL CORP OF NEW YORK IN

C

Address:1174 ERIE AVE

Box:728

City:NORTH TONAWANDA

State:NY

ZIP:14120-3036

Country:US

Phone:716-695-2100

CAGE:EO110

=====
===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (CAS #6474-52-5)

CAS:64742-52-5

RTECS #:PY8035000

Fraction by Wt: 85%

ACGIH TLV:5 MG/CUM (MIST)

Ingred Name:SODIUM SULFONATE

Fraction by Wt: 10%

Ingred Name:WATER (CAS #7732-18-5)

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 2%

Ingred Name:TALL OIL (SODIUM SALT) (CAS #65997-01-5)

Fraction by Wt: 2%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MAY CAUSE MILD, TRANSIENT SKIN AND EYE IRRITATION ON CONTACT. MAY CAUSE SKIN AND RESPIRATORY TRACT SENSITIZATION.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of

Overexposure:SKIN: REDNESS, ITCHING. EYES: REDNESS, TEARING, BLURRED VISION, DISCOMFORT.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:INHALED: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES. SEE DOCTOR. SKIN : REMOVE CONTAMINATED CLOTHES. WASH WITH SOA

P AND

WATER. INGESTED: DO NOT INDUCE VOMITING! GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:340F,171C

Autoignition Temp:Autoignition Temp Text:380F

Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND OR EARTH.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. CAUTION-WATER MAY CAUSE FROTHING.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. ABSORB WITH INERT MATERIAL AND PLACE IN A CONTAINER FOR LATER DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM SOURCES OF IGNITION. KEEP CONTAINER CLOSED.

Other Precautions:WASH THOROUGHLY AFTER HANDLING, DO NOT GET IN EYES OR ON CLOTHING. DO NOT BREATHE DUST, VAPOR, MIST, GAS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV EXCEEDED OR ENGINEERING SYSTEMS FAIL OR IN EMERGENCY; USE NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE. IF RESPIRATOR USED; A PROGRAM IN ACCORDANCE WITH 29 CFR 1910.134 MUST BE IMPLEMENTED.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION.

Protective Gloves:RUBBER/NEOPRENE

Eye Protection:FACE SHIELD

Other Protective Equipment:APRON, RUBBER BOOTS. HMIS: EYE WASH STATION

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING OR SMOKING. LAUNDRY CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

MSDS REPRESENTS FORMULA CHANGE AND UPDATE IN CAGE CODE FOR MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:700F,371C

Melt/Freeze Pt:M.P/F.P Text:-10F,-23C

Spec Gravity:0.93

Solubility in Water:COMPLETE

Appearance and Odor:OILY FLUID, BLA

ND ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS

Stability Condition to Avoid: OPEN FLAMES, OTHER SOURCES OF IGNITION

Hazardous Decomposition Products: OXIDES OF CARBON

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. MANUFACTURER RECOMMENDS RECYCLING.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.