

SOUTHWESTERN PETROLEUM CORP. -- 306-10W30 SUPREME BLEND ENGINE -- 9150-01-345-6150
===== Product Identification =====

Product ID:306-10W30 SUPREME BLEND ENGINE
MSDS Date:03/24/1992
FSC:9150
NIIN:01-345-6150
MSDS Number: BPCGL
=== Responsible Party ===
Company Name:SOUTHWESTERN PETROLEUM CORP.
Address:534 N MAIN STREET
Box:789
City:FORT WORTH
State:TX
ZIP:76101
Country:US
Info Phone Num:817-334-23
36
Emergency Phone Num:800-424-9300 (CHEMTREC)
CAGE:14392
=== Contractor Identification ===
Company Name:SOUTHWESTERN PETROLEUM CORP
Address:534 N MAIN ST
Box:961005
City:FORT WORTH
State:TX
ZIP:76106
Country:US
Phone:817-348-7235
CAGE:14392

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM LUBRICATING OIL BASE STOCK
Fraction by Wt: >94%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3 AS OIL MIST
ACGIH TLV:5 MG/M3 AS OIL MIST

Ingred Name:ZINC DITHIO D

IPHOSPHATE/ZINC DIALKYL DITHIOPHOSPHATE (ZDDP)

CAS:68649-42-3

Fraction by Wt: 179C

Autoignition Temp:Autoignition Temp Text:>500F

Lower Limits:0.9

Upper Limits:7

Extinguishing Media:USE WATER SPRAY, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:USE WATER TO KEEP FIRE-EXPOSED CONTAINER COOLED. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURES. USE SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:WATER OR FOAM MAY CAUSE FROTHING. HYDROGEN

SULFIDE MAY BE PRODUCED ABOVE 121C.

===== Accidental Release Measures =====

Spill Release Procedures:USE INERT ABSORBENT MATERIAL TO CONFINE AND TO ABSORB MATERIAL. SCOOP INTO A DISPOSABLE CONTAINER.

Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY SUPPLIER

===== Handling and Storage =====

Handling and Storage Precautions:NO INFORMATION GIVEN ON MSDS BY SUPPLIER

Other Precautions:"NOT APPLICABLE"

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATORS TO MEET EXPOSURE LIMITS.

Ventilation:ADEQUATE VENTILATION

Protective Gloves:GLOVES

Eye Protection:GOGGLES OR FACE SHIELD

Other Protective Equipment:GLOVES AND OTHER PROTECTIVE CLOTHING.

Work Hygienic Practices:SUPPLIER DID NOT ADDRESS THIS FIELD.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>559F,

>293C
Vapor Density:>5
Spec Gravity:0.9
Solubility in Water:NO
Appearance and Odor:PURPLE, LUBE OIL ODOR
Percent Volatiles by Volume:NONE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS; AQS RELATED TO GENERAL ORGANIC MATERIALS.
Stability Condition to Avoid:STABLE BELOW 121C. AVOID HIGH HEAT, OPEN
FLAMES AND OTHER SOURCES OF IGNITION
Hazardous Decomposition Products:HYDROGEN SULFIDE MAY BE FORMED ABOVE
121C.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL OR INCINERATE AS FEDERAL, STATE AND
LOCAL LAWS AND REGULATIONS PERMIT.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to
be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.