

FARWEST PAINT MFG CO -- INTERIOR WIPING STAIN (WALNUT) -- 8010-00-597-8225

=====
Product Identification
=====

Product ID:INTERIOR WIPING STAIN (WALNUT)

MSDS Date:06/01/1992

FSC:8010

NIIN:00-597-8225

MSDS Number: BPFCV

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-8844

Emergency Pho

ne Num:206-941-1619

Preparer's Name:NORNA HABEEB

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====
Composition/Information on Ingredients
=====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

Fraction by Wt: >57%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PPM; 9293

=====

==== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: MAY CAUSE RESPIRATORY TRACT IRRITATION AND CENTRAL NERVOUS SYSTEM DEPRESSION IF VAPORS INHALED. MAY CAUSE SKIN AND EYE IRRITATION ON CONTACT. MAY BE HARMFUL IF SWALLOWED. CHRONIC: PROLONGED INHALATION OF VAPORS MAY CAUSE NERVOUS SYSTEM DAMAGE OR BRAIN DAMAGE. MAY CAUSE SKIN SENSITIZATION.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.

Effects of Overexposure:INHALED: COUGHING, WHEEZING, SHORTNESS OF BREATH, NAUSEA, DIZZINESS, DROWSINESS, HEADACHE. EYES: REDNESS, TEARING, DISCOMFORT. SKIN: DRYING, REDNESS OR RASH, ITCHING OR DISCOMFORT. INGESTED: NAUSEA, VOMITING, VOMIT MAY BE ASPIRATED CAUSING CHEMICAL PNEUMONIA.

Medical Condition Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

==== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHES. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. SEE DOCTOR. INHALED: REMOVE PERSON TO FRESH AIR. IF RESPIRATORY SYMPTOMS DEVELOP, GET IMMEDIATE MEDICAL HELP. INGESTED: DO NOT INDUCE VOMITING! GET IMMEDIATE MEDICAL ATTENTION.

==== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:104F,40C

Lower Limits:0.7%

Upper Limits:6.0%

Extinguishing Media:FOAM, DRY CHEMICAL, WATER FOG, CARBON DIOXIDE OR ANY CLASS "B" EXTINGUISHING AGENT.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. EVACUATE AREA OF NON-ESSENTIAL PEOPLE.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN AIR AND MAY BE IGNITED BY SPARKS OR OTHER IGNITION SOURCES. CLOSED CONTAINERS MAY RUPTURE IN FIRE

XTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. ABSORB SPILL WITH INERT MATERIAL AND PLACE IN A CONTAINER FOR LATER DISPOSAL. WEAR PROPER PROTECTIVE CLOTHING AND EQUIPMENT.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT OR OPEN FLAME.
KEEP CONTAINERS
CLOSED.

Other Precautions:DO NOT WELD, HEAT, BRAZE OR CUT CONTAINERS; EMPTY OR FULL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV EXCEEDED; USE NIOSH/MSHA APPROVED RESPIRATOR. IF RESPIRATOR IS USED; A PROGRAM IN ACCORDANCE WITH 29 CFR 1910.134 MUST BE IN PLACE.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION. LOCAL EXHAUST MAY BE NEEDED ON OCCASSION TO MAINTAIN REGULATORY EXPOSURE LIMITS.

Protective Gloves:NITRILE, NEOPRENE,
OR RUBBER

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER; PROTECTIVE CLOTHING TO PREVENT PROLONGED OR REPEATED CONTACT.

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>307F,>153C

Vapor Pres:2.6 MM HG

Vapor Densit

y:>1 (AIR=1)

Spec Gravity:0.9

Viscosity:>10

Evaporation Rate & Reference:65

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, STRONG ALKALIS, AND EPOXY HARDENERS.

Stability Condition to Avoid:HEAT, SPARKS, AND OPEN FLAMES.

Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD CARBON MONOXIDE AND TOXIC VAPORS.

===== Disposal Considerations =====

=====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. MATERIAL IS A RCRA IGNITABLE WASTE (40 CFR 261).

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.