

FALCON SAFETY PRODUCTS -- NO SCRATCH -- 6750-00-927-8672

===== Product Identification =====

Product ID:NO SCRATCH

MSDS Date:01/01/1990

FSC:6750

NIIN:00-927-8672

MSDS Number: BPFFY

=== Responsible Party ===

Company Name:FALCON SAFETY PRODUCTS

Address:25 CHUBB WAY

City:BRANCHBURG

State:NJ

ZIP:08876

Country:US

Info Phone Num:201-707-4900

Emergency Phone Num:201-707-4900

Preparer's Name:TIMOTHY J. COL

LITON

CAGE:19110

=== Contractor Identification ===

Company Name:FALCON SAFETY PRODUCTS EDWAL SCIENTIFIC PRODUCT

Address:25 CHUBB WAY

Box:1299

City:SOMERVILLE(BRANCHBURG)

State:NJ

ZIP:08876

Country:US

Phone:201-707-4900

CAGE:19110

===== Composition/Information on Ingredients =====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 10-20%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:350 PPM

ACGIH TLV:350 PPM/450STEL;939

4
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:TURPENTINE
CAS:8006-64-2
RTECS #:YO8400000
Fraction by Wt: 55-65%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM

Ingred Name:MINERAL OIL; (WHITE MINERAL OIL) (EXPOSURE REGULATED AS
'OIL MIST')
CAS:8012-95-1
RTECS #:PY8030000
Fraction by Wt: BALANCE
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3;10 STEL

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of
Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CHLOROCARBON MATLS HAVE PRODUCED
SENSIT OF MYOCARDIUM TO EPINEPHRINE IN LAB ANIMALS & COULD HAVE SIM
EFT IN HUMANS. ADRENOMETICS (E.G., EPINEPHRINE) MAY BE
CONTRAINDICATED EXCEPT FOR LIFE-SUSTAINING U SES IN HUMANS
ACUTELY/CHRONICALLY EXPOSED TO CHLOROCARBONS . INHAL MAY CAUSE RESP
IRRIT AND/OR (EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT
RELEVANT
Effects of Overexposure:HLTH HAZ:CNS DEPRESS. SYMPT OF OVEREXPOS MAY
INCLUDE HDCH, DIZZ, NAUS, UNCONSCIOUSNESS. PRLNGD/RPTD SKIN CONT
MAY LEAD TO DRYING & IRRIT. MAY CAUSE SENSIT DERM IN HYPERSENSITIVE
INDIV. POSS SKIN ABSOR B. EYE CONT IS IRRIT & MAY CAUSE DMG.
CHRONIC OVEREXPOS MAY CAUSE KIDNEY DMG.
Medical Cond Aggravated by Exposure:NONE KNOWN

===== First Aid Measures =====

First Aid:EYES:IMMED FLUSH W/LRG AMTS OF WATER FOR AT

LEAST 15 MIN
WHILE HOLDING EYELIDS OPEN. GET PROMPT MD ATTN. SKIN:REMOVE CONTAM
CLTHG & WASH SKIN W/PLENTY OF WATER. IF IRRIT PERSISTS, SEEK MD
ATTN. WASH C LTHG BEFORE REUSE. INHAL:MOVE VICTIM TOFRESH AIR &
RESTORE BRTHG IF NEC. STAY W/VICTIM UNTIL ARRIVAL OF EMERG MD
PERSONNEL. INGEST:CONT LOC POIS CTL CTR/MD IMMED!

===== Fire Fighting Measures =====

Flash Point:91.0F,32.8C
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL OR FOAM.
Fire F
ighting Procedures:WEAR NIOSH/MSHA APPROVED PRESSURE DEMAND SCBA
AND FULL PROTECTIVE EQUIPMENT . USE WATER SPRAY OR FOG TO COOL FIRE
EXPOSED CONTAINERS
Unusual Fire/Explosion Hazard:THERMAL DECOMPOSITION PRODUCTS MAY
INCLUDE HCL AND PHOSGENE . VAPORS CAN FLOW TO IGNITION SOURCES AND
FLASHBACK.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PERSONAL PROTECTIVE EQUIPMENT. REMOVE
HEAT AND IGNITION SOURCES, VENTILATE AREA, CLEA
N UP WITH INERT
ABSORBENT.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:FLAMM LIQ. STORE IN CLSD CNTR IN COOL,
WELL-VENT AREA. NOTE TO MD:DO NOT GIVE EPINEPHRINE-TYPE DRUGS.
Other Precautions:NO SMOKING IN AREA OF USE. DO NOT USE IN GENERAL
VICINITY OF ARC WELDING, OPEN FLAMES/HOT SURF. HEAT AND/OR UV
RADIATION MAY CAUSE FORMATION OF HCL AND/OR PHOSGENE .

===== E
xposure Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED, OR FOR SYMPTOMS OF
OVEREXPOSURE, WEAR NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC
VAPORS.
Ventilation:LOC EXHAUST MAY BE NEC UNDER SOME HANDLING/USE CNDTNS.
SPECIFIC NEEDS SHOULD BE ADDRESSED BY SUPERVISORY/HLTH (SUPDAT)
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:CHEM WORK GOGG/FULL LENGTH FCSHLD.
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:N

ONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

VENT:SAFETY PERSONNEL.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175F,79C

Vapor Pres:100

Vapor Density:3.9

Spec Gravity:1.15

Evaporation Rate & Reference:70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS.

Stability Condition to Avoid:HEAT, SPARKS AND OPEN FLAME.

Hazardous Decomposition Products:PHOSG

ENE . HYDROGEN CHLORIDE, CARBON

MONOXIDE, CARBON DIOXIDE, TRACES OF CHLORINE.

===== Disposal Considerations =====

Waste Disposal Methods:WASTE MAY BE BURNED IN AN APPROVED INCINERATOR,
OR DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever

r,

expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.