

LHB INDUSTRIES -- SO SURE MARINE CORPS GREEN #23,(64-341)

=====  
MSDS Safety Information  
=====

FSC: 8010  
NIIN: 00-948-7388  
MSDS Date: 04/23/1992  
MSDS Num: BPGCF  
Product ID: SO SURE MARINE CORPS GREEN #23,(64-341)  
MFN: 03  
Responsible Party  
Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LO  
UIS MO 63134  
Info Phone Number: 314-522-3141  
Emergency Phone Number: 314-522-3141 800-424-9300(CHEMTREC)  
Preparer's Name: RUDOLF OPPENHEIM  
Review Ind: Y  
Published: Y

=====  
Preparer Co. when other than Responsible Party Co.  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134

=====  
Contractor Summary  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134  
Phone: 314-522-3141

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: ENAMEL  
Specification Number: TT-E-527D  
Unit of Issue: BX  
Quantitative Expression: 00000000012EA  
UI Container Qty: 0  
=====

## Ingredients

---

Cas: 64475-85-0

RTECS #: PY8240000

Name: MINERAL SPIRITS

% Wt: 12.81

Other REC Limits: NONE SPECIFIED

OSHA PEL: 100 PPM

ACGIH TLV: 100 PPM

---

Cas: 7758-97-6

RTECS #: GB2975000

Name: LEAD CHROMATE (SARA 313)

% Wt: 3.20

Other REC Limits: NONE SPECIFIED

OSHA PEL: 0.05 MG(CR)/M3

ACGIH TLV: 0.05 MG(CR)/M3

---

Cas: 108-88-3

RTECS #: XS5250000

Name: TOLUENE (SARA 313)

% Wt: 14.66

Other REC Limits: NONE SPECIFIED

OSHA PEL: 200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Rpt Qty: 1000 LBS

DOT Rpt Qty: 1000 LBS

---

Cas: 67-64-1

RTECS #: AL3150000

Name: ACETONE (SARA 313)

% Wt: 22.35

Other REC Limits: NONE SPECIFIED

OSHA PEL: 1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Rpt Qty: 5000 LBS

DOT Rpt Qty: 5000 LBS

---

Cas: 74-98-6

RTECS #: TX2275000

Name: PROPANE

% Wt: 18.88

Other REC Limits: NONE SPECIFIED

OSHA PEL: 1000 PPM

ACG

IH TLV: 1000 PPM

-----  
Cas: 75-28-5

RTECS #: TZ4300000

Name: ISOBUTANE

% Wt: 7.43

Other REC Limits: NONE SPECIFIED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: 800 PPM  
-----

Cas: 106-97-8

RTECS #: EJ4200000

Name: N-BUTANE

% Wt: 4.64

Other REC Limits: NONE SPECIFIED

OSHA PEL: 800 PPM

ACGIH TLV: 800 PPM  
-----

RTECS #: 9999999VO

Name: VOC: 634 G/L

Other REC Limits: NONE SPECIFIED  
=====

==

Health Hazards Data

=====  
Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: YES

IARC: YES

OSHA: YES

Effects of Exposure: CONCENTRATE/INHALE CONTENTS HARMFUL-FATAL. REPORTS  
ASSOCIATE REPEATED/PROLONGED OCCUPATIONAL OVEREXPOSURE W/PERMANENT  
BRAIN/NERVOUS SYSTEM DAMAGE. CONFINED AREAS/HIGH CONCENTRATES-ANESTHETIC.  
IRRITATION: SKIN/RESPIRATORY TRACT. HARMFUL IF SWALLOWED. SEVERE EYE  
IRRITATION. CON

TAINS LEAD: CHRONIC EXPOSURE TO LEAD MAY \*

Explanation Of Carcinogenicity: RELATIVELY INSOLUBLE CHROMATES MAY CAUSE LUNG  
CANCER.\*

Signs And Symptoms Of Overexposure: IRRITATION TO EYES, THROAT, AND  
RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING. \*RESULT IN  
SEVERE DAMAGE TO BLOOD FORMING/NERVOUS/URINARY/REPRODUCTIVE SYSTEMS.

REPEATED/PROLONGED OVEREXP OSURE TO RELATIVELY INSOLUBLE CHROMATESMAY  
CAUSE  
LUNG CANCER.

Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS.

F

First Aid: SKIN/CLOTHES: WASH W/SOAP/WATER; WASH CLOTHES BEFORE REUSE. EYES: FLUSH W/WATER 15 MIN/CONTACT PHYSICIAN/OPHTHALMOLOGIST IMMEDIATELY. INGEST: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL AID. INHALE: MOVE TO FRESH AIR/ARTIFICIAL RESPIRATION IF NEEDED. MEDICAL AID. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====  
Handling and Disposal  
=====

Spill Release Procedures:

REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA.  
MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: IN ACCORDANCE W/APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT PUNCTURE/INCINERATE/STORE ABOVE 120F. EXPOSURE TO HEAT/PROLONGED EXPOSURE TO SUN: CONTAINER MAY BURST. DISCARD EMPTY CAN IN TRASH PICK-UP. DO NOT PLACE IN HOME TRASH COMPACTOR.

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN.

CAUTION-CONTENTS UNDER PRESSURE. DO NOT STORE ABOVE 120F. AVOID BREATHING

SPRAY/MIST/VAPOR. AVOID CONTACT W/EYES/SKIN.

Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION.

READ ENTIRE LABEL BEFORE USING. FOLLOW ALL LABEL DIRECTIONS. INTENTIONAL MISUSE BY CONCENTRATING AND INHALING OR SWALLOWING CONTENTS MAY BE HARMFUL OR FATAL.

=====  
Fire and Explosion Hazard Information  
=====

Flash Point Text: NR

Autoi

gnition Temp Text: 874F

Lower Limits: 1.8

Upper Limits: 9.5

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY.  
AVOID SPREADING ANY BURNING LIQUID WITH WATER SPRAY.

Fire Fighting Procedures: WATER INEFFECTIVE/USED TO COOL EXPOSED CONTAINERS.  
WEAR SELF-CONTAINED BREATHING APPARATUS. USE SHIELDING TO PROTECT FROM BURST/RUPTURE/VENT OF CONTAINERS.

Unusual Fire/Explosion Hazard: DO NOT SPRAY NEAR OPEN FLAME. AT ELEVATED TEMPERATURE (OVER 120F) CONTAINER MAY VENT, RUPTURE OR BURST. AEROSOL

CONTAINER: DO NOT EXPOSE TO TEMPS ABOVE 120F.

=====  
Control Measures  
=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.

Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL: ACCEPTABLE AT POINT OF MIST OR SPRAY RELEASE.

Protective Gloves: TO PROTECT SKIN

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHES

TO PROTECT SKIN. EYE WASH  
STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK OR SMOKE  
WHILE USING PRODUCT.

=====  
Physical/Chemical Properties  
=====

HCC: V3  
Vapor Pres: 60 @ 68F  
Vapor Density: >1.5  
Spec Gravity: .972 (WATER=1)  
Solubility in Water: INSOLUBLE  
Appearance and Odor: GREEN/PAINT  
Percent Volatiles by Volume: 82  
=====

=====  
Reactivity Data  
=====

Stability Indicator: YES  
Stability Condition To Avoid: EXTREME HEAT  
Hazardous Decomposition Products: CARBON MONOXIDE, AND POSSIBLE HYDROGEN  
CHLORIDE.  
Hazardous Polymerization Indicator: NO  
=====

Toxicological Information  
=====

Ecological Information  
=

=====  
MSDS Transport Information  
=====

Regulatory Information  
=====

Other Information  
=====

=====  
Transportation Information  
=====

Responsible Party Cage: 0FTT5  
Trans ID NO: 94409  
Product ID: SO SURE MARINE CORPS GREEN #23,(64-341)  
MSDS Prepared Date: 04/23/1992  
Review Date: 09/04/1992  
MFN: 3  
Multiple KIT Number: 0  
Review IND: Y  
Unit Of Issue: BX  
Container QTY: 0  
=====

=====  
Detail DOT Information  
=====

DOT PSN Code: DTJ  
Symbols:  
D  
DOT Proper Shipping Name: CONSUMER COMMODITY  
Hazard Class: ORM-D  
Label: NONE  
Non Bulk Pack: 156,306  
Bulk Pack: NONE  
Max Qty Pass: 30KGGROSS  
Max Qty Cargo: 30KGGROSS  
Vessel Stow Req: A  
=====

=====  
Detail IMO Information  
=====

IMO PSN Code: AKH  
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?  
IMDG Page Number: SEE 9022  
UN Number: 1950  
UN Hazard Class: 9?  
IMO Packaging Group: -  
Subsidiary Risk Label  
:-  
EMS Number: 2-13  
=====

=====  
Detail IATA Information  
=====

IATA PSN Code: ALS  
IATA UN ID Num: 1950  
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE  
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)  
IATA UN Class: 2.1  
IATA Label: FLAMMABLE GAS  
Packing Note Passenger: 203  
Max Quant Pass: 75KG  
Max Quant Cargo: 150KG  
Packaging Note Cargo: 203  
=====

Det

ail AFI Information

=====  
AFI PSN Code: ALS

AFI Proper Shipping Name: AEROSOLS, NONFLAMMABLE, N.O.S.

AFI PSN Modifier: CONTAINING SUBSTANCES IN CLASS 8, PACKING GROUP I OR II

AFI Hazard Class: FORB

Back Pack Reference: FORBIDDEN  
=====

HAZCOM Label

=====  
Product ID: SO SURE MARINE CORPS GREEN #23,(64-341)

Cage: 0FTT5

Company Name: LHB INDUSTRIES

S

Street: 8833 FLEISCHER PLACE

City: ST. LOUIS MO

Zipcode: 63134

Health Emergency Phone: 314-522-3141 800-424-9300(CHEMTREC)

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: CONCENTRATE/INHALE CONTENTS HARMFUL-FATAL. REPORTS  
ASSOCIATE REPEATED/PROLONGED OCCUPATIONAL OVEREXPOSURE W/PERMANENT  
BRAIN/NERVOUS SYSTEM DAMAGE. CONFINED AREAS/HIGH CONCENTRATES-ANESTHETIC.  
IRRITATION: SKIN/RESPIRATORY TRACT. HARMFUL

IF SWALLOWED. SEVERE EYE

IRRITATION. CONTAINS LEAD: CHRONIC EXPOSURE TO LEAD MAY \* IRRITATION TO  
EYES, THROAT, AND RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND  
VOMITING. \*RESULT IN SEVERE DAMAGE TO BLOOD

FORMING/NERVOUS/URINARY/REPRODUCTIVE SYSTEMS. REPEATED/PROLONGED  
OVEREXPOSURE

TO RELATIVELY INSOLUBLE CHROMATES MAY CAUSE LUNG CANCER.  
=====

Disclaimer (provided with this information by the compiling agencies): This  
inform

ation is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied  
warrants, states, or intends said information to have any application, use or  
viability by or to any person or persons outside the Department of Defense  
nor any person or persons contracting with any instrumentality of the United  
States of America and disclaims all liability for such use. Any person  
utilizing this instruction who is not a mil

itary or civilian employee of the

United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.