

MANSFILED OIL CO OF GAINESVILLE INC -- MID-GRADE GASOLINE -- 9130-01-272-0983

=====
Product Identification
=====

Product ID:MID-GRADE GASOLINE

MSDS Date:12/19/1986

FSC:9130

NIIN:01-272-0983

MSDS Number: BPGHZ

=== Responsible Party ===

Company Name:MANSFILED OIL CO OF GAINESVILLE INC

Address:1025 AIRPORT PKY SW

City:GAINESVILLE

State:GA

ZIP:30505-0198

Country:US

Info Phone Num:404-532-7571

Emergen

cy Phone Num:404-532-7571

CAGE:2Y744

=== Contractor Identification ===

Company Name:MANSFILED OIL CO OF GAINESVILLE INC

Address:1025 AIRPORT PKY SW

Box:City:GAINESVILLE

State:GA

ZIP:30505-0198

Country:US

Phone:404-532-7571

CAGE:2Y744

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: < 25% %

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT

Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: < 20% %

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL TERT-BUTYL ETHER (SARA III)

CAS:1634-04-4

RTECS #:KN5250000

Fraction by Wt: < 10% %

Other REC Limits:NONE RECOMMENDED

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fractio

n by Wt: < 5% %

Other REC Limits:NONE RECOMMENDED

OSHA PEL:1PPM/5STEL;1910.1028

ACGIH TLV:10 PPM; A2; 9293

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:HEXANE (N-HEXANE)

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: < 5% %

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:CYCLOHEXANE (SARA III)

CAS:110-82-7

RTECS #:GU6300000

Fraction by Wt: < 5% %

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM, 9

293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: < 5% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/125 STEL
ACGIH TLV:100 PPM/125STEL 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHALENE (SARA III)
CAS:91-20-3
RTECS #:QJ0525000
Fraction by Wt: < 5% %
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM/15 STEL
ACGIH TLV:10 PPM/15 STEL; 9293
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NOT SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:EYE IRRITATION, PROLONGED OR REPEATED
CONTACT MAY CAUSE SKIN IRRITATION, CENTRAL NERVOUS SYSTEM
DEPRESSION, PULMONARY EDEMA, BRONCHITIS, PNEUMONITIS.
Explanation of Carcinogenicity:PRODUCT MAY CONTAIN UP TO 4.9% BENZENE
WHICH IS
CLASSIFIED AS CARCINOGENIC TO HUMANS.
Effects of Overexposure:EYE IRRITATION, SKIN DEFATTING/DRYING,
HEADACHE, DIZZINESS, LOSS OF APPETITE, WEAKNESS, LOSS OF
COORDINATION, CONVULSIONS, DELIRIUM, HALLUCINATIONS, NUMBNESS IN
THE EXTREMITES, LOSS OF DEEP TENDON REFLEXES.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES: FLUSH IMMEDIATELY WITH WATER FOR 15 MINUTES. IF
IRRITATION

N PERSISTS, CONTACT PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. SEE DOCTOR IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR. IF NECESSARY RESUSCITATE. CALL A PHYSICIAN IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS; ASPIRATION HAZARD. CALL A PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point: