

POLY-CARB INC. -- MIL-P-2441 A SH 1C PRIMER MAR/C 80.1 A GREE -- 8010-01-350-4742
===== Product Identification =====

Product ID:MIL-P-2441 A SH 1C PRIMER MAR/C 80.1 A GREE
MSDS Date:02/14/1992
FSC:8010
NIIN:01-350-4742
Kit Part:Y
MSDS Number: BPGMF
=== Responsible Party ===
Company Name:POLY-CARB INC.
Address:33095 BAINBRIDGE
City:SOLOON
State:OH
ZIP:44139-2834
Country:US
Info Phone Num:216-248-12
23
Emergency Phone Num:216-248-1223
Preparer's Name:DR ARNEL D POTTER
CAGE:1T794
=== Contractor Identification ===
Company Name:POLY-CARB INC.
Address:33095 BAINBRIDGE
Box:City:SOLOON
State:OH
ZIP:44139-2834
Country:US
Phone:216-248-1223
CAGE:1T794

===== Composition/Information on Ingredients =====

Ingred Name:AMIDOAMINE RESIN
Other REC Limits:NONE SPECIFIED

Ingred Name:POLYAMIDE ADDUCT
Other REC Limits:NONE SPECIFIED

Ingred Name:N-BUTYL ALCOHOL
CAS:71-36-3
RTECS #:EO1400000

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE OVEREXPOSURE: IRRITATION OF EYES, SKIN AND MUCOUS MEMBRANE. CHRONIC OVEREXPOSURE: DAMAGE OF LIVER AND KIDNEYS. BURNS TO ABOVE CITED ORGANS; SENSITIZATION.

CORROSIVE, IRRITANT, SENSITIZER.

Medical Cond Aggravated by Exposure:ALLERGY, ECZEMA AND SKIN CONDITIONS.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING IS DIFFICULT. EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINS. CONSULT PHYSICIAN. SKIN: REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREA WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING. IF CONSCIOUS, GIVE WATER FOR DILUTION. CONSULT PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:105F,41C

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM OR WATER SPRAY.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WHEN FIRE FIGHTING. WATER MAY BE USED TO COOL CONTAINERS BY TRAINED FIREFIGHTERS.

Unusual Fire/Explosion Hazard:DENSE SMOKE EXPECTED. MAY FORM EXPLOSIVE MIXTURES WITH AIR DUE TO HEAT. DECOMPOSITION AND COMBUSTION PRODUCTS ARE TOXIC.

=====
===== Accidental Release Measures =====

Spill Release Procedures:FLAMMABLE LIQUID. REMOVE SOURCES OF IGNITION. TAKE UP WITH ABSORBENT MATERIAL. SHOVEL INTO CLOSEABLE CONTAINERS. FLUSH AREA WITH WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL DRY AREA AWAY FROM INCOMPATIBLE MATERIALS. AVOID CONTACT WITH EYES, SKIN OR CLOTHING BREATHING VAPOR. USE WITH GOOD V

ENTILATION.

Other Precautions:WEAR APPROPRIATE EQUIPMENT TO PREVENT EYE OR SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CHEMICAL CARTRIDGE RESPIRATOR.

Ventilation:LOCAL: YES; MECHANICAL (GENERAL): YES; SPECIAL: MAINTAIN GOOD VENTILATION.

Protective Gloves:SOLVENT RESISTANT.

Eye Protection:SPLASHPROOF GOGGLES.

Other Protective Equipment:PROTECTIVE CLOTHING (E.G., COVERALL), EYEWASH STATION AND SAFETY SHOWER.

Work Hygienic P

ractices:WASH AFTER HANDLING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>240F,>116C

Solubility in Water:INSOLUBLE

Appearance and Odor:GREEN COLOR LIQUID WITH ALCOHOL ODOR.

Percent Volatiles by Volume: