

GARDINER SOLDER CO DIV GARDINER METAL CO -- TIN LEAD ANTIMONY ALLOY: XM-200 CORE --
3439-01-026-1084

===== Product Identification =====

Product ID:TIN LEAD ANTIMONY ALLOY: XM-200 CORE

MSDS Date:05/01/1990

FSC:3439

NIIN:01-026-1084

MSDS Number: BPHPY

=== Responsible Party ===

Company Name:GARDINER SOLDER CO DIV GARDINER METAL CO

Address:4820 SOUTH CAMPBELL AVENUE

City:CHICAGO

State:IL

ZIP:60632-149

4

Country:US

Info Phone Num:312-847-0100

Emergency Phone Num:312-847-0100, CHEMTREC 800-424-9300

CAGE:84311

=== Contractor Identification ===

Company Name:GARDINER SOLDER CO, DIV OF GARDINER METAL CO

Address:4820 S CAMPBELL AVE

Box:City:CHICAGO

State:IL

ZIP:60632-1416

Country:US

Phone:312-847-0100/800-424-9300(CHEMTREC)

CAGE:56244

Company Name:GARDINER SOLDER COMPANY DIV GARDINER METAL CO

Address:4820 S CAMPBELL AVE

Box:City:CHICAGO

State:IL

ZIP:60632-1494

Country:US

Phone:312-847-0100 CHEMTRE

C AFTER HOURS

CAGE:84311

===== Composition/Information on Ingredients =====

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 5-94.8%

Other REC Limits:O.O3 MG/M3

OSHA PEL:0.05 MG/M3;1910.1025

ACGIH TLV:0.15 MG/M3;DUST 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:ANTIMONY (SARA III)

CAS:7440-36-0

RTECS #:CC4025000

Fraction by Wt: 0.2-2%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.5 MG/M3

Qty:5000 LBS

Ingred Name:TIN

CAS:7440-31-5

RTECS #:XP7320000

Fraction by Wt: 5-94.8%

Other REC Limits:NONE SPECIFIED

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9192

Ingred Name:ROSIN

CAS:8050-09-7

Fraction by Wt: 0.5-3%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.1MG/M3 FORMALDEHYD

ACGIH TLV:0.1MG/M3 FORMALDEHYD

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazar

ds Acute and Chronic:ACUTE-INHALATION OF FUMES(DURING

SOLDERING): IRRITATION OF EYES AND RESPIRATORY TRACT SYSTEM.

CHRONIC:LONG AND REPEATED EXPOSURE TO METAL FUMES MAY CAUSE

HEADACHE, NAUSEA/VOMITING, ACHING BONES, FATIG UE, DECREASED

APPETITE, ABDOMINAL CRAMPING, ANEMIA, BRAIN, HEART, LUNG, LIVER AND

KIDNEY DEGENERATIVE CHANGES.

Explanation of Carcinogenicity:FORMALDEHYDE IS LISTED AS A PROBABLE

CARCINOGEN BY NTP,IARC, EPA,& IT IS REGULATED BY OSHA.

Effects of Overexpos

ure:EXPOSURE TO FUMES MAY RESULT IN IRRITATION OF

NOSE, THROAT, EYES AND SKIN. BURNS FROM SKIN CONTACT OF MOLTEN

SOLDER. WATERY EYES, HEADACHE, BREATHING DIFFICULTY, FREQUENT

COUGHING.

Medical Cond Aggravated by Exposure:SOME WORKERS WITH PRE-EXISTING

CONDITIONS OF LUNGS, EYES, SKIN, AND THOSE PREVIOUSLY EXPOSED TO

LEAD & ANTMONY MAY BE AT INCREASED RISK.

===== First Aid Measures =====

First Aid:SKIN BURNS:FLUSH WITH COLD WATER OR APPLY

ICE. IN CASE OF
SEVERE BURNS GET MEDICAL HELP. EYE IRRITATION:FLUSH WITH WATER FOR
15 MINUTES. INHALATION:REMOVE TO FRESH AIR. ADMINISTER OXYGEN IF
BREATHING IS DIFFICULT. IF NOT BREATHING, BEGIN ARTIFICIAL
RESPIRATION. GET MEDICAL HELP. INGESTION:GET MEDICAL HELP.

===== Fire Fighting Measures =====

Extinguishing Media:DRY CHEMICAL. DO NOT USE WATER.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE E
QUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY DUST OR WASTE RESIDUES AND PLACE
IN SUITABLE DOT APPROVED CONTAINERS AND DISPOSE OF IN FULL
COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. AVOID
INHALATION A
ND SKIN EXPOSURE.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:NO SPECIAL REQUIREMENTS FOR STORAGE.
WEAR GLOVES AND FLAME RETARDANT CLOTHING WHEN SOLDERING.
Other Precautions:DO NOT BREATH FUMES WHILE SOLDERING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE FUME/ORGANIC VAPOR RESPIRATOR OR AIR
SUPPLIED RESPIRATOR WHEN SOLDERING IN A CONFINED SPACE OR WHERE
LOCAL EXHAUST OR GENERAL VENTILATION DOES NOT KEEP EXPOSURE BELOW
RECOMMENDED LIMITS. USE ONLY NIOSH APPROVED RESPIRATORS.
Ventilation:USE ENOUGH VENTILATION WHEN SOLDERING TO KEEP THE DUST,
FUMES & GASES BELOW TLV.
Protective Gloves:LEATHER GLOVES
Eye Protection:OSHA APPROVED GOGGLES/FACE SHIELD
Other Protective Equipment:FLAME RETARDANT CLOTHING AND LEATHER GLOVES
WHEN SOLDERING.
Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING OR SMOKING.
LAUNDER CONTAMINATIED CLOTHI

NG BEFORE REUSE.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:2516F,1380C
Melt/Freeze Pt:M.P/F.P Text:361F,183C
Vapor Pres:1 AT 1626F
Solubility in Water:INSOLUBLE
Appearance and Odor:SILVER GREY SOLID, ODORLESS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS. STRONG ACIDS.
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:TOXIC METAL FUMES ABOVE 886C(1627F).
FROM THE ROSIN CORE; FORMALDEHYDE, CARBON MONOXIDE & DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE &
LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.