View NSN Online: https://aerobasegroup.kr/nsn/5330-01-091-3342

## DARCO SOUTHERN INC -- COMPRESSED ASBESTOS-SBR BONDED WHITE -- 5330-01-091-3342

Product ID:COMPRESSED ASBESTOS-SBR BONDED WHITE

MSDS Date:01/01/1988

FSC:5330

NIIN:01-091-3342

MSDS Number: BPHRQ === Responsible Party ===

Company Name: DARCO SOUTHERN INC

Address:253 DARCO DRIVE

Box:454

City:INDEPENDENCE

State:VA ZIP:24348 Country:US

Info Phone Num:703-773-2711

Emerge

ncy Phone Num:703-773-2711

CAGE:3N264

=== Contractor Identification ===

Company Name: DARCO SOUTHERN INC

Address:253 DARCO DRIVE

Box:454

City:INDEPENDENCE

State:VA ZIP:24348 Country:US

Phone:703-773-2711

CAGE:3N264

======= Composition/Information on Ingredients ========

Ingred Name: ASBESTOS (FRIABLE) (SARA III)

CAS:1332-21-4 RTECS #:CI6425000 Fraction by Wt: 70-90%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:SEE 1910.1001 ACGIH TLV:0.2 - 2 FIBERS/CC

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

| Ingred Name:STYRENE-BUTADIENE POLYMER                                 |
|---|
| CAS:9003-55-8   |
| RTECS #:WL6478000   |
| Fraction by Wt: 8-15%   |
| Other REC Limits:NONE RECOMMENDED                                     |
| Other NEC Limits. NONE NECONINIENDED                                  |
| Ingred Name:TITANIUM DIOXIDE  |
| CAS:13463-67-7  |
| RTECS #:XR2275000   |
| Fraction by Wt: .5-1.5%   |
| Other REC Limits:NONE RECOMMENDED                                     |
| OSHA PEL:15 MG/M3 TDUST   |
| ACGIH TLV:10 MG/M3 TDUST; 9293  |
| 7.00m 12.10 mg/me 12.001, 02.00                                       |
| =========== Hazards Identification ==============                     |
|   |
| Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO                  |
| Reports of Carcinogenicity:NTP:YES                                    |
| Health Hazar  |
| ds Acute and Chronic:DUST FROM SHEET SHOULD BE TREATED AS             |
| FREE ASBESTOS. INHALATION- DYSPNEA, INTERSTITIAL FIBROSIS,            |
| RESTRICTED PULMONARY FUNCTION, FINGER CLUBBING. TARGET ORGAN:         |
| LUNGS.  |
| Explanation of Carcinogenicity:THIS MATERIAL CONTAINS ASBESTOS.       |
| Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.               |
| Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.  |
|   |
| ======================================                                |
| First Aid:FOR ASBESTOS DUST: EYES- IRRIGA                             |
| TE IMMEDIATELY WITH WATER.  |
| INHALATION- SEEK MEDICAL ATTENTION.                                   |
| INHALATION- SEEK MEDICAL ATTENTION.                                   |
| ======================================                                |
| i no i igitang medearee   |
| Extinguishing Media:WATER, CARBON DIOXIDE, DRY POWDER, OR FOAM.       |
| Fire Fighting Procedures:FIREFIGHTERS SHOULD USE SELF-CONTAINED       |
| BREATHING EQUIPMENT AND EYE PROTECTION FOR THE RUBBER FUMES.          |
| Unusual Fire/Explosion Hazard:THE RUBBER, ONCE IGNITED MAY NEED EXTRA |
| COOLING TO PREVENT REIGNITION.  |
|   |
| ========= Accidental Release Measures ========                        |

| Spill Release Procedures:WET SWEEP. DO NOT CLEAN UP IN A MANNER THAT<br>GENERATES DUST.<br>Neutralizing Agent:NONE   |
|--|
| ======================================   |
| Handling and Storage Precautions:DO NOT DRILL, SAW, GRIND, SAND OR SUBJECT TO ANY DUST PRODUCING PROCESS WITHOUT ADEQUATE DUST EXTRACTION OR DAMP DOWN.  Other Precautions:ASBESTOS IS BONDED BY ELASTOMER COMPOUND, HOWEVER, PROTECT AGAINST UNNECESSARY RELEASE OF FIBER WHEN CUTTING OR HANDLING.   |
| =<br>======= Exposure Controls/Personal Protection =========   |
| Respiratory Protection:WHEN DUST IS GENERATED USE NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS THAT HAS A FULL FACEPIECE AND IS OPERATED IN A PRESSURE-DEMAND OR OTHER POSITIVE-PRESSURE MODE. USE RESPIRATOR FOR ANY DETE CTABLE CONCENTRATION OF ASBESTOS. Ventilation:LOCAL EXHAUST AND MECHANICAL VENTILATION AS NEEDED. Protective Gloves:NOT REQUIRED.  Eye Protection:SAFETY GLASSES MAY BE WORN. Other Protective Equipm ent:NONE NORMALLY REQUIRED. Work Hygienic Practices:WASH DAILY AND CHANGE CLOTHES AFTER WORK IF THERE IS A REASONABLE PROBABILITY OF CONTAMINATION. Supplemental Safety and Health NONE. |
| ========== Physical/Chemical Properties ===========  |
| HCC:T6 Boiling Pt:B.P. Text:DECOMPOSES Spec Gravity:1.65-1.85 Solubility in Water:INSOLUBLE Appearance and Odor:OFF-WHITE, NO ODOR.  ===================================   |
| Stability Indicator/Materials to Avoid   |

:YES STRONG OXIDIZERS.

Stability Condition to Avoid:DIRECT FLAME WILL IGNITE ELASTOMER COMPOUND.

Hazardous Decomposition Products: CARBON MONOXIDE UNDER CERTAIN CIRCUMSTANCES. THERE MAY BE OTHERS UNKNOWN TO US.

======= Disposal Considerations ==========

Waste Disposal Methods:NORMAL LANDFILL, AS REQUIRED BY FEDERAL, STATE AND LOCAL REGULATIONS. WASTE MAY BE PLACED IN PLASTIC BAG TO REDUCE GENERATION OF ASBESTOS FIBER TO A MINIMUM.

Disclaimer (provided

with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.