

DARCO SOUTHERN, INC -- COMPRESSED ASBESTOS-SBR BONDED- WHITE -- 5330-01-194-8989  
===== Product Identification =====

Product ID:COMPRESSED ASBESTOS-SBR BONDED- WHITE

MSDS Date:01/01/1987

FSC:5330

NIIN:01-194-8989

MSDS Number: BPHST

=== Responsible Party ===

Company Name:DARCO SOUTHERN, INC

Address:253 DARCO DRIVE

Box:454

City:INDEPENDENCE

State:VA

ZIP:24348

Country:US

Info Phone Num:703-773-2711

Em

ergency Phone Num:703-773-2711 OR 703-236-8913

Preparer's Name:JILL M. BURCHAM

CAGE:EO059

=== Contractor Identification ===

Company Name:DARCO SOUTHERN INC

Address:253 DARCO DRIVE

Box:454

City:INDEPENDENCE

State:VA

ZIP:24348

Country:US

Phone:703-773-2711

CAGE:3N264

Company Name:DARCO SOUTHERN, INC.

Box:454

CAGE:EO059

===== Composition/Information on Ingredients =====

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 0.5-1.5%

Other REC Limits:NONE R

ECOMMENDED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:ASBESTOS (FRIABLE) (SARA III)  
CAS:1332-21-4  
RTECS #:CI6425000  
Fraction by Wt: 70-90%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:SEE 1910.1001  
ACGIH TLV:0.2 - 2 FIBERS/CC  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:STYRENE POLYMER WITH 1,3-BUTADIENE  
CAS:9003-55-8  
RTECS #:WL6478000  
Fraction by Wt: 8-15%  
Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of

Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:ACUTE HAZARDS ARE NOT EXPECTED WITH THIS MATERIAL, EXCEPT FOR SKIN IRRITATION DUE TO TRAUMA. CHRONIC HAZARDS IN ORDER OF INCREASING SEVERITY ARE: ASBESTOSIS, LUNG CANCER, & MESOTHELIOMA, ALL OF WHICH ARE DISABLING AND FATAL DISEASES OF THE LUNG. INHALATION AND INGESTION OF ASBESTOS FIBERS MAY CAUSE CANCER OF THE BOWEL.

Explanation of Carcin

ogenicity:ASBESTOS IS A KNOWN HUMAN CARCINOGEN.

Effects of Overexposure:FATIGUE AND SHORTNESS OF BREATH THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING.

Medical Cond Aggravated by Exposure:ASTHMA, EMPHYSEMA, AND TUBERCULOSIS ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

=====  
===== First Aid Measures =====

First Aid:SUPPORTIVE CARE AND TREATMENT OF TRAUMA ARE THE ONLY FIRST AID PROCEDURES SUITABLE FOR EXPOSURE TO ASBESTOS.

=====  
Fire Fighting Measures  
=====

Extinguishing Media:USE WATER, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.  
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS FOR THE RUBBER FUMES.  
Unusual Fire/Explosion Hazard:THE RUBBER, ONCE IGNITED MAY NEED EXTRA  
COOLING TO PREVENT REIGNITION.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:VACUUM THE MATERIAL WITH A HEPA FILTERED  
VACUUM. THE EQUIPMENT SHALL BE USED & EMPTIED SO AS TO MINIMIZE THE  
RE-ENTRY OF ASBESTOS INTO THE WORKPLACE. OTHERWISE, WET THE  
MATERIAL WITH WATER & SURFACTANT AND THEN SHOVEL OR MOP UP  
CONTAMINATION.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:GASKET IS NONFRIABLE & WILL NOT SHED  
FIBERS IN NORMAL USE AND STORAGE. DO NOT DRILL, SAW, GRIND, SAND OR  
CAUSE DUST WITHOUT DUST EXTRACTION OR DAM

P.  
Other Precautions:IF IT IS NECESSARY TO CUT OR IMPACT THE GASKET WHILE  
INSTALLING IT, WEAR A RESPIRATOR AND PROTECTIVE CLOTHING. USED  
GASKETS SHALL BE IDENTIFIED AND DISPOSED OF IN ACCORDANCE WITH ALL  
LOCAL, STATE AND FEDERAL REGULATIONS.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF  
REQUIRED WHEN CUTTING LARGE QUANTITIES. WEAR SELF-CONTAINED  
BREATHING APPARATUS IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES.  
Ventilation:LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTICULATE  
EMISSIONS. HEPA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN.  
Protective Gloves:COTTON OR LEATHER  
Eye Protection:SAFETY GLASSES OR GOGGLES  
Other Protective Equipment:USE COVERALLS OR DISPOSABLE CLOTHING.  
Work Hygienic Practices:WORK WET TO THE DEGREE POSSIBLE. WASH HANDS  
AFTER HANDLING GASKET. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.  
Supplemental Safety and Health  
ARRANGEMENTS SHOULD BE MADE

E TO REPLACE THIS GASKET WITH A SUBSTITUTE  
THAT DOES NOT CONTAIN ASBESTOS.

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:1.65-1.85

Solubility in Water:INSOLUBLE

Appearance and Odor:OFF WHITE- NO ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:DIRECT FLAME WILL IGNITE ELASTOMER  
COMPOUND

Hazardous Decomposition Products:ASB

ESTOS DUST, CARBON MONOXIDE UNDER

CERTAIN CIRCUMSTANCES. THERE MAY BE OTHERS UNKNOWN TO THE  
MANUFACTURER.

===== Disposal Considerations =====

Waste Disposal Methods:WET THE MATERIAL WITH WATER AND SURFACTANT.  
PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS  
INTO ANOTHER POLY BAG OR A SAFE PLACE UNTIL IT CAN BE SHIPPED TO AN  
APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING  
LABEL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.