

OLIN CORPORATION -- CPE00251# CHLORINE -- 6830-00-169-0783

=====
Product Identification
=====

Product ID:CPE00251# CHLORINE

MSDS Date:09/04/1997

FSC:6830

NIIN:00-169-0783

MSDS Number: BPHXZ

=== Responsible Party ===

Company Name:OLIN CORPORATION

Address:501 MERRITT 7

Box:4500

City:NORWALK (FORMALLY IN STAMFORD,CT)

State:CT

ZIP:06856-4500

Country:US

Info Phone Num:203-750-3000/203-750-3543

Emergenc

y Phone Num:800-654-6911/203-356-2000

Preparer's Name:OLIN MSDS CNTRL GROUP

CAGE:99530

=== Contractor Identification ===

Company Name:OLIN CORPORATION

Address:501 MERRITT 7

Box:4500

City:NORWALK

State:CT

ZIP:06856-4500

Country:US

Phone:203-750-3000/800-511-MSDS

CAGE:99530

=====
Composition/Information on Ingredients
=====

Ingred Name:CHLORINE (SARA 302/313) (CERCLA)

CAS:7782-50-5

RTECS #:FO2100000

Fraction by Wt: 98-100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:C 1 PPM

ACGI

H TLV:0.5 PPM/1 STEL; 9596

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50:NOT AVAIL-GAS @ROOM TEMPERATURE

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:HARMFUL IF INHAL.CAUSES EYE/SKIN/RESP

TRACT BURNS.CAN CAUSE LUNG DMG.ODOR THRESHOLD:APPROX

1.7MG/M3(0.3PPM).IDLH=10PPM.EYE:RED,PAIN,BLUR VISION,TEAR.LIQ C

AUSE

BURNS W/VISION IMPAIR,CORNEAL DMG.SKIN:IRRIT,RED,SWELL,SCAB

FORM.LIQ BURNS,PROL CONTACT CAUSES DERMIS DESTRUCTION W/IMPAIR

SKIN.INGEST:IRRIT/BURNS GI(AGGRAV MED)

Explanation of Carcinogenicity:PER MSDS:NOT KNOWN OR REPORTED TO BE

CARC BY ANY REF SOURCE INCLUDING IARC/OSHA/NTP/EPA.

Effects of Overexposure:ACUTE:INHAL IRRIT NOSE/MOUTH/THROAT/LUNGS.MAY

CAUSE INFLAMM TO RESP TRACT W/PRODUCTION OF LUNG EDEMA-SHORTNESS OF

BREATH,WHEEZ,CHOKE,CHEST PAIN,IMPARI LUNG FUNCTIO

N.HI LEVELS CORRO

TO RESP TRACT,LUNG DMG.CHRONIC:REP INHAL EXPO MAY CAUSE IMPAIRMENT

OF LUNG FUNCTION & PERM LUNG DMG.MAY CONTRIBUTE TO DEVELOPMENT OF

BRONCHITIS.

Medical Cond Aggravated by Exposure:ASTHMA AND RESPIRATORY AND

CARDIOVASCULAR DISEASE. HEALTH:TRACT,NAUSEA,VOMIT,DIARR,ABD

PAIN,BLEEDING,TISSUE ULCERATION.

===== First Aid Measures =====

First Aid:EYE:IMMED FLUSH W/LG AMTS OF H2O @LEAST 15MINS,LIT

UPPER/LOWER EYELIDS.CALL DR @ONCE.

SKIN:IMMED FLUSH W/H2O @LEAST

15MINS.CALL DR.CLOTH CONTACT PROD SHOULD BE REMOVED

IMMED.INGEST:IMMED DRINK LG QUANT OF H2O.DONT INDUCE VOMIT.CALL DR

@ONCE.DONT GIVE ANYTHING BY MOUTH IF

UNCONSC/CONVULS.INHAL:NAUSEA,HEAD,DIZZ STOP WORK IMMEDIATE,MOVE TO FRESH

AIR TIL SYMPT DISAPPEAR.BREATH DIFF GIVE OXY.CALL DR.(SUPPLEMENT)

===== Fire Fighting Measures =====

Flash Point:NA

Autoignition Temp:Autoignition Temp Text:NP

Lower Limits:NA

Upper Limits:NA

E

Extinguishing Media:USE EXTINGUISHING MEDIA COMPATIBLE TO SURROUNDING MATERIALS.

Fire Fighting Procedures:USE WATER TO COOL CNTNR EXPO TO FIRE HOWEVER DIRECT SPRAY BETWEENFIRE/CNTNR.DONT SPRAY DIRECTLY ON CNTNR UNLESS ABSOLUTELY NECESSARY.H2O REACTIVE MATL;DONT(SUP)

Unusual Fire/Explosion Hazard:OXIDIZER.WATER REACTIVE.CORROSIVE.

===== Accidental Release Measures =====

Spill Release Procedures:ALL TRANSP ACCIDENT:800-424-9300 CHEMTREC.SUBJ TO RQ W/RES

PECT TO CL2.REF:40CFR302.4.HAZ CONC IN AIR MAY BE FOUND IN SPILL AREA/IMMED DOWNWIND.DONT PUT H2O ON PROD-GAS EVOLU INCR.EXPLO HAZ IF CONTACT W/INCOPAT MATL.REMOVE ALL IGN SOURCES.(DISPO)

Neutralizing Agent:MATL MAY BE NEUTRALIZED FOR DISPO;YOUR REQUESTED TO CALL OCEAN 800-OLIN-911.

===== Handling and Storage =====

Handling and Storage Precautions:DONT TAKE INTERNALLY.AVOID CONTACT W/SKIN/EYE/CLOTHING.UPON CONTACT W/SKIN/EYES WASH OFF W/WATER.DONT

BREATHE GAS/VAP.STORE IN COOL DRY WELL VENTI PLC

Other Precautions:DONT STORE @TEMPS ABOVE 59C/140F.SHELF LIFE LIMITATIONS:INDEF.TITNAIUM WILL RX VIGOROUSLY RESULTING IN SPONT IGN WHEN CONTACT BY DRY CHLORINE.COMBUST WILL BE SUPPORTED IN CARBON STEEL SYS/EQPMT W/CHLR INE ENVIRO @TEMPS >340F.PROPERLY(SUPPLE)

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF AIR CONCENTRATIONS ABOVE TLV POSSIBLE WEAR NIOSH/MSHA APPROVE

D RESPIRATOR.WEAR NIOSH/MSHA APPROVED FULL-FACE RESPIRATOR EQUIPPED W/CHEM CARTRIDGES FOR CHLORINE GAS.

Ventilation:USE LOCAL EXHAUST VENTILATION TO MAINTAIN LEVELS TO BELOW TLV.

Protective Gloves:WEAR GLOVES-NEOPRENE,BUTYL RUBBER

Eye Protection:FACE SHIELD W/SAF GLASSES.

Other Protective Equipment:WEAR BOOTS,APRON-NEOPRENE.FULL IMPERM SUIT RECOMMENDED IF EXPO POSSIBLE TO LG PORTION OF BODY.EMER EYEWASH,SAF SHOWER

Work Hygienic Practices:LAUNDER CONTAM CLOTH BEF REUSE.PROTECTION

CONCERNS MUST ADDRESS POT OF PHYS CHARACT OF PROD-COMPRESSED GAS,CORR,POISON.

Supplemental Safety and Health

FIRE/EXPLO:SPRAY W/H2O.CONTACT W/RX METLAS(AL)MAY RESULT IN GENERATION OF FLAMM H2 GAS. INCOMPAT:TITANIUM,ZN,TIN.ALKALIES,RED AGENTS,ORG MATLS. OTHER PRECAUT:PURGE SYSTEMS/EPQMT PRIOR TO CONDUCTING HO T WORK. 1STAID:INHAL VAP UNCONSC,MOVE IMMED TO FRESH AIR,CALL DR IMMED.STOP BREATH-ART RESP.ADE VENTI/RESP BEF WORKING.

===== Physical/Chemical Properties =====

HCC:G7

Boiling Pt:B.P. Text:-29F,-34C

Melt/Freeze Pt:M.P/F.P Text:149F,65C

Decomp Temp:Decomp Text:NONE

Vapor Pres:114PSI

Vapor Density:2.5

Spec Gravity:NA

pH:NA

Viscosity:NP

Evaporation Rate & Reference:HEAT OF VAP 123.67BTU/LB

Solubility in Water:MISCIBLE

Appearance and Odor:GREENISH LIQUID OR GAS, PRODUCT IS COMPRESSED GAS, ACRID ODOR

Percent Volatiles by Volume:100

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability

Indicator/Materials to Avoid:YES

NOTICE-SHOULDNT BE REPKG EXCEPT BY QUALIFIED/TRAIN

PERSONNEL.ALKALIS,REDUCING AGENTS,ORG MATLS.RXS VIGOROUSLY W/(SUPPLE)

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:HYDROCHLORIC ACID, HYPOCHLOROUS ACID

===== Disposal Considerations =====

Waste Disposal Methods:SPILL:SURPRES VAP W/H2OFOG.CONTAIN

FOG-NEU/TREAT.CL2 SINK IN H2O,BUBBLE TO FORM HYPOCHLOROUS ACID-SELF

DECOMPO.DIVERT TO HOLD AREA-TREAT/NEU.LAND-DIKE,COVER
W/FOAM.NEU.WEAR PPE. WASTE-EPA D003,D001.SU BJ TO 40CFR268.CNTRL
EVAPO WARRANT.TPQ:100LBS.SARA

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.