View NSN Online: https://aerobasegroup.kr/nsn/5330-00-567-4878

FLEXITALLIC GASKET CO INC -- ASBESTOS FILLED SPIRAL WOUND GASKET -- 5330-00-567-4878

Product ID:ASBESTOS FILLED SPIRAL WOUND GASKET MSDS Date:07/09/1986 FSC:5330 NIIN:00-567-4878 **MSDS Number: BPJDC** === Responsible Party === Company Name: FLEXITALLIC GASKET CO INC Address:6915 LAPORTE RD Box:760 **City:DEER PARK** State:TX ZIP:77536 Country:US Info Phone Num:713-479-34 91 Emergency Phone Num:713-479-3491 CAGE:58156 === Contractor Identification === Company Name: FLEXITALLIC GASKET CO INC. Address:6915 LAPORTE RD Box:760 City:DEER PARK State:TX ZIP:77536 Country:US Phone:713-479-3491 CAGE:58156 Company Name: TURBODYNE, DIV OF MCGRAW EDISON CO/DRESSER INDUST. Address:142 CLINTON RD Box:City:FAIRFIELD State:NJ ZIP:07004-2969 Country:US Phone:201-227-4565 CAGE:51219

Ingred Name: ASBESTOS, CHRYSOTI

LE CAS:12001-29-5 RTECS #:CI6478500 Other REC Limits:NONE RECOMMENDED OSHA PEL:0.2 FIBERS/CC ACGIH TLV:2 FIBERS/CC; A1;9293

LD50 LC50 Mixture:PEL FOR ASBESTOS FIBERS 0.2 FIBER/CC Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:ACUTE AND CHRONIC- BREATHING OF ASBESTOS FIBERS IN SIGNIFICANT AMOUNTS MAY PRODUCE IRREVERSIBLE

LUNG DISEASE AND CANCER. FREE FIBERS CAN CAUSE EYE AND SKIN IRRITATION. INGESTION IS NOT LIKELY.

Explanation of Carcinogenicity: CONTAINS ASBESTOS.

Effects of Overexposure:BREATHING OF ASBESTOS FIBERS IN SIGNIFICANT AMOUNTS MAY PRODUCE IRREVERSIBLE LUNG DISEASE AND CANCER. FREE FIBERS CAN CAUSE EYE AND SKIN IRRITATION. INGESTION IS NOT LIKELY.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS OR EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCTION MAY BE MO

RE SUSCEPTIBLE TO THE EFFECTS OF THE SUBSTANCE.

First Aid:GET MEDICAL ATTENTION IF NEEDED. SKIN:WASH WITH SOAP & WATER. EYE:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. INHALED:REMOVE TO FRESH AIR. PROVIDE OXYGEN/CPR IF NEEDED. ORAL:CALL A PHYSICIA N.

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, FOAM OR DRY CHEMICAL FOR SURROU NDING FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Spill Release Procedures: VACUUM FIBERS AND DUSTS, CAREFULLY, AVOIDING DUSTING. IF SWEEPING IS USED, CONTROL DUST BY WETTING AND USE APPROPRIATE DUST MASK.

Handling and Storage Precautions:STORAGE- NOT RELEVANT FOR A FINISHED PRODUCT IN SPIRAL WOUND GASKET. Other Precautions:SEE OTHE R REGULATIONS FOR ASBESTOS HANDLING IN CFR 29, PART 1910, SUB PART 2, PAR. 1910.1001. DO NOT BREATHE DUST OR FIBERS. WASH THOROUGHLY AFTER HANDLING.

Respiratory Protection:NONE REQUIRED WHERE ADEQUATE VENTILATION CONDITIONS EXIST. IF EXCESSIVE DUSTS OR FIBERS PRESENT, A NIOSH-APPROVED DUST RESPIRATOR IS RECOMMENDED. IF CONCENTRATION EXCEEDS CAPACITY OF RESPIRATOR, USE S ELF-CONTAINED BREATHING APPARATUS

Ventilation:MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).
Protective Gloves:RUBBER RECOMMENDED
Eye Protection:SAFETY GOGGLES
Other Protective Equipment:EYE WASH STATION, QUICK DRENCH SHOWER AND IMPERVIOUS CLOTHING
Work Hygienic Practices:KEEP WORK AREA CLEAN OF ASBESTOS DUST.
Supplemental Safety and Health

HCC:T6
Spec Gravity:2.5
Solubility in Water:NEGLIGIBLE
Appearance an
d Odor:LIGHT BLUE - NO ODOR

Stability Indicator/Materials to Avoid:YES NONE KNOWN Hazardous Decomposition Products:NONE KNOWN

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Dep artment

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.