

YARDNEY TECHNICAL PRODUCTS, INC -- LISOCL2 BATTERY HT (HIGH TEMPERATURE) --
6135-01-357-0621

===== Product Identification =====

Product ID:LISOCL2 BATTERY HT (HIGH TEMPERATURE)

MSDS Date:10/18/1990

FSC:6135

NIIN:01-357-0621

MSDS Number: BPLBM

=== Responsible Party ===

Company Name:YARDNEY TECHNICAL PRODUCTS, INC

Address:82 MECHANIC STREET

City:PAWCATUCK

State:CT

ZIP:06379

Country:US

Info Phone Num

:203-599-1100

Emergency Phone Num:203-599-1100

CAGE:87326

=== Contractor Identification ===

Company Name:YARDNEY TECHNICAL PRODUCTS INC

Address:82 MECHANIC ST

Box:City:PAWCATUCK

State:CT

ZIP:06379

Country:US

Phone:203-599-1100

CAGE:87326

Company Name:YARDNEYTECHNICAL PRODUCTS INC.

Address:82 MECHANIC ST

Box:City:PAWCATUCK

State:CT

ZIP:06379

Country:US

Phone:203-599-1100

CAGE:0RKK3

===== Composition/Information on Ingredients =====

Ingred Name:THIONYL CHLORIDE

CAS:7719-09-7

RT

ECS #:XM5150000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:C 1 PPM
ACGIH TLV:C 1 PPM; 9192

Ingred Name:LITHIUM METAL
CAS:7439-93-2
RTECS #:OJ5540000
Other REC Limits:NONE RECOMMENDED

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NO INFORMATION GIVEN ON MSDS BY MFR.
Health Hazards Acute and Chronic:UNDER NORMAL CONDIT
IONS;NONE. IN EVENT
OF AN ACCIDENT;CORROSIVE FUMES WILL INJURE ANY EXPOSED ITSSUE.
PULMONAAAARY EDEMA MAY OCCUR SEVERAL HOURS AFTER SEVERE EXPOSURE TO
FUMES.
Explanation of Carcinogenicity:THE PRODUCT CONTAINS NO INGREDIENT THAT
IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.
Effects of Overexposure:IN EVENT OF ACCIDENT:THIONYL CHLORIDE FUMES ARE
CORROSIVE AND WILL INJURE EYES, MUCOUS MEMBRANES AND LUNGS.
Medical Cond Aggravated by Exposure:RESPIRATORY ILLNESS AND SKIN
CON
DITIONS.

=====
===== First Aid Measures =====

First Aid:FOR CONTACT WITH LITHIUM, THIONYL CHLORIDE OR CARBON
BLACK:FLUSH WITH COPIOUS AMOUNTS OF WATER.

=====
===== Fire Fighting Measures =====

Extinguishing Media:LITH-X OR OTHER METAL FIRE EXTINGUISHER POWDER
(CLASS D).
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS AND
PROTECTIVE CLOTHING MUST BE USED. DO NOT USE WATER.
Unusual Fire/Explosion Hazard:BATTERY

MAY RUPTURE VIOLENTLY WHEN
EXPOSED TO FIRE OR TEMPERATURES ABOVE 355F.

===== Accidental Release Measures =====

Spill Release Procedures: THIONYL CHLORIDE SPILLS SHOULD BE NEUTRALIZED
WITH A SOLUTION OF SODA ASH. DISPOSE OF REMAINING LIQUID I/A/W
ENVIRONMENTAL REGULATIONS.

Neutralizing Agent: SOLUTION OF SODA ASH.

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN TEMPERATURES BELOW
302F/150

C. STORE SO THAT TERMINALS DO NOT SHORT CIRCUIT.

Other Precautions: DO NOT PUNCTURE, DISASSEMBLE, OR INCINERATE THE
BATTERY. DO NOT CHARGE THE BATTERY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: A HALF-MASK OR FULL FACE RESPIRATOR WITH ACID
GAS CARTRIDGES SHOULD BE AVAILABLE.

Ventilation: UNDER NORMAL CONDITIONS: NONE. IN ACCIDENT: VENT WORK AREA
TO CLEAR FUMES. IF POSSIBLE VENT THROUGH A SCRUBBER.

Protective Gloves: UNDER NORMAL CONDITIONS: NONE.

Eye Protection: UNDER NORMAL CONDITIONS: NONE.

Other Protective Equipment: IN EVENT OF ACCIDENT: WEAR SPLASH GOGGLES,
RUBBER GLOVES, AND ACID RESISTANT CLOTHING AND RESPIRATOR.

Work Hygienic Practices: WASH THOROUGHLY AFTER WORKING WITH THIS OR ANY
OTHER BATTERY.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC: F8

NRC/State Lic Num: NONE

Appearance and Odor: MFR SAID "N/A". TIR SAYS BUTTON DRY CELL BATTERY,
1.380 IN O.D.

X 2.420 IN LONG

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

DO NOT IMERSE IN WATER

Stability Condition to Avoid: DO NOT EXPOSE TO TEMPERATURES ABOVE 302F/150C, PUNCTURE, SHORT CIRCUIT, OR CHARGE.

Hazardous Decomposition Products: LITHIUM METAL BURNS IN AIR TO FORM CAUSTIC LITHIUM OXIDE SMOKE. THIONYL CHLORIDE HYDROLYZES TO HCL AND SO2.

Conditions to Avoid Polymerization: WILL NOT OCCUR

===== Disposal

Considerations =====

Waste Disposal Methods: SPENT BATTERIES CONTAIN RESIDUAL ELECTROLYTE AND MAY CONTAIN RESIDUAL LITHIUM METAL AND MUST BE DISPOSED OF IN ACCORDANCE WITH ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

d

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.