

BURKE INDUSTRIES -- PVC GRAPHITE TILE -- 9330-00-489-1781

===== Product Identification =====

Product ID:PVC GRAPHITE TILE

MSDS Date:11/19/1987

FSC:9330

NIIN:00-489-1781

MSDS Number: BPMHB

=== Responsible Party ===

Company Name:BURKE INDUSTRIES

Address:2250 S 10TH

Box:190

City:SAN JOSE

State:CA

ZIP:95103

Country:US

Info Phone Num:408-297-3500

Emergency Phone Num:408-297-3500

CAGE:96780

=== Contract

or Identification ===

Company Name:BURKE INDUSTRIES

Address:2250 S 10TH

Box:190

City:SAN JOSE

State:CA

ZIP:95103

Country:US

Phone:408-297-3500

CAGE:96780

===== Composition/Information on Ingredients =====

Ingred Name:GRAPHITE, NATURAL (* MFR LISTS 3 CLASSES OF NATURAL
GRAPHITE THE SUM TOTAL CONTENT EQUALS 121%!)
CAS:7782-42-5
RTECS #:MD9659600
Fraction by Wt: *
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MPPCF RDUST
ACGIH TLV:2 MG/M3 RDUST; 9293

Ingred Name:VINYL CHLO

RIDE (SARA III)
CAS:75-01-4
RTECS #:KU9625000
Fraction by Wt: TRACE
Other REC Limits:NONE RECOMMENDED
OSHA PEL:SEE 1910.1017
ACGIH TLV:5 PPM, A1; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:VINYL ACETATE (SARA III)
CAS:108-05-4
RTECS #:AK0875000
Fraction by Wt: TRACE
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM/15 STEL
ACGIH TLV:10 PPM/15,A3 STEL;93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inh
alation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Explanation of Carcinogenicity:"NOT APPLICABLE"
Effects of Overexposure:"NOT APPLICABLE"
Medical Cond Aggravated by Exposure:PNEUMOCONIOSIS. SAX REPORTS CASES
OF FIBROSIS, EMPHYSEMA AND CORPULMONALE FROM PROLONGED INHALATION
OF GRAPHITE DUST.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/CLEAN WATER 15 MIN, HOLD LIDS OPEN. EXCESS
INHALATION:REMOVE FR
OM EXPOSURE.

===== Fire Fighting Measures =====

Extinguishing Media:CARBON DIOXIDE, CHEMICAL FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures:SUPPLIER LEFT THIS FIELD BLANK.
Unusual Fire/Explosion Hazard:WHEN HEATED TO DECOMPOSITION, EMITS TOXIC
FUMES AND VAPORS. FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED
BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING.

===== Accidental Release Measures =====

Spill Release Procedures:SWEEP U

P OR VACUUM THOROUGHLY AS POWDERED
GRAPHITE IS A LUBRICANT AND THEREFORE SLIPPERY.
Neutralizing Agent:NO INFORMATION GIVEN BY MFR ON THE MSDS.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID EXCESSIVE HEAT AND OPEN FLAME.
Other Precautions:GRAPHITE IS ELECTRICALLY CONDUCTIVE. USE GOOD
HOUSEKEEPING PRACTICE TO PREVENT CONTAMINATION OF ELECTRICAL
DEVICES.

===== Exposure Controls/Personal Protection =====

R
Respiratory Protection:NONE
Protective Gloves:COTTON
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING TILES.
Supplemental Safety and Health
MSDS RECEIVED FROM NAVY (FOCAL POINT N). NAVY IDENTIFIED NSN.

===== Physical/Chemical Properties =====

HCC:N1
NRC/State Lic Num:NONE
Spec Gravity:1.65
Appearance and Odor:BLACK RIGID HOMOGENOUS FLUXED 12X12 TILE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:SUPPLIER LEFT THIS FIELD BLANK.
Hazardous Decomposition Products:MAY FORM TOXIC FUMES AND VAPORS. HCL,
CO, CO2 AND ACETIC ACID WHEN HEATED TO DECOMPOSITION.
Conditions to Avoid Polymerization:WILL NOT OCCUR

===== Disposal Considerations =====

Waste Disposal Methods:DEPOSITE IN LANDFILL I/A/W FEDERAL, STATE &
LOCAL REGULATIONS, NOT BY INCINERATION.

Disclaimer (pro

vided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.