View NSN Online: https://aerobasegroup.kr/nsn/2530-00-278-6505

## STANCO INDUSTRIES INC -- WOVEN BRAKE LINING - 100 ALC -- 2530-00-278-6505

Product ID:WOVEN BRAKE LINING - 100 ALC

MSDS Date:05/01/1986

FSC:2530

NIIN:00-278-6505

MSDS Number: BPMRN === Responsible Party ===

Company Name: STANCO INDUSTRIES INC

Address:8220 MOSLEY ST

Box:87

City:HOUSTON

State:TX ZIP:77001 Country:US

Info Phone Num:713-944-3160 Emergency Phone Num:713

-944-3160 CAGE:LO101

=== Contractor Identification ===

Company Name: STANCO INDUSTRIES INC

Address:8220 MOSLEY ST

Box:87

City:HOUSTON

State:TX ZIP:77001 Country:US

Phone:713-944-3160

CAGE:LO101

Company Name: STANDCO INDUSTRIES-STERLING

Address:8220 MOSLEY ST

Box:City:HOUSTON

State:TX ZIP:77001 Country:US

Phone:713-224-6311

CAGE:07756

====== Composition/Information on Ingredients ========

Ingred Name: ASBESTOS, CHRYSOTILE

CAS:12001-29-5 RTECS #:CI6478500 Fraction by Wt: 40%

Other REC

Limits: NONE RECOMMENDED OSHA PEL:0.2 FIBERS/CC ACGIH TLV:2 FIBERS/CC; A1;9293 Ingred Name: RAYON Other REC Limits: NONE RECOMMENDED Ingred Name: BRASS WIRE Other REC Limits: NONE RECOMMENDED Ingred Name: SOLIDIFIED TUNG Other REC Limits: NONE RECOMMENDED Ingred Name: SOLIDIFIED LINSEED Other REC Limits: NONE RECOMMENDED Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES YES Health Hazards Acute and Chronic: THERE IS NO HAZARD IN HANDLING THE FINISHED PRODUCT. IF ADDITIONAL SAWING, DRILLING OR MACHINING IS PERFORMED, ASBESTOS FIBERS CAN BE RELEASED. Explanation of Carcinogenicity: ASBESTOS IS A KNOWN HUMAN CARCINOGEN. Effects of Overexposure: SEE "MEDICAL CONDITIONS" BELOW. Medical Cond Aggravated by Exposure: OVEREXPOSURE TO FREE ASBESTOS CAN INCREASE THE CHRONIC RISK OF LUNG FIBROSIS, CANCER AND/OR MESOTHELIMO. TOBACCO SMOKING CAN INCREASE THE EXPO SURE PROCESS. First Aid:NONE. Autoignition Temp: Autoignition Temp Text: 835F Extinguishing Media:WATER Fire Fighting Procedures: NONE Unusual Fire/Explosion Hazard:NONE Spill Release Procedures: DUST FROM MACHINING OPERATION SHOULD BE REMOVED USING OSHA APPROVED VACUUM.

=========

====== Handling and Storage ==============
Handling and Storage Precautions:NORMAL CARE SHOULD BE USED TO PREVENT BREAKING OF FINISHED PARTS WHICH COULD RELEASE ASBESTOS FIBERS TO THE ATMOSPHERE.  Other Precautions:NONE.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:WHEN NECESSARY USE NIOSH APPROVED RESPIRATOR WITH HIGH EFFICIENCY PARTICULATE AIR FILTERS.  Ventilation:LOCAL-PROVIDE DUST REMOVAL WHEN MACHINING. MECHANICAL-PRO VIDE SUCTION HOODS DURING MACHINING. Protective Gloves:NO Eye Protection:NORMAL Other Protective Equipment:WORKERS MUST CHANGE CLOTHING CONTAMINATED WITH MACHINE DUST BEFORE LEAVING WORK.  Work Hygienic Practices:ALTERATION OF THE FINISHED PRODUCT MAY REQUIRE YOUR COMPLIANCE WITH THE O.SSS.H.A. (PART STANDARD CFR-1910.1001) Supplemental Safety and Health
NOTE: MATERIAL WILL ACHIEVE AUTO IGNITION AT 835F.
======================================
HCC:N1 Spec Gr avity:1.4 Solubility in Water:NONE Appearance and Odor:TAN TO BROWN - VARNISH ODOR.
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NOT KNOWN Hazardous Decomposition Products:WHEN HEATED TO DECOMPOSITION - MAY EMIT TOXIC FUMES.
======== Disposal Considerations ===========

Waste Disposal Methods:DUST FROM MACHINING OPERATIONS SHOULD BE SEALED IN IMPERMEABLE BAGS OR CONTAINERS AND DISPOSED OF AS REQUI

RED BY 29 CFR 1910.1001.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this informatio n to their particular situation.