

HULS AMERICA INC. -- MIL-H-46170B TYPE 2

=====
MSDS Safety Information
=====

FSC: 9150

NIIN: 01-131-3325

MSDS Date: 02/21/1991

MSDS Num: BPPFJ

Product ID: MIL-H-46170B TYPE 2

MFN: 02

Responsible Party

Cage: 0DH22

Name: HULS AMERICA INC.

Address: TURNER PLACE,

Box: 365

City: PISCATAWAY NJ 08854

Info Phone Number: 201-763-7173

Emergency Phone Number: 201-763-7173

Proprietary Ind: Y

Review Ind: Y

Published: Y

=====
Contractor Summary
=====

Cage: 0DHB8

Name: HUL AMERICA INC

Address: TURNER PLACE

Box: 365

City: PISCATAWAY NJ 08854-0365

Phone: 201-763-7173

Cage: 0DH22

Name: HULS AMERICA INC

Address: TURNER PLACE

Box: 365

City: PISCATAWAY NJ 08854-0365

Phone: 908-981-5016

Cage: 63182

Name: HUL

S AMERICA INC
Address: TURNER PLACE
Box: 365
City: PISCATAWAY NJ 08855
Phone: 201-763-7173

=====
Item Description Information
=====

Item Manager: S9G
Item Name: HYDRAULIC FLUID,FIRE RESISTANT
Specification Number: MIL-H-46170B
Type/Grade/Class: TYPE II
Unit of Issue: CN
Quantitative Expression: 00000000005GL
UI Container Qty: 0
Type of Container: CAN
=====

=====
Ingredients
=====

Name: *** PROPRIETARY ***

=====

=====
Health Hazards Data
=====

LD50 LC50 Mixture: UNKNOWN
Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: NO
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO
Effects of Exposure: ACUTE- LOW ORAL AND DERMAL TOXICITY. MISTS OR FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION, NAUSEA, VOMITING. BARIUM COMPOUND IS A MODERATE SKIN IRRITANT AND IS CORROSIVE TO EYES. CHRONIC- NONE KNOWN.
Signs And Symptoms Of Overexposure: LOW ORAL AND DERMAL TOXICITY. MISTS OR FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION, NAUSEA, VOMITING. BARIUM COMPOUND IS A MODERATE SKIN IRRITANT AND IS CORROSIVE TO EYES.
Medical Cond Aggravated By Exposure: PRE-EXISTING SKIN DISORDERS MAY BE MO

RE

SUSCEPTIBLE TO THIS MATERIAL.

First Aid: CONSULT PHYSICIAN IF SYMPTOMS PERSIST. EYE:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER.

INHALATION:REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. INGESTION:DO NOT INDUCE VOMITING. CONTACT PHYSICIAN.

=====
Handling and Disposal
=====

Spill Release Procedures: WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF

IGNITION. VENTILATE THE AREA. CONTAIN THE SPILL. PICK UP LARGE SPILL WITH NON-SPARKING TOOLS; SMALL SPILLS/RESIDUE WITH INERT ABSORBENT MATERIAL. PLACE IN CONTAINERS. PREVENT ENTERING WATERWAYS/SEWERS.

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Handling And Storage Precautions: STORAGE- STORE IN COOL, VENTILATED AREA. DO NOT USE OIL ABOVE THE MAXIMUM RECOMMENDED TEMPERATURE OF 430F.

Other Precautions: KEEP CONTAINER CLOSED. WASH THOROUGHLY AFTER HANDLING. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. KEEP OUT OF REACH OF CHILDREN. MAY SOFTEN SOME PLASTIC AND PAINT SURFACES. WIPE UP SPILLS IMMEDIATELY .

=====
Fire and Explosion Hazard Information
=====

Flash Point Method: COC

Flash Point Text: 430F,221C

Extinguishing Media: WATER FOG, CARBON DIOXIDE, FOAM OR DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL.

Fire Fighting Procedures: WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard: CONTAINERS MAY RUPTURE DUE TO VAPOR PRESSURE BUILDUP.

=====
Control Measures
=====

Respiratory Protection: WEAR NIOSH-APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGES OR

SELF CONTAINED BREATHING APPARATUS IF MATERIAL IS HEATED.
Ventilation: MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF)
VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves: NATURAL RUBBER, NITRILE

Eye Protection: SAFETY GOGGLES

Other Protective Equipment: EYE WASH STATION, QUICK DRENCH SHOWER AND IMPERVIOUS CLOTHING

Work Hygienic Practices: PRACTICE GOOD HYGIENIC PROCEDURE. WASH THOROUGHLY BEFORE EATING OR DRINKING. USE WITH ADEQUATE VENTILATION.

Supplemental Safety

and Health: FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PNI A UNDER THE SAME NSN.

=====
Physical/Chemical Properties
=====

HCC: V6

Decomp Text: UNKNOWN

Spec Gravity: 0.842

Solubility in Water: NEGLIGIBLE

Appearance and Odor: RED LIQUID

Corrosion Rate: UNKNOWN
=====

Reactivity Data
=====

Stab

ility Indicator: YES

Stability Condition To Avoid: EXCESSIVE HEAT

Materials To Avoid: STRONG OXIDIZERS

Hazardous Decomposition Products: TOXIC FUMES

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT
=====

Toxicological Information
=====

Ecological Information
=====

=====
MSDS Transport Information
=====

Regulatory Information
=====

Other Information
=====

=====
Transportation Informatio

n

=====
Responsible Party Cage: 0DH22
Trans ID NO: 109667
Product ID: MIL-H-46170B TYPE 2
MSDS Prepared Date: 02/21/1991
Review Date: 12/22/1992
MFN: 2
Net Unit Weight: 35.1 LBS
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: CN
Container QTY: 0
Type Of Container: CAN
=====

=====
Detail DOT Information
=====

DOT PSN Code: ZZZ
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

=====
Detail IMO Information
=====

IMO PSN Code: ZZZ
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION
=====

=====
Detail IATA Information
=====

IATA PSN Code: ZZZ
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

=====
Detail AFI Information
=====

AFI PSN Code: ZZZ
AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION
=====

=====
HAZCOM Label
=====

Product ID: MIL-H-46170B TYPE 2
Cage: 0DH22
Company Name: HULS AMERICA INC
Street: TURNER PLACE
PO Box: 365
City: PISCATAWAY NJ
Zipcode: 08854-036

5
Health Emergency Phone: 201-763-7173
Label Required IND: Y
Date Of Label Review: 12/22/1992
Status Code: C
MFG Label NO: UNKNOWN
Label Date: 12/22/1992
Year Procured: 1993

Origination Code: F
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: CAUTION
Health Hazard: Slight
Contact Hazard: Slight
Fire Hazard: Slight
Reactivity Hazard: None

Hazard And Precautions: ACUTE- LOW ORAL AND DERMAL TOXICITY. MISTS OR FUMES FROM EXCESSIVE HEATING MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION, NAUSEA, VOMITING. BARIUM COMPOUND IS A MODERATE SKIN IRRITANT AND IS CORROSIVE TO EYES. CHRONIC- NONE KNOWN. STORAGE- STORE IN COOL, VENTILATED AREA. DO NOT USE OIL ABOVE THE MAXIMUM RECOMMENDED TEMPERATURE OF 430F. FIRST AID- CONSULT PHYSICIAN IF SYMPTOMS PERSIST. EYE: FUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN: WASH WITH SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. INGESTION: DO NOT INDUCE VOMITING. CONTACT PHYSICIAN.

=====
=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.