

INTERNATIONAL PAINT USA INC -- 5753, TPD-24441/3C EXT. TOPCOAT WHITE (SUPP) --
8010-01-350-4743

===== Product Identification =====

Product ID:5753, TPD-24441/3C EXT. TOPCOAT WHITE (SUPP)

MSDS Date:03/08/1990

FSC:8010

NIIN:01-350-4743

Kit Part:Y

MSDS Number: BPPJP

=== Responsible Party ===

Company Name:INTERNATIONAL PAINT USA INC

Address:2270 MORRIS AVE

City:UNION

State:NJ

ZIP:07083-0386

Country:U

S

Info Phone Num:713-682-1711

Emergency Phone Num:713-682-1711

CAGE:26351

=== Contractor Identification ===

Company Name:INTERNATIONAL PAINT INC

Address:6001 ANTOINE DR

Box:City:HOUSTON

State:TX

ZIP:77091

Country:US

Phone:800-589-1267/800-854-6813

CAGE:26351

===== Composition/Information on Ingredients =====

Ingred Name:BUTYL ALCOHOL; (N-BUTYL ALCOHOL). VP: 4@20C

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 25-30%

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000

LBS
DOT Rpt Qty:5000 LBS

Ingred Name:POLYAMIDE RESIN
CAS:68410-23-1
Fraction by Wt: 15-20%

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: EYES: SEVERE IRRITANT. MAY
CAUSE VISION IMPAIRMENT EVEN BLINDNESS. CORROSIVE. CAUSES
IRREVERSIBLE DAMAGE. SKIN: IRRITATING. MAY
RESULT IN DERM. MAY
CAUSE SENSIT/OTHER ALLERGIC RESPONSES. INHAL: IRRIT OF RESPIRATORY
TRACT. HEADACHE &DIZZINESS & UNCONSCIOUSNESS. INGEST: GI IRRIT,
(EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:HLTH HAZ: NAUSEA, VOMITING, DIARRHEA. CHRONIC
OVEREXPOSURE TO, AND MISUSE OF, SOLVENTS HAS BEEN LINKED TO
PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.
Medical Cond Aggravated by Exposure:SKIN AND RESPIRATORY CONDITIONS.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH IMMEDIATELY WITH COPIOUS QTY OF WATER FOR AT
LEAST 15 MINUTES. GET MED ATTN IMMED. SKIN: REMOVE CONTAMINATED
CLOTHING, WASH WITH PLENTY OF SOAP AND WATER. LAUNDER CLOTHES
BEFORE REUSE. INH AL: REMOVE TO FRESH AIR. GIVE
ARTFICIALRESPIRATION IF NEEDED. GET MEDICAL ATTENTION. INGEST: CALL
A PHYSICIAN IMMEDIATELY TO DETERMINE WHETHER OR NOT TO INDUCE
VOMITING.

=====
===== Fire Fighting Measures ==
=====

Flash Point Method:SCC
Flash Point:99.0F,37.2C
Lower Limits:1.4%
Extinguishing Media:FOAM, CO*2, DRY CHEMICAL.
Fire Fighting Procedures:NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP.
SMOTHER FLAMES W/1 OF ABOVE EXTING MEDIA. H*2O MAY BE USED TO COOL
UNOPENED CONTRS, BUT MUST NOT (SUPP DATA)
Unusual Fire/Explosion Hazard:CONTAINS FLAMMABLE SOLVENT. DO NOT USE IN
AREAS WHERE SPARK OR OPEN FLAME ARE PRESENT. CLOSED CONTAINERS MAY
EXPLODE WHEN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID INHALATION OF VAPORS. VENTILATE AREA. CLEAN UP WITH ABSORBENT MATERIALS.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN BLDG DESIGNED & PROTECTED FOR STORAGE OF LIQ W/NFPA CLASS GIVEN BY OSHA CLASS. AVOID BRTHG DUST/CHIPS FROM SAND/BLAST SURF COATED W/PROD.

Other Precautions: RECOM GROUNDING & BONDING OF CONTAINERS WHEN TRANSFERRING LIQ & POWDERS TO AVOID STATIC CHARGE BUILD UP.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: IN OUTDOOR/OPEN AREAS, W/UNRESTRICTED VENT, USE A NIOSH/MSHA APPRVD FILTER RESP TO REMOVE SOLID AIR-BORNE PARTICLES OF OVERSPRAY DURING SPRAY APPLICATN. IN RESTRICTED VENT AREAS, USE A NIOSH/MSHA APPR VD RESP IN ACCORDANCE WITH (SUPP DATA)

Ventil

ation: PROVIDE SUFFICIENT VENT IN VOL & PATTERN, TO KEEP TLV & LEL OF HAZ INGRED BELOW LIM SPECIFIED, & TO REMOVE (SUPP DATA)

Protective Gloves: CHEMICAL RESISTANT GLOVES.

Eye Protection: CHEM WORK GOG/FULL LENGTH FSHLD.

Other Protective Equipment: WEAR APPROPRIATE IMPERVIOUS PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT.

Work Hygienic Practices: REMOVE AND WASH SOILED CLOTHING BEFORE REUSE. WASH HANDS BEFORE EATING OR SMOKING.

Supplemental Safety and Health

MFR TRADE NAME/PART NO: F152H A P

ART A. FIRE FIGHT PROC: BE USED AS AN

EXTING MEDIA. TAKE CARE TO PVNT SPREAD OF BURNING LIQ W/H*20. CLSD CONTRS MAY EXPLODE WHEN EXPOS TO EXTREME HEAT. RESP PROT: 29CFR 1910.134 TO REMOVE COMBINATION OF PARTICULATES & VAPS. VENT: DECOMP PROD DURING WELD/FLAM CUTTING ON SURF COATED W/PROD.

===== Physical/Chemical Properties =====

HCC: F4

Boiling Pt: B.P. Text: 244F, 118C

Vapor Pres: SEE INGRED

Vapor Density: HVR/AIR

Spec Gravity: 1.5

Evaporation Rate & R

Reference: SLOWER THAN ETHER

Appearance and Odor: NONE SPECIFIED BY MANUFACTURER.

Percent Volatiles by Volume: 26(WT)

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

OXIDIZING AGENTS.

Stability Condition to Avoid: STORE AWAY FROM DIRECT HEAT, FLAME/SPARK.

Hazardous Decomposition Products: CO, CO*2, VARIOUS HYDROCARBON
FRAGMENTS, NITROGEN COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:

DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND
FEDERAL REGULATIONS. DO NOT INCINERATE UNOPENED CONTAINER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.