View NSN Online: https://aerobasegroup.kr/nsn/5960-00-242-6051

RAYTHEON CO, ELECTRONIC COMPONENTS DIV -- ELECTRON TUBE,2 J 55 -- 5960-00-242-6051

========== Product Identification ==========

Product ID:ELECTRON TUBE,2 J 55
MSDS Date:02/15/1991
FSC:5960
NIIN:00-242-6051
MSDS Number: BPPKQ
=== Responsible Party ===
Company Name:RAYTHEON CO, ELECTRONIC COMPONENTS DIV
Address:190 WILLOW ST
City:WALTHAM
State:MA
ZIP:02254
Country:US
Info Phone Num:617-899-8400
Emergency Pho
ne Num:617-899-8400
CAGE:6H339
=== Contractor Identification ===
Company Name:RAYTHEON CO, ELECTRONIC COMPONENTS DIV
Address:190 WILLOW ST
Box:City:WALTHAM
State:MA
ZIP:02254
Country:US
Phone:617-899-8400
CAGE:6H339

========== Composition/Information on Ingredients ==========

Ingred Name:MAGNETIZED MATERIAL
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT ESTABLISHED.
ACGIH TLV:NOT ESTABLISHED.

========== Hazards Identification ==========

Reports of Carcinogenic

ity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE AND CHRONIC- THIS PRODUCT IS CONSIDERED AN "ARTICLE" AS DEFINED IN 29 CFR 1910.1200(B) FOR "HAZARD COMMUNICATION" PURPOSES. PERSONNEL MAY BE EXPOSED TO ELECTROMAGNETIC RADIATION WHICH MAY RADIAT E FROM THIS DEVICE IF IMPROPERLY USED OR CONNECTED.
Effects of Overexposure:THIS PRODUCT IS CONSIDERED AN "ARTICLE" AS DEFINED IN 29 CFR 1910.1200(B) FOR "HAZARD COMMUNICATION" PURPOSES. PERSONNEL MAY BE EXPOSED
TO ELECTROMAGNETIC RADIATION WHICH MAY
RADIATE FROM THIS DEVICE IF IMPROPERLY USED OR CONNECTED.

========== First Aid Measures ==========

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS DEVELOP.

========== Fire Fighting Measures ==========

Extinguishing Media:AS APPROPRIATE FOR ELECTRICAL EQUIPMENT.
Fire Fighting Procedures:AS APPROPRIATE FOR ELECTRICAL EQUIPMENT.

========== Accidental Release Measures ==========

Spill
Release Procedures:WEAR GLOVES. USE FORCEPS AND TONGS FOR PICK UP.

========== Handling and Storage ==========

Handling and Storage Precautions:STORE IN COOL DRY PLACE IN ORIGINAL CONTAINER.
Other Precautions:THE MAGNETIC FIELD STRENGTH AROUND ELECTRON TUBE TYPE 2J55 IS LESS THAN 5.25 MILLIGAUSS AT FIFTEEN FEET DISTANCE FROM THE TUBE SURFACES. NEVER LOOK INTO AN OPEN WAVEGUIDE OR ANTENNA WHILE THE DEVICE I S ENERGIZED.

========== Exposure Contro
ls/Personal Protection ==========

Respiratory Protection:NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS, IF NEEDED.
Ventilation:ADEQUATE
Protective Gloves:RECOMMENDED
Eye Protection:SAFETY GOGGLES RECOMMENDED
Other Protective Equipment:EYE WASH STATION, QUICK DRENCH SHOWER AND IMPERVIOUS CLOTHING
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.
Supplemental Safety and Health
THIS PRODUCT IS CONSIDERED AN "ARTICLE" AS DEFINED IN 29 CF

R
1910.1200(B) FOR "HAZARD COMMUNICATION" PURPOSES. CONTAINS NO RADIOACTIVE MATERIALS.

========== Physical/Chemical Properties ==========

HCC:M1
Solubility in Water:INSOLUBLE

========== Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.