View NSN Online: https://aerobasegroup.kr/nsn/6140-01-134-5413

GNB INCORPORATED -- PC-31-625C BATTERY ELECTRICAL STORAGE, WET -- 6140-01-134-5413

Product ID:PC-31-625C BATTERY ELECTRICAL STORAGE, WET

MSDS Date:04/15/1986

FSC:6140

NIIN:01-134-5413

MSDS Number: BPPNF === Responsible Party ===

Company Name: GNB INCORPORATED

Address:1110 HIGHWAY 110 City:MENDOTA HEIGHTS

State:MN ZIP:55118 Country:US

Info Phone Num:612-681-5000

Em

ergency Phone Num:612-681-5000

CAGE:OMM77

=== Contractor Identification ===

Company Name: BATTERY OUTLET INC

Address:1608 CAMPOSTELLA RD

Box:City:CHESAPEAKE

State:VA ZIP:23324 Country:US

Phone:757-545-4442

CAGE:0FGN2

Company Name: CHICAGO INDUSTRIAL TRADING CO

Address:1901 LANDMEIER RD Box:City:ELK GROVE VILLAGE

State:IL ZIP:60007 Country:US

Phone:708-981-0090

CAGE:0K4U5

Company Name: EXIDE TECHNOLOGIES INC CO, GNB INDUSTRIAL POWER DIV

Address:829 PARKVIEW BOULEVARD

Box:City:LOMBARD

State:IL ZIP:60 148-3249 Country:US

Phone:800-872-0471/630-691-7841

CAGE:88219

Company Name: GNB INCORPORATED

Address:1110 HIGHWAY 110 City:MENDOTA HEIGHTS

State:MN ZIP:55118 Country:US

Phone:612-681-5000

CAGE:OMM77

====== Composition/Information on Ingredients ========

Ingred Name: SULFURIC ACID (SARA III)

CAS:7664-93-9

RTECS #:WS5600000 Fraction by Wt: 27% OSHA PEL:1 MG/CUM

ACGIH TLV:1 MG/CUM; 9192

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:LEAD (SARA III)

CAS:7439-92-1 RTECS #:OF75

25000

Fraction by Wt: 50%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9293

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: ELECTROLYTE- ACUTE: BURNS, SEVERE

IRRITATION OF SKIN & EYES, MOUTH, THROAT, ESOPHAGUS AND STOMACH;

INFLAMMATION OF BRONCHIA

Explanation of Carcinogenicity: NONE
Effects of Overexposure:INHALED: COUGHING, WHEEZING, SHORTNESS OF BREATH. SKIN: BURNING SENSATION, BURNS, REDNESS, BLISTERS, PAIN. EYES: PAIN, REDNESS, BLURRED VISION, TEARING. INGESTED: BURNS OF MOUTH AND THROAT, SEVERE STO MACH PAIN, NAUSEA, VOMITING. Medical Cond Aggravated by Exposure:EXPOSURE TO MISTS MAY CAUSE LUNG DAMAGE AND AGGRAVATE PULMONARY CONDITIONS.
======================================
First Aid:INHALED: REMOVE TO FRESH AIR. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: REMOVE CONTAMINATED CLOTHES. FLUSH WITH LOTS OF WATER FOR 15 MINUTES.
======================================
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PRO
TECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. Unusual Fire/Explosion Hazard:ELECTROLYTE REACTS VIOLENTLY WITH WATER AND ORGANIC MATERIALS WITH EVOLUTION OF HEAT.
========= Accidental Release Measures ==========
Spill Release Procedures:WEAR APPROPIATE PROTECTIVE EQUIPMENT. DILUTE CAUTIOUSLY WITH WATER. COVER WITH SODA ASH OR QUICKLIME. SCOOP UP AND PLACE IN APPROPIATE DISPOSAL CONTAINER. Neutralizing Agent:SODA ASH (SODIUM CARBONATE) OR QUICKLIME (CALCIUM OX IDE).
========== Handling and Storage ============
Handling and Storage Precautions:STORE AWAY FROM IGNITION SOURCES AND COMBUSTIBLE MATERIALS.AVOID CONTACT WITH ORGANIC MATERIALS. Other Precautions:KEEP TERMINALS COVERED IN PLASTIC CASE.AVOID SHORTING BATTERIES.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED CARTRIDGE RESPIRATOR FOR ACIDS OR FULL FACE MASK AS APPROPIATE

L MEMBRANES. CHRONIC: EROSION OF TEETH,

FOR EXPOSURE OF CONCERN WHEN TLV IS EXCEEDED. Ventilation: GENERAL (MECHANICAL) VENTILATION. LOCAL EXHAUST IN CONFINED AREAS. Protective Gloves:RUBBER Eye Protection: GOGGLES Other Protective Equipment: RUBBER APRON AND BOOTS. EYES WASH STATION AND SAFETY SHOWER. Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. Supplemental Safety and Health THIS MSDS IS FOR ACID IN BATTERY. ADDITIONAL HAZARDS ASSOCIATED WITH THE LEAD CONTAINED IN THE BATTERY PLATES MAY BE PRESENT AT TIME OF DISPOSAL. ======== Physical/Chemical Properties ============ HCC:C1 Appearance and Odor:BATTERY ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES COMBUSTIBLES, ORGANIC MATERIALS, STRONG REDUCING AGENTS. Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES. OVERCHARGING. Hazardous Decomposition Products: SULFURIC ACID FUMES, SULFUR DIOXIDE, SULFUR TRIOXIDE, CARBON MONOXIDE. ======= Disposal Considerations ============

Waste Disposal Methods:CONSULT YOUR LOCAL ENVIRONMENTAL OFFICER.
DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL ENVIRONMENTAL REGUALTIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrant

s this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.