View NSN Online: https://aerobasegroup.kr/nsn/7035-01-209-0031

UNION CARBIDE CORP INDUSTRIAL CHEMICALS DIV -- ISOPROPANOL, 91%, PM-437 7045-01-209-0031 Product ID: ISOPROPANOL, 91%, PM-437 MSDS Date:08/04/1989 FSC:7045 NIIN:01-209-0031 MSDS Number: BPQYJ === Responsible Party === Company Name: UNION CARBIDE CORP INDUSTRIAL CHEMICALS DIV Address:39 OLD RIDGEBURY ROAD City:DANBURY State:CT ZIP:06817-0001 Country:US Info Phone Num:800-822-4357 Emergency Phone Num:800-822-4357 CAGE:61637 === Contractor Identification === Company Name: COMPUTER ACCESSORIES CORP Address:211 NEW YORK AVENUE Box:City:HUNTINGTON State:NY ZIP:11743-2711 Country:US Phone:516-421-0929 CAGE:25041 Company Name: UNION CARBIDE CORP Address:39 OLD RIDGEBURY ROAD Box:City:DANBURY State:CT ZIP:06817-0001 Country:US Phone:800-822-4357/732-563-5522 (MSDS) CAGE:61637

Ingred Name: ISOPR

OPYL ALCOHOL (SARA III) CAS:67-63-0 RTECS #:NT8050000 Fraction by Wt: 91% OSHA PEL:400 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 9% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:ORAL LD50 (RAT) = 5840 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUT

E:EYE:LIQUID CAUSES SLIGHT TO

MODERATE IRRITATION WITH POSSIBLE CORNEAL INJURY. SKIN: NO HEALTH HAZARD FROM ABSORPTION, CONTACT CAUSES REDNESS & DRYING. INHALED:MILD IRRITATION, HEADACHE DROWSINES S. INGESTION:SLIGHTLY TOXIC. CHRONIC:NOEVIDENCE OF ADVERSE EFFECTS FROM AVILABLE INFORMATION.

Explanation of Carcinogenicity:MFR GAVE THE ABOVE LISTINGS ON THE MSDS BUT NO OTHER COMMENTS ABOUT CARCINOGENICITY WERE RECORDED. Effects of Overexposure:ACUTE:EYE:LIQUID CAUSES SLIGHT TO MODERATE

IRRITATION WITH POSSIBLE CORNEAL INJURY. SKIN: NO HEALTH HAZARD FROM ABSORPTION, CONTACT CAUSES REDNESS & DRYING. INHALED:MILD IRRITATION, HEADACHE DROWSINES S. INGESTION:SLIGHTLY TOXIC. CHRONIC:NOEVIDENCE OF ADVERSE EFFECTS FROM AVILABLE INFORMATION. Medical Cond Aggravated by Exposure:MAY AGGRAVATE EXISTING DERMATITIS.

First Aid:SKIN: REMOVE CONTAMINATED CLOTHING, LAUNDER BEFORE REUSE. WASH W

ITH SOAP AND WATER. INHALATION: IMMEDIATELY REMOVE VICTIUM TO FRESH AIR. GIVE OXYGEN OR ARTIFICIAL RESPIRATION AS NEEDED. GET MEDICAL AT TENTION. EYE: IMMEDIATELY FLUSH WITH WATER FOR SEVERAL MINUTES. GET PROMPT MEDICAL ATTENTION. INGESTION:GIVE 2 GLASSES WATER AND INDUYCE VOMITING IF CONSCIOUS. GET IMMEDIATE MEDICAL ATTENTION.

Flash Point Method:TCC Flash Point:65.0F,18.3C Lower Limits:2.0 Upper Limits:12

	_
	7
٠	1

- Extinguishing Media:ALCOHOL OR UNIVERSAL FOAM APPLIED BY MFR'S RECOMMENDED TECHNIQUES FOR LARGE FIRE. CO2 OR DRY CHEMICAL FOR SMALL FIRE.
- Fire Fighting Procedures:USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS AND STRUCTURES AND TO DISPERSE VAPORS. WEAR SCBM & PROTECTIVE CLOTHING WHEN FIGHTING FIRE IN ENCLOSED AREA. Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG GROUND OR FLOOR, THEN 'FLASH BACK' FROM A DISTANT IGNITION SOURCE.

Spill Release Procedures: ELIMINATE ALL SOURCES OF IGNITION. COLLECT LARGE SPILLS FOR DISPOSAL. FLUSH SMALL SPILLS WITH WATER. Neutralizing Agent: NO INFORMATION GIVEN ON MSDS BY MFR.

Handling and Storage Precautions:WARNING! FLAMMABLE! CAUSES EYE IRRITATION. KEEP AWAY FROM HEAT,SPARKS,& FLAME. AVOID CONTACT W/EYES. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILA.

Other Precautions: WASH THYOOUGHLY AFTER HANDLING. FOR INDUSTRIAL USE ONLY. TRANSFER HAZARD. VAPORS MAY BE IGNITED BY STATIC SPARKS. GROUND CONTAINERS WHEN TRANSFERRING LIQUID.

====== Exposure Controls/Personal Protection ==========

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS IN HIGH VAPOR CONCENTRATIONS.

Ventilation:NORMAL ROOM VENTILATION IS SUFFICIENT. SUPPLEMENT WITH LOCAL EXHAUST AT POINTS WHERE VAPORS ARE RELEASED TO WORKPLACE. Protectiv e Gloves:BUTYL Eye Protection:MONOGOGGLES Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER, Work Hygienic Practices:MFR GAVE NO INFORMATION OF MSDS. Supplemental Safety and Health NONE

HCC:F2 NRC/State Lic Num:NONE Boiling Pt:B.P. Text:176F,80C Melt/Freeze Pt:M.P/F.P Text:-76F,-60C Vapor Pres:34 MMHG Vapor Density:2.1 Spec Gravity:0.8159 Evaporation Rate & amp; Reference:3.0 (N-BUTYL ACETATE=1) Solubility in Wat er:COMPLETE Appearance and Odor:CLEAR LIQUID, ALCOHOL ODOR Percent Volatiles by Volume:100.0

Stability Indicator/Materials to Avoid:YES
CONC. NITRIC & SULFURIC ACIDS, STRONG OXIDIZING AGENTS, ALDEHYDES, HALOGENS, HALOGEN COMPOUNDS.
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:INCOMPLETE COMBUSTION MY YIELD CARBON MONOXIDE AND OTHER TOXIC GASES
Conditions to Avoid Polymerization:WILL NOT OCCUR

===

Waste Disposal Methods: INCINERATE IN FURNACE I/A/W FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.