

ULTRAMAR INC, AFFIL OF ULTRAMAR AMERICA LTD -- GASOLINE, AUTOMOTIVE, UNLEADED --
9130-01-282-2844

===== Product Identification =====

Product ID:GASOLINE, AUTOMOTIVE, UNLEADED

MSDS Date:07/15/1992

FSC:9130

NIIN:01-282-2844

MSDS Number: BPQYW

=== Responsible Party ===

Company Name:ULTRAMAR INC, AFFIL OF ULTRAMAR AMERICA LTD

Address:1111 W OCEAN BLVD SUITE 1400

Box:93102

City:LONG BEACH

State:CA

ZIP

:90809-3102

Country:US

Info Phone Num:310-495-5300/310-435-5832

Emergency Phone Num:310-495-5300/310-435-5832

CAGE:KO282

=== Contractor Identification ===

Company Name:ULTRAMAR INC

Address:1111 WEST OCEAN BLVD SUITE 1400

Box:93102

City:LONG BEACH

State:CA

ZIP:90809-3102

Country:US

Phone:310-495-5300

CAGE:0VZA7

Company Name:ULTRAMAR INC, AFFIL OF ULTRAMAR AMERICA LTD

Address:1111 W OCEAN BLVD SUITE 1400

Box:93102

City:LONG BEACH

State:CA

ZIP:90809-3102

Country:US

Phone:310-495-5300/310-435-5832

C

AGE:KO282

=====
Composition/Information on Ingredients
=====

Ingred Name:GASOLINE
CAS:8006-61-9
RTECS #:LX3300000
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:300 PPM/500 STEL
ACGIH TLV:300 PPM/500STEL;9293

Ingred Name:MAY CONTAIN BENZENE (SARA III)
CAS:71-43-2
RTECS #:CY1400000
Fraction by Wt: >0.1%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1PPM/5STEL;1910.1028
ACGIH TLV:10 PPM; A2; 9293
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

=====
Fire
Fighting Measures
=====

Flash Point Method:CC
Flash Point:-45F,-43C
Autoignition Temp:Autoignition Temp Text:536F
Lower Limits:1.2
Upper Limits:7.6
Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR
REGULAR FOAM. FOR LARGE FIRES, USE WATER SPRAY, FOG OR REGULAR
FOAM.
Fire Fighting Procedures:EXTINGUISH ONLY IF FLOW CAN BE STOPPED; USE
WATER IN FLOODING AMOUNTS AS FOG. AVOID BREATHING VAPORS, KEEP
UPWIND. COOL CONTAINER WITH FLOODING AMOUNTS OF WAT
ER
Unusual Fire/Explosion Hazard:DANGEROUS FIRE HAZARD WHEN EXPOSED TO
HEAT OR FLAME. VAPORS ARE HEAVIER THAN AIR, MAY TRAVEL TO A SOURCE
OF IGNITION & FLASHBACK. VAPOR-AIR MIXTURE IS EXPLOSIVE

=====
Exposure Controls/Personal Protection
=====

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F2
Boiling Pt:B.P. Text:100-400F
Vapor Density:3.0-4.0
Spec Gravity:0.7-0.8
pH:UNK
Solubility in Water:INSOLUBLE
Appearanc

e and Odor: CLEAR COLORLESS TO AMBER, AROMATIC, VOLATILE LIQUID.

Percent Volatiles by Volume: UNK

Corrosion Rate: UNK

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

OXIDIZERS (STRONG): FIRE AND EXPLOSION HAZARD.

Stability Condition to Avoid: HEAT, FLAMES, SOURCES OF IGNITION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.