

CHEMRAY COATING CORP -- ENAMEL, ALKYD, GLOSS, EXT, INT, BLUE 15102 -- 8010-00-597-7844

=====
Product Identification
=====

Product ID:ENAMEL, ALKYD, GLOSS, EXT, INT, BLUE 15102

MSDS Date:11/09/1988

FSC:8010

NIIN:00-597-7844

MSDS Number: BPRHR

=== Responsible Party ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Info Phone Num:201-245-1

111

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:33832

=== Contractor Identification ===

Company Name:CHEMRAY COATING CORP

Address:209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ

ZIP:07033

Country:US

Phone:201-245-1111

CAGE:33832

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS 66

Fraction by Wt: 48%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:200 PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by

Wt: .2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:100 PPM/150STEL;9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VOC: 4.03 LBS/GAL OR 483 GRAMS/LITER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:(ACIGH) (OSHA) 100 PPM (590 MG/M3) FOR
8 HOUR WORK DAY. HIGH VAPOR CONCENTRATIONS (OVER 1000 PPM) ARE
IRRITATING TO THE EYE & RESPIRATORY TRACT. MAY CAUSE HEADACHES &
DIZZINESS. PROLONGED SKIN CONTACT IRRITATES.

=====
===== First Aid Measures =====
=====

First Aid:EYE CONTACT: FLUSH WITH WATER 15 MINS OR UNTIL IRRITATION
SUBSIDES. IF IRRITATION PERSISTS CALL A PHYSICIAN. SKIN CONTACT:
REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY WITH SOAP AND
WATER. INHALATION: IF OVERCOME BY VAPORS REMOVE TO FRESH AIR, CALL
PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:SCC
Flash Point:103F,39C
Lower Limits:.9
Upper Limits:7
Extinguishing Media:CARBON DIOXIDE, FOAM, WATER FOG, DRY CHEMICAL
Fire Fighting Procedures:USE AIR SUPPLIED BREATHING EQUIPEMNT FOR
ENCLOSED CONTAINERS WITH WATER SPRAY, AVOID BREATHING VAPOR OR
FUMES.
Unusual Fire/Explosion Hazard:IF LEAK OR SPILL HAS IGNITED, USE WATER
SPRAY TO DISPERSE THE VAPORS FROM FIRE

FIGHTERS.

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE IGNITION SOURCES. KEEP FROM HEAT, SPARKS & OPEN FLAME. ADD ABSORBENT (SAND, EARTH, SAWDUST) TO SPILL. VENT (OPEN WINDOWS, DOORS). IF LARGE SPILL KEEP PRODUCT FROM ENTERING SEWERS & WATERCOURSES BY DIKING. ADVISE AUTHORITIES IF PROD HAS ENTERED

===== Handling and Storage =====

Handling and Storage Precautions: PROPER SHIPPING NAME - PAINT.

HAZARDOUS CLASSIFICATION -- COMBUSTIBLE LIQUID ID NO UN1263.

Other Precautions: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE HYDROCARBON VAPOR CANISTER OR SUPPLIED AIR RESPIRATOR IN CONFINED AREA.

Ventilation: LOCAL: FACE VELOCITY 60 FPM. MECHANICAL (GENERAL): USE EXPLOSION PROOF EQUIPMENT. SPECIAL USE ONLY WITH ADEQUATE VENT.

Protective Gloves: CHEMICAL RESISTANT GLOVES.

Eye Protection: SPLASH GOGGLES OR FACE SHIELD

Other Protective Equipment: USE CHEMICAL RESISTANT APRON OR OTHER CLOTHING TO AVOID REPEATED SKIN CONTACT.

Work Hygienic Practices: WASH HANDS THOROUGHLY AFTER USE AND KEEP CONTAINER CLOSED WHEN NOT IN USE.

Supplemental Safety and Health

===== P
Physical/Chemical Properties =====

HCC: F4

Boiling Pt: B.P. Text: 308F, 153C

Melt/Freeze Pt: M.P/F.P Text: