View NSN Online: https://aerobasegroup.com/nsn/8030-01-218-0321

Product ID:SWAK MSDS Date:09/01/1991 FSC:8030 NIIN:01-218-0321 MSDS Number: BPRQD === Responsible Party === **Company Name: CAJON COMPANY** Address:9760 SHEPARD ROAD City:MACEDONIA State:OH ZIP:44056 Country:US Info Phone Num:216-467-0200 Emergency Phone Num:216-467-0200,CHEMTREC 800-424-9300 CAGE:11649 === Contractor Identif ication === Company Name: CAJON COMPANY Address:9760 SHEPARD ROAD Box:City:MACEDONIA State:OH ZIP:44056 Country:US Phone:216-467-0200 CAGE:11649

Ingred Name:POLYTETRAFLUOROETHYLENE (TEFLON) CAS:116-14-3 RTECS #:KX4025000 Fraction by Wt: 30-40% Other REC Limits:NONE SPECIFIED

Ingred Name:ETHOXYLATED BISPHENOL A DIMETHACRYLATE CAS:24447-78-7 Fraction by Wt: 30-40% Other REC Limits:NONE SPECIFIED

Ingred Name: POLY(1,2-PROPYLENEG

LYCOL AZELATE)ESTER CAS:29408-67-1 Fraction by Wt: 20-30% Other REC Limits:NONE SPECIFIED

Ingred Name:TITANIUM DIOXIDE.OSHA PEL AND ACGIH TLV ARE FOR TOTAL DUST CONTAINING NO ASBESTOS AND 230F,110C Lower Limits:NONE Upper Limits:NONE Extinguishing Media:NONFLAMMABLE.USE WATER SPRAY,CARBON DIOXIDE,DRY CHEMICAL,OR FOAM. Fire Fighting Procedures:NO SPECIAL PROCEDURES REQUIRED. Unusual Fire/Explosion Hazard:PRODUCT CAN EMIT TOXIC FUMES AT TEMPERATURES ABOVE 500F,260C.

Spill Release Procedures:CLEAN UP ANY SPILLS OR LEAKS WITH ABSORBENT MATERIAL AND A SUITABLE CLEANER.RECOMMEND PROPER EYE AND SKIN PROTECTION. Neutralizing Agent:NOT KNOWN

Handling and Storage Precautions:STORE BETWEEN 45F TO 85F (7C TO 29C). Other Precautions:NOT KNOWN

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:AT TEM

\_\_\_\_\_

PERATURES OVER 500F (260C), DECOMPOSITION

PRODUCTS MAY REQUIRE EXPOSED INDIVIDUALS TO WEAR RESPIRATORY PROTECTION.

Ventilation:CONTACT LOCAL SAFETY/INDUSTRIAL HYGIENE OFFICE TO DETERMINE IF LOCAL EXHAUST VENTILATION IS NEEDED .

Protective Gloves: RUBBER OR IMPERVIOUS GLOVES.

Eye Protection: SAFETY GLASSES W/ SIDE SHIELDS (SUP DATA)

Other Protective Equipment: EYE WASH STATION NEAR WORK AREA.

Work Hygienic Practices: AVOID SKIN CONTACT. DO NOT EAT, DRINK, OR SMOKE DURING USE. WASH HANDS AFT

ER USE.AVOID TRANSFER OF SWAK TO (SEE SUP DATA) Supplemental Safety and Health HAZ DECOMP PROD: PERFLUOROISOBUTYLENE, CARBONYL FLUORIDE. EYE PROT: OR GOGGLES.WORK HYG PRAC:MOUTH.GLOVES,CLOTHES,EQUIPMENT WHICH HAVE COME IN CONTACT WITH SWAK SHOULD BE THOROUGHLY CLEANED. Boiling Pt:B.P. Text:NOT KNOWN Melt/Freeze Pt:M.P/F.P Text:NOT KNOWN Decomp Temp: Decomp Text: NOT KNOWN Vapor Pres:NOT KNOWN Vapor Density:NOT KNOWN Spe c Gravity:1.2 (WATER=1) Evaporation Rate & amp; Reference: NOT KNOWN Solubility in Water: INSOLUBLE Appearance and Odor: OFF-WHITE PASTE WITH SLIGHT ODOR. THREAD SEALANT HAS TEMP RATING OF -65 TO 350F. Percent Volatiles by Volume:2.0 Stability Indicator/Materials to Avoid:YES AVOID PURE OXYGEN, CHLORINE, AND FLUORINE. AVOID USE ON PLASTIC SYSTEMS OTHER THAN TFE. Stability Condition to Avoid: TEMPERATURES ABOVE 500F, 260C. Hazard ous Decomposition Products:>400F:CARBON MONOXIDE & DIOXIDE, ORGANOCHLORINE COMPOUNDS.>500F:TETRAFLUOROETHYLENE,HEXAFLUOROPROPYLENE (SEE SUP DATA) Conditions to Avoid Polymerization: WILL NOT OCCUR. 

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH FEDERAL,STATE,AND LOCAL REGULATIONS.COORDINATE WITH SUPPORTING INSTALLATION AND/OR MACOM ENVIRONMENTAL OFFICE PRIOR TO DISPOSAL .UNCONTAMINATED PRODUCT IS NOT A HAZARDOUS WASTE AS DEFINED IN 40 CFR.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitab ility of this information to their particular situation.