

EXXON CO USA, A DIV OF EXXON CORP. -- JOBBER PLUS GASOLINE; PRODUCR CODE 047200-0 --
9130-01-272-0983

===== Product Identification =====

Product ID:JOBBER PLUS GASOLINE; PRODUCR CODE 047200-0

MSDS Date:12/02/1991

FSC:9130

NIIN:01-272-0983

MSDS Number: BPRQP

=== Responsible Party ===

Company Name:EXXON CO USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

C

Country:US

Info Phone Num:713-656-2443

Emergency Phone Num:713-656-3424

CAGE:29700

=== Contractor Identification ===

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:ROGERS R T OIL CO INC

Address:300 GRACE ST

Box:160

City:HINTON

State:WV

ZIP:25951

Country:US

CAGE:0A889

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA, LIGHT CATALYTIC CRACKED

CAS:64741-55-5

Other REC Limits:NONE RECOMMENDED

Ingred Name:NAPHTHA, HEAVY CATALYTIC CRACKED

CAS:64741-54-4

Other REC Limits:NONE RECOMMENDED

Ingred Name:NAPHTHA, FULL-RANGE REFORMED

CAS:68919-37-9

Other REC Limits:NONE RECOMMENDED

Ingred Name:NAPHTHA, FULL-RANGE ALKYLATE

CAS:64741-64-6

Other REC Limits:NONE RECOMMENDED

Ingred Name:NAPHTHA, SWEETENED

CAS:64741-87-3

Other REC Limits:NONE RECOMMENDED

Ingred Name:BUTANE

CAS:106-97-8

RTECS #:EJ4200000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:800 PPM

ACGIH

TLV:800 PPM; 9293

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >5 G/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:PROLONGED/REPEATED SKIN CONTACT TENDS TO REMOVE SKIN OILS, POSSIBLY LEADING TO IRRITATION & DERMATITIS.

PRODUCT HAS A LOW ORDER OF ACUTE & DERMAL TOXICITY, BUT MINUTS AMOUNTS ASPIRATED INTO THE LUNGS DURIN

G INGESTION/VOMITING MAY

CAUSE MILD TO SEVERE PULMONARY INJURY & POSSIBLY DEATH.

Explanation of Carcinogenicity:THIS PRODUCT MAY CONTAIN UP TO A MAX OF

4.9% BENZENE. BENZENE IS LISTED AS A CARCINOGEN BY NTP, IARC, OSHA AND EPA.

Effects of Overexposure:HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES & THE RESPIRATORY TRACT, AND MAY CAUSE HEADACHES, DIZZINESS,

ANESTHESIA, DROWSINESS, UNCONSCIOUSNESS, AND OTHER CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DEATH.

Medical Con

d Aggravated by Exposure:INDIVIDUALS WITH LIVER DISEASE (BENZENE), NEUROLOGICAL (HEXANE) AND SKIN DISORDER SHOULD USE CAUTION WHEN HANDLING OR USING THIS PRODUCT.

===== First Aid Measures =====

First Aid:EYE-FLUSH WITH CLEAR WATER FOR 15 MIN OR UNTIL IRRITATION STOPS. SKIN-WASH SKIN WITH SOAP & WATER. IF INJECTED UNDER THE SKIN, THE INDIVIDUAL SHOULD BE EVALUATED IMMEDIATELY BY A PHYSICIAN. INHALATION -IF OVERCOME BY VAPOR, REMOVE FROM EXPOSURE & CALL PHYSICIAN. IF BREATHING IS IRREGULAR OR STOPS, START RESUSCITATION, ADMINISTER OXYGEN, IF AVAILIABLE. INGEST-DO NOT INDUCE VOMITING; CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point: