View NSN Online: https://aerobasegroup.com/nsn/8040-00-142-9913

TACC INTERNATIONAL CORP. -- ACCELERATOR AC 102 -- 8040-00-142-9913

Product ID: ACCELERATOR AC 102 MSDS Date:01/01/1987 FSC:8040 NIIN:00-142-9913 Kit Part:Y MSDS Number: BPTVY === Responsible Party === Company Name: TACC INTERNATIONAL CORP. Address: AIR STATION INDUSTRIAL PARK Box:390 City:ROCKLAND State:MA ZIP:02370 Country:US Info Phone Num:617-878-7015 Emergency Phone Num:800-424-9300 CHEMTREC CAGE:0HZU1 === Contractor Identification === Company Name: TACC INTERNATIONAL CORP Address: AIR STATION INDUSTRIAL PARK Box:City:ROCKLAND State:MA ZIP:02370 Country:US Phone:781-878-7015 CAGE:0HZU1

Ingred Name:POLYMERIC ALIPHATIC AMINE CAS:63512-71-0 Fraction by Wt: 20% Other REC Limits:NONE SPECIFIED

Ingred Name:ETHANOL CAS:64-17-5 RTECS #:KQ6300000 Fraction by Wt: 80% Other REC Limits:NONE SPE CIFIED OSHA PEL:1000 PPM ACGIH TLV:1000 PPM

======================================
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: NONE. EYES: STRONGLY IRRITATING TO EYES. SKIN: REDNESS, BURNING. CAN LEAD TO SENSITIZATION WITH REPEATED EXPOSURE. INGESTION: HARMFUL IF SWALLOWED.
======================================
First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES. CALL A PHYSICIAN.
SKIN: WASH WITH SOAP AND WATER; CALL A PHYSICIAN IF NECESSARY. INGESTION: CALL POISON CENTER IMMEDIATELY.
======================================
Flash Point:50.0F,10.0C Lower Limits:3.3 Upper Limits:19.0
Extinguishing Media:FOAM, DRY CHEMICAL, CO2, WATER SPRAY OR FOG. Fire Fighting Procedures:AVOID BREATHING SMOKE. USE AIR SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREA. WATER TENDS TO SPREAD BURNING LIQUID IF LARGE AMOUNTS USED.
Unusual Fir e/Explosion Hazard:FLAMM. VAPORS MAY IGNITE EXPLOSIVELY/CAUSE FLASH FIRE. NO IGNIT SOURCE/SMOKING. CROSS VENT TO REMOVE VAPOR/SOLVENT ODOR. ELECTRICALLY GROUND CNTNRS WHEN TRANFER
======================================
Spill Release Procedures: SMALL QUANTITIES MAY BE ABSORBED INTO AN APPROPRIATE ABSORBENT. FOR LARGE SPILLS SEE SECTIONS ON FIRE &

EXPLOSION HAZARDS, CONTROL MEASURES, HANDLING & PRECAUTIONS.

======================== Handling and Sto

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.
STORE AT 60-95F, OUT OF SUN. USE ADEQUATE VENTILATION TO AVOID BREATHING VAPOR WHEN COVER REMOVED.
Other Precautions:GROUND ALL EQUIPMENT WHEN HANDLING FLAMMABLE SOLVENTBORNE MATEIALS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: IF VAPORS EXCEED TLV, USE CONTAINED ORGANIC MASK NIOSH APPROVED. Ventilation: LOCAL EXHAUST: SUFFICIENT T O KEEP WORKROOM CONCENTRATION BELOW TLV. Protective Gloves: CHEMICAL RESISTANT GLOVES Eye Protection: SAFETY GLASSES OR FACE SHIELD Supplemental Safety and Health

HCC:F2 Boiling Pt:B.P. Text:173F,78C Vapor Pres:44 MM HG Vapor Density:>1 Spec Gravity:0.86 Evaporation Rate & amp; Reference:>1 Solubility in Water:YES Appearance and Odor:BROWN, AMMONIA LIKE ODOR Percent Volatiles by Volume:80

======== Stability and Re

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS, STRONG ACIDS AND BASES Stability Condition to Avoid:FIRE, SPARKS, STATIC ELECTRICITY Hazardous Decomposition Products:CO AND CO2

Waste Disposal Methods:LIQUID MATERIAL IS DESIGNATED AS HAZARDOUS WASTE UNTIL ALL SOLVENT AND VAPORS HAVE EVAPORATED. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DRIED

## ADHESIVE MAY BE DISPOSED OF AS ORDINARY WASTE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitab ility of this information to their particular situation.