

ALPHA METALS -- SOLDER ALLOYS OF LEAD, TIN, SILVER, BIMUTH, -- 3439-00-153-4280

===== Product Identification =====

Product ID:SOLDER ALLOYS OF LEAD, TIN, SILVER, BIMUTH,

MSDS Date:03/13/1990

FSC:3439

NIIN:00-153-4280

MSDS Number: BPTWC

=== Responsible Party ===

Company Name:ALPHA METALS

Address:600 ROUTE 440

City:JERSEY CITY

State:NJ

ZIP:07304

Country:US

Info Phone Num:201-434-6778

Emergency Phone

Num:201-434-6778

CAGE:96613

=== Contractor Identification ===

Company Name:DEANCO INC

Address:7933 QUEENAIR DR

Box:City:GAITHERSBURG

State:MD

ZIP:20879-4137

Country:US

Phone:301-948-5444

CAGE:9K946

Company Name:FRYS METALS INC (FORMER ALPHA METALS)

Address:600 ROUTE 440

Box:City:JERSEY CITY

State:NJ

ZIP:07304

Country:US

Phone:201-434-6778

CAGE:96613

===== Composition/Information on Ingredients =====

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

Other REC Limit

s:NONE RECOMMENDED
OSHA PEL:0.05 MG/M3;1910.1025
ACGIH TLV:0.15 MG/M3;DUST 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:TIN
CAS:7440-31-5
RTECS #:XP7320000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9293

Ingred Name:SILVER (SARA III)
CAS:7440-22-4
RTECS #:VW3500000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.01 MG/M3
ACGIH TLV:0.1 MG/M3; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:BISMUTH
CAS:7440-69-9
RTECS #:EB2600000
Other REC Limits:NONE RECOMMEND
ED

Ingred Name:ANTIMONY (SARA III)
CAS:7440-36-0
RTECS #:CC4025000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.5 MG/M3
ACGIH TLV:0.5 MG SB/M3; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:INDIUM
CAS:7440-74-6
RTECS #:NL1050000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.1 MG/M3
ACGIH TLV:0.1 MG/M3; 9293

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:

NO

Health Hazards Acute and Chronic:ACUTE: INHALATION OF FUMES MAY CAUSE NERVOUS SYSTEM AND MUSCLE IRREGULARITIES, IRRITATION OF EYES, NOSE, THROAT, AND RESPIRATORY SYSTEM, METAL FUME FEVER. CHRONIC: INHALATION OF FUMES MAY CAUSE CANCER , SIDEROSIS, AND AFFECT LUNG FUNCTION.

Explanation of Carcinogenicity:IARC CLASSES LEAD AND SOME LEAD COMPOUNDS AS 2B CARCINOGENS (POSSIBLE CARCINOGENS).

Effects of Overexposure:INHALATION: NAUSEA, DIZZINESS, DRYNESS OF NOSE AND THROAT, CO

UGHING, WHEEZING AND SHORTNESS OF BREATH. EYES: REDNESS, TEARING, BLURRED VISION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESUSCITATE IF NEEDED. EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH WITH SOAP AND WATER. FOR BURNS, COOL AREA AND SEE DOCTOR. INGESTION: DO NOT INDUCE VOMITING. CALL POISON CONTROL CENTER

IMMEDIATELY.

===== Fire Fighting Measures =====

Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:WHEN HEATED TO HIGH TEMPERATURES, LEAD EMITS HIGHLY TOXIC FUMES.

===== Accidental Release Measures =====

Spill Release Procedures:SWEEP UP OR MOP. PLACE RESIDUE IN A CONTAINER FOR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:REMOVE ANY COMBUSTIBLES FROM WORK AREA: SPARKS OR WELDING ARC COULD IGNITE NEARBY COMBUSTIBLES.

Other Precautions:FOOD AND DRINK SHOULD NOT BE CONSUMED OR TOBACCO PRODUCTS USED NOR COSMETICS APPLIED IN AREAS WHERE SOLDER MAY BE USED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NI

OSH/MSHA APPROVED RESPIRATOR FOR WELDING
FUMES OR SUPPLIED AIR RESPIRATOR IN CONFINED SPACES OR WHERE FUME
CONCENTRATION EXCEEDS REGULATORY LIMITS.
Ventilation:USE MECHANICAL OR LOCAL EXHAUST OR BOTH TO MAINTAIN LEVELS
OF FUMES BELOW REGULATORY LIMITS.
Protective Gloves:WORK GLOVES
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING,
DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTH
ING BEFORE REUSE.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1
Solubility in Water:NEGLIGIBLE
Appearance and Odor:OPAGUE, CHARCOAL COLORED SOLID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, HYDROGEN PEROXIDE >52%
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:LEAD OXIDE AND
ANTIMONY OXIDE MAY BE
VOLVED AT TEMPERATURES GREATER THAN 1000F.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be
accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.