

DAVIS-HOWLAND OIL CORPORATION -- MIL-G-81827 -- 9150-00-408-9635

===== Product Identification =====

Product ID:MIL-G-81827

MSDS Date:10/13/1991

FSC:9150

NIIN:00-408-9635

MSDS Number: BPTYX

=== Responsible Party ===

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Info Phone Num:716-473-6651/716-473-6650

Emergency Phone Num:716-473

-6651

CAGE:FO626

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

Company Name:DAVIS-HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Phone:(716) 473-6650

CAGE:FO626

===== Composition/Information on Ingredients =====

Ingred Name:SYNTHETIC OIL

Fraction by Wt: >69%

Other REC Limits:NONE RECOMMENDED

Ingred Name:ADDITIVES

AND OTHER INGREDIENTS

Fraction by Wt: 5 G/KG

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NONE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:ON RARE OCCASIONS, HYPERSENSITIVE INDIVIDUALS MAY DEVELOP SKIN ALLERGIES. IF THIS OCCURS, REMOVE FROM FURTHER

EXPOSURE AND SEEK ADVICE OF A PHYSICIAN.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
First Aid Measures  
=====

First Aid:EYE-FLUSH WITH WATER. SKIN-WASH CONTACT AREA WITH SOAP & WATER. HIGH PRESSURE ACCIDENTAL INJECTION THROUGH THE SKIN REQUIRES IMMEDIATE MEDICAL ATTENTION. INHALATION-NOT EXPECTED TO BE A PROBLEM. INGESTION-NOT EXPECTED TO BE A PROBLEM. HOWEVER, IF GREATER THAN 1/2 LITER INGESTED, IMMEDIATELY GIVE 1 TO 2 GLASSES OF WATER & CALL A PHYSICIAN, HOSPITAL OR POISON CONTROL CENTER. DO NOT INDUCE VOMITING.

=====  
Fire Fighting Measures  
=====

Flash Point Method:COC

Flash Point:>400F,>204C

Autoignition Temp:Autoignition Temp Text:NA

Lower Limits:0.6

Upper Limits:7.0

Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG. WATER OR FOAM MAY CAUSE FROTHING. USE WATER TO COOL EXPOSED CONTAINERS

Fire Fighting Procedures:

FOR FIRES IN ENCLOSED AREAS, FIREFIGHTERS MUST USE SELF CONTAINED BREATHING APPARATUS. PREVENT RUNOFF FROM FIRE OR DILUTION FROM ENTERING STREAMS/WATER SUPPLY.

Unusual Fire/Explosion Hazard:NONE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:SHOVEL UP AND DISPOSE OF AT AN APPROPRIATE WASTE FACILITY IN ACCORDANCE WITH CURRENT APPLICABLE LAWS AND REGULATIONS, AND PRODUCT CHARACTERISTICS AT TIME OF DISPOSAL.

Neutralizing Agent:NA

=

=====  
Handling and Storage  
=====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.  
Other Precautions:NO SPECIAL PRECAUTIONS REQUIRED.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY  
CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.  
Ventilation:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE  
AND WITH ADEQUATE VENTILATION.  
Protective Gloves:NO SPECIAL  
EQUIPMENT REQUIRED.  
Eye Protection:NO SPECIAL EQUIPMENT REQUIRED.  
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.  
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE  
EATING, DRINKING OR SMOKING.  
Supplemental Safety and Health  
NONE

=====  
Physical/Chemical Properties  
=====

HCC:V6  
Boiling Pt:B.P. Text:>600F,>316C  
Melt/Freeze Pt:M.P/F.P Text:NA  
Decomp Temp:Decomp Text:NA  
Vapor Pres: