

TACC INTERNATIONAL CORP. -- NEOPRENE SOLVENT BORNE ADHESIVE -- 8040-00-515-2245
===== Product Identification =====

Product ID:NEOPRENE SOLVENT BORNE ADHESIVE

MSDS Date:04/01/1992

FSC:8040

NIIN:00-515-2245

Kit Part:Y

MSDS Number: BPTZN

=== Responsible Party ===

Company Name:TACC INTERNATIONAL CORP.

Address:AIR STATION INDUSTRIAL PARK

Box:390

City:ROCKLAND

State:MA

ZIP:02370

Country:US

Info Phone N

um:617-878-7015

Emergency Phone Num:617-878-7015

CAGE:0HZU1

=== Contractor Identification ===

Company Name:TACC INTERNATIONAL CORP

Address:AIR STATION INDUSTRIAL PARK

Box:City:ROCKLAND

State:MA

ZIP:02370

Country:US

Phone:781-878-7015

CAGE:0HZU1

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 40-45%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000

LBS
DOT Rpt Qty:1000 LBS

Ingred Name:HEXANE
CAS:110-54-3
RTECS #:MN9275000
Fraction by Wt: 30-36%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:VOLATILE ORGANIC CONTENT: 663 G/L
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards

Acute and Chronic:INHALATION: ACUTE SIGNS OF
OVEREXPOSURE COULD BE HEADACHE, DIZZINESS, NAUSEA, UPPER
RESPIRATORY DRYNESS OR IRRITATION, DROWSINESS, MENTAL DEPRESSION OR
NARCOSIS, DIFFICULTY IN BREATHING. CHRONIC EFFEC TS OF OVEREXPOSURE
TO SOLVENT VAPORS COULD LEAD TO PERMONENT NERVOUS SYSTEM/BODY
ORGANS/BRAIN EFFECTS. USE **

Effects of Overexposure:**WITH ADEQUATE VENTILATION. EYES: IRRITATION.
INGESTION: MAY BE HARMFUL OR FATAL IF SWALLOWED. SKIN: REMOVAL OF
SKIN O
ILS, IRRITATION, DERMATITIS, EVEN SENSITIZATION WITH
OVEREXPOSURE.

=====
===== First Aid Measures =====

First Aid:INHALATION: GET FRESH AIR. EYES: IF NECESSARY CALL A
PHYSICIAN. FLUSH WITH WATER FOR AT LEAST 15 MINUTES, IF NECESSARY,
CALL A PHYSICIAN. SKIN: WASH WITH MILD SOAP AND WATER APPLY A MILD
CREAM. INGEST ION: CALL POISON CENTER IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point: 1 (BUTYL ACETA

TE = 1)

Solubility in Water:NIL

Appearance and Odor:NEUTRAL LIQUID, AROMATIC ODOR

Percent Volatiles by Volume:78 %

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS, STRONG BASES

Stability Condition to Avoid:FIRE, SPARKS, STATIC ELECTRICITY

Hazardous Decomposition Products:CO AND CO2.

===== Disposal Considerations =====

Waste Disposal Methods:MATERIAL IS DESIGNAT

ED AS HAZARDOUS WASTE UNTIL

ALL SOLVENTS AND VAPORS HAVE EVAPORATED. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DRIED ADHESIVE MAY BE DISPOSED OF AS ORDINARY WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all lia

bility for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.