View NSN Online: https://aerobasegroup.com/nsn/8030-00-555-2878

THOMPSON & FORMBY, INC. -- THOMPSON'S WATER SEAL BRAND WATERPROOFING F

8030-00-555-2878

============= Product Identification =================

Product ID:THOMPSON'S WATER SEAL BRAND WATERPROOFING F

MSDS Date:10/18/1988

FSC:8030

NIIN:00-555-2878

MSDS Number: BPVBP === Responsible Party ===

Company Name: THOMPSON & FORMBY, INC.

Address:10136 MAGNOLIA DRIVE

City:OLIVE BRANCH

State:MS ZIP:38654 Country:US Info Phone N um:601-895-5594

Emergency Phone Num:901-685-7555

CAGE:25458

=== Contractor Identification ===

Company Name: THOMPSON & FORMBY, INC

Address:10136 MAGNOLIA DRIVE

Box:City:OLIVE BRANCH

State:MS ZIP:38654 Country:US

Phone:901-895-5594

CAGE:25458

======= Composition/Information on Ingredients ========

Ingred Name: ALIPHATIC PETROLEUM DISTILLATE (MINERAL SPIRITS)

CAS:64475-85-0 RTECS #:PY8240000 Fraction by Wt: 32%

Other REC Limits: NONE SPECIFIED

OSHA PEL:500 PPM ACGIH TLV:100 PPM

Ingred

Name: MINERAL OIL (MINERAL OIL MIST) CAS:64742-54-7 RTECS #:PY8035500 Fraction by Wt: 52% Other REC Limits: NONE SPECIFIED OSHA PEL:5 MG/M3 Ingred Name: VOC: LESS THAN 400 (GRAMS PER LITER LESS WATER) RTECS #:9999999VO Other REC Limits: NONE SPECIFIED Effects of Overexposure: EYE: IRRITATE/RED/TEAR/BLURRED VISION. SKIN: MODERATE IRRITATE/DEFAT/DERMATITIS. INHALE: NASAL/RESPIRATORY IRRITATION/ DIZZY/WEAK/FATIGUE/NAUSE A/HEADACHE/UNCONSCIOUS/ASPHYXIATION. INGEST: GASTROINTEST INAL IRRITATE/NAUSEA/VOMIT/DIARRHEA. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS-CAN BE FATAL. First Aid:SKIN: THOROUGHLY WASH AREA W/SOAP/WATER. REMOVE CONTAMINATED/LAUNDER CLOTHING BEFORE REUSE. EYE: FLUSH W/WATER LIFT LIDS OCCAS. GET MED AID. INGEST: DO NOT INDUCE VOMITING, KEEP WARM/QUIET. GET MED AI D. INHALE: MOVE TO F RESH AIR. ARTIFICIAL RESPIRATION/OXYGEN AS NEEDED. KEEP WARM/QUIET. GET MED AID. Lower Limits: 1.0 Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICAL

Flash Point Method:SCC Flash Point:>100F,>38C

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACE-PIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE MODE WHEN FIGHTING FIRES.

Unusual Fire/Explosion Hazard: VAPORS HEAVIER THAN AIR/TRAV

EL ALONG GROUND/ MOVED BY VENTILATION/IGNITED BY PILOT LIGHT/OTHER FLAMES/IGNITION SOURCES AT LOCATIONS DISTANT FROM HANDLING POINT.
========= Accidental Release Measures ===========
Spill Release Procedures: ABSORB ON SAND/CLAY/OTHER ABSORBENT MATERIALS ELIMINATE IGNITION SOURCES.
======================================
Handling and Storage Precautions:KEEP CONTAINERS CLOSED. STORE/USE AWAY FROM HIGH TEMPS/SPARKS/OPEN FLAME. GROU ND CONTAINERS WHEN POURING/LIMIT FREE FALL TO FEW INCHES TO PREVENT Other Precautions:AVOID PROLONGED/REPEATED BREATHING OF VAPOR OR CONTACT WITH SKIN. KEEP OUT OF REACH OF CHILDREN. STATIC SPARKS. USE ONLY WITH ADEQUATE VENTILATION.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IF TLV IS EXCEEDED USE NIOSH/MSHA APPROVED RESPIRATOR.  Ventilation:USE WITH ADEQUATE VENTILATION TO PREVENT EXCEEDING TLV. Protective Gloves:HYDROCARBON-INSO LUBLE RUBBER/PLASTIC  Eye Protection:SAFETY GLASSES/GOGGLES Other Protective Equipment:NONE  Work Hygienic Practices:AVOID SKIN CONTACT. WASH CONTAMINATED SKIN/ CLOTHING WITH SOAP/WATER.  Supplemental Safety and Health
========= Physical/Chemical Properties ==========
HCC:F4 Boiling Pt:B.P. Text:300 TO 430F Vapor Pres:AIR Spec Gravity:.840 Appearance and Odor:COLORLESS LIQUID WITH PETROLEUM DISTILLATE ODOR. Percent Volatiles by Volume:WT: 40
========= Stability an

Stability Indicator/Materials to Avoid:YES
OXYGEN AND STRONG OXIDIZERS.
Stability Condition to Avoid:KEEP AWAY FROM HEAT/SPARKS/FLAME/OTHER
SOURCES OF IGNITION.
Hazardous Decomposition Products: CARBON DIOXIDE AND CARBON MONOXIDE

d Reactivity Data ========

====== Disposal Considerations ==========

Waste Disposal Methods:PLACE IN CLOSED CONTAINERS. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS GOVERNING COMBUSTIBLE WASTE.

Di sclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.