

GERARD PACKING AND BELTING CORP -- MILA7021C -- 5330-00-599-4521

=====
Product Identification
=====

Product ID:MILA7021C
MSDS Date:01/25/1993
FSC:5330
NIIN:00-599-4521
MSDS Number: BPVBV
=== Responsible Party ===
Company Name:GERARD PACKING AND BELTING CORP
Address:24 MIDLAND AVE
City:HICKSVILLE
State:NY
ZIP:11801
Country:US
Info Phone Num:516-935-2400
Emergency Phone Num:516-935-2400
Preparer's Name:HMIS TECHNICIAN
CAGE:2G277
=== Contractor Identification ===
Company Name:GERARD PACKING AND BELTING CORP
Address:24 MIDLAND AVENUE
Box:City:HICKSVILLE
State:NY
ZIP:11801
Country:US
Phone:516-935-2400
CAGE:2G277

=====
Composition/Information on Ingredients
=====

Ingred Name:ASBESTOS, CHRYSOTILE
CAS:12001-29-5
RTECS #:CI6478500
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.2 FIBERS/CC
ACGIH TLV:2 FIBERS/CC; A1;9293

Ingred Name:RUBBER
Other REC Limits:NONE RECOMMENDED

====

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:ACUTE:MINOR EYS/SKIN IRRITATION.
INGESTION- IRRITATION OF GI TRACT. INHALATION-IRRITATION OF
RESPIRATORY TRACT. CHRONIC: ASBESTOSIS, LUNG CANCER, &
MESOTHELIOMA, ALL OF WHICH ARE DISABLING AND FATAL D ISEASES OF THE
LUNG. INHALATION AND INGESTION OF ASBESTOS FIBERS MAY CA
USE CANCER
OF THE BOWEL.
Explanation of Carcinogenicity:ASBESTOS IS A KNOWN HUMAN CARCINOGEN.
Effects of Overexposure:INHALATION: FATIGUE AND SHORTNESS OF BREATH
THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING. EYES:
IRRITATION. SKIN: IRRITATION. INGESTION: MILD STOMACH DISTRESS.
DIARRHEA, VOMITING, AND NA USEA.
Medical Cond Aggravated by Exposure:ASTHMA, EMPHYSEMA, AND TUBERCULOSIS
ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

=====
== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. SEE DOCTOR. EYES: RINSE
THOROUGHLY WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH
THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEE DOCTOR.
INGESTION: DIL UTE WITH WATER. DO NOT INDUCE VOMITING.SEE DOCTOR.

=====
===== Fire Fighting Measures =====

Flash Point:NOT REQUIRED
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fir
e Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:VACUUM THE MATERIAL WITH A HEPA FILTERED
VACUUM. THE EQUIPMENT SHALL BE USED & EMPTIED SO AS TO MINIMIZE THE
RE-ENTRY OF ASBESTOS INTO THE WORKPLACE. OTHERWISE,

WET THE
MATERIAL WITH WATER & SURFACTANT AND THEN SHOVEL OR MOP UP
CONTAMINATION.

===== Handling and Storage =====

Handling and Storage Precautions: ITEM IS NONFRIABLE & WILL NOT SHED
FIBERS IN NORMAL USE AND STORAGE. USED ITEMS SHALL BE WETTED
BEFORE, DURING & AFTER DISASSEMBLY.

Other Precautions: IF IT IS NECESSARY TO CUT OR IMPACT THE ITEM WHILE
INSTALLING IT, WEAR A RESPIRATOR AND PROTECTIVE CLOTHING. USED
ITEMS SHALL BE IDENTIFIED
AND DISPOSED OF IN ACCORDANCE WITH ALL
LOCAL, STATE AND FEDERAL REGULATIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: WEAR A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF
REQUIRED. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR
HIGH LEVELS OF CONTAMINATES.

Ventilation: LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTICULATE
EMISSIONS. HEPA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN.

Protective Gloves: COTTON OR LEATHER

Eye

Protection: SAFETY GLASSES OR GOGGLES

Other Protective Equipment: USE COVERALLS OR DISPOSABLE CLOTHING.

Work Hygienic Practices: WET WORK TO THE DEGREE POSSIBLE. WASH HANDS
AFTER HANDLING ITEM. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

MSDS GENERATED BY HMIS TECHNICIAN. WHEN HMIS IS ABLE TO OBTAIN AN MSDS
FROM MANUFACTURER, THIS RECORD WILL BE UPDATED. INGREDIENTS ARE
FROM DLSC TIR PART M OR PARTSMASER TECHNICAL CHARACTERISTICS AND
NAME.

===== Physical/Chemical Properties =====

HCC: T6

Solubility in Water: NEGLIGIBLE

Appearance and Odor: BLACK, RUBBER AND ASBESTOS SHEET

Percent Volatiles by Volume: 0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, AND STRONG ALKALIS

Stability Condition to Avoid: ACCUMULATIONS OF DUST

Hazardous Decomposition Products: ASBESTOS DUST

===== Disposal Considerat

ions =====

Waste Disposal Methods:WET THE MATERIAL WITH WATER AND SURFACTANT.
PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS
INTO ANOTHER POLY BAG OR A SAFE PLACE UNTIL IT CAN BE SHIPPED TO AN
APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING
LABEL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America i
n no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.