

TACC INTERNATIONAL CORP. -- NEOPRENE RUBBER/PHENOLIC RESIN ADHESIVE MA --
8040-00-754-2685

===== Product Identification =====

Product ID:NEOPRENE RUBBER/PHENOLIC RESIN ADHESIVE MA

MSDS Date:01/01/1987

FSC:8040

NIIN:00-754-2685

MSDS Number: BPVCN

=== Responsible Party ===

Company Name:TACC INTERNATIONAL CORP.

Address:AIR STATION INDUSTRIAL PARK

Box:390

City:ROCKLAND

State:MA

ZIP:02370

Country:US

I

Info Phone Num:617-878-7015

Emergency Phone Num:617-878-7015

CAGE:0HZU1

=== Contractor Identification ===

Company Name:TACC INTERNATIONAL CORP

Address:AIR STATION INDUSTRIAL PARK

Box:City:ROCKLAND

State:MA

ZIP:02370

Country:US

Phone:781-878-7015

CAGE:0HZU1

===== Composition/Information on Ingredients =====

Ingred Name:HEXANE

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 42-50%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty

:1 LB

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 15-18%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 20-25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:VOC: 645 GRAMS/LITER
RTECS #:9999999VO
Other REC Limits:NONE SP
ECIFIED

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:HEADACHE, DIZZINESS, NAUSEA, UPPER
RESPIRATOR DRYNESS, IRRITATION, DROWSINESS, MENTAL DEPRESSION,
NARCOSIS, DIFFICULTY BREATHING. PERMANENT EFFECTS TO NERVOUS
SYSTEM, BODY ORGANS OR BRAIN. USE W/ADEQU ATE VENTILATION. SKIN:
REMOVAL OF SKIN OILS, IRRITATION, DERMATITIS, EVEN SENSITIZATION
W/LONG OVEREXPOSURE. *

Eff
ects of Overexposure:* EYE: IRRITATION. INGESTION: MAY BE HARMFUL OR
FATAL IF SWALLOWED.

=====
===== First Aid Measures =====

First Aid:INHALATION: GET FRESH AIR, IF NECESSARY, CALL A PHYSICIAN.
SKIN: WASH WITH MILD SOAP AND WATER, APPLY A MILD CREAM. EYES:
FLUSH WITH WATER AT LEAST 15 MINUTES. INGESTION: CALL POISON CENTER
IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:>0F,>

-18C

Lower Limits:1.1

Upper Limits:12.8

Extinguishing Media:FOAM, DRY CHEMICAL, CO2, WATER SPRAY OR FOG

Fire Fighting Procedures:AVOID BREATHING SMOKE. USE AIR SUPPLIED RESCUE EQUIPMENT FOR ENCLOSED AREA. WATER TENDS TO SPREAD BURNING LIQUID IF LARGE AMOUNTS ARE USED.

Unusual Fire/Explosion Hazard:EXTREME FLAMM.VAPOR MAY IGNITE EXPLOSIVELY/FLASH FIRE.NO IGNIT SOURCE/SMOKING.CROSS VENT TO REMOVE VAPOR/SOLVENT ODOR.ELECTRICALLY GROUND CNTNR DURING TRANSFER.

=====
Accidental Release Measures =====

Spill Release Procedures:SMALL QUANTITIES MAY BE DESIGNATED AS HAZARDOUS WASTE UNTIL ALL SOLVENTS AND VAPORS HAVE EVAPORATED. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DRIED ADHESIVE MAY BE DISPOSED OF AS ORDINARY WASTE.

=====
Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. STORE AT 60-95F OUT OF SUN. USE ADEQUATE VENTILATION TO AVOID BREATHING VAPORS WHEN COVER IS REMOVED.

Other Precautions:GROUND ALL EQUIPMENT WHEN HANDLING FLAMMABLE SOLVENTBORNE MATERIALS.

=====
Exposure Controls/Personal Protection =====

Respiratory Protection:IF VAPORS EXCEED TLV USE SELF-CONTAINED MASK (ORGANIC MASK) NIOSH APPROVED.

Ventilation:LOCAL EXHAUST: SUFFICIENT TO KEEP WORKROOM CONCENTRATION BELOW TLV

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:SAFETY GLASSES OR FACE SHIELD

Supplemental Safety and Health

=====
Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:133F,56C

Vapor Pres:136

Vapor Density:>1

Spec Gravity:0.78 (WATER=1)

Evaporation Rate & Reference:>1 (BU AC=1)

Solubility in Water:NIL

Appearance and Odor:KETONE ODOR/CLEAR

Percent Volatiles by Volume:80

=====
Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS. STRONG ACIDS AND STRONG BASES.

Stability Condition to Avoid:FIRE, SPARKS, STATIC ELECTRICITY.

Hazardous Decomposition Products:CARBON MONOXIDE, AND CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DRIED ADHESIVE MAY BE DISPOSED OF AS ORDINARY WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.