View NSN Online: https://aerobasegroup.kr/nsn/3610-01-326-6495

XEROX CORP -- 1R99, 8200/8700/9200/9210/9400/9500/9700/99 -- 3610-01-326-6495

Product ID:1R99, 8200/8700/9200/9210/9400/9500/9700/99

MSDS Date:01/22/1987

FSC:3610

NIIN:01-326-6495

MSDS Number: BPVKL === Responsible Party ===

Company Name:XEROX CORP Address:100 CLINTON AVE S

City:ROCHESTER

State:NY ZIP:14644 Country:US

Info Phone Num:800-828-6571

Emergency Phone N um:716-422-2177

CAGE:0E6G9

=== Contractor Identification ===
Company Name:XEROX CORP
Address:300 MAIN ST NO 27C

City:EAST ROCHESTER

State:NY ZIP:14645 Country:US

Phone:800-828-6571; 800-351-2024

CAGE:0E6G9

Company Name:XEROX CORPORATION Address:100 CLINTON AVE SOUTH

Box:City:ROCHESTER

State:NY

ZIP:14644-1877 Country:US

Phone:800-828-6571/716-422-2177

CAGE:26921

====== Composition/Information on Ingredients ========

Ingred Name:NICKEL; (NICKEL BELT), (SUBSTRATE) (SARA III)

CAS:744

0-02-0 RTECS #:QR5950000 Fraction by Wt: 75-80%

OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3

Ingred Name: COATING (CONSISTING OF INGREDIENTS 3 & 4)

RTECS #:9999999ZZ Fraction by Wt: 20-25%

Ingred Name: SELENIUM (SARA III)

CAS:7782-49-2

RTECS #:VS7700000 Fraction by Wt: >99% OSHA PEL:0.2 MG/M3 ACGIH TLV:0.2 MG/M3

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: ARSENIC (SARA III)

CAS:7440-38-2

RTECS #:CG0525000 Fraction by Wt: 5 G/KG.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcin

Health Hazards Acute and Chronic:THIS MATERIAL HAS BEEN EXTENSIVELY TESTED & EVALUATED BY XEROX CORPORATION. WHEN USED AS INTENDED, IT DOES NOT REPRESENT ANY KNOWN HEALTH OR SAFETY HAZARD.

Explanation of Carcinogenicity:NICKEL:GROUP 1(IARC), ANTICIPATED TO BE A CARCIN (NTP). ARSENIC:GROUP 1(IARC), KNOWN CARCIN (NTP), OSHA REGULATED.

Effects of Overexposure: NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure: NONE WHEN USED A


S DESCRIBED BY

PRODUCT LITERATURE.

First Aid:INGEST:CALL MD IMMEDIATELY . INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O*2/ARTF RESP) . EYES:FLUSH W/WATER FOR AT LEAST 15 MINUTES. SKIN:WASH W/SOAP & WATER.

Extinguishing Media:WATER, CO*2, FOAM.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . WHEN I



arance and Odor:SOLID; ODORLESS.
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG ACIDS. Stability Condition to Avoid:AVOID EXPOSURE TO HIGH TEMPERATURES. Hazardous Decomposition Products:OXIDES OF SELENIUM & ARSENIC.
======= Disposal Considerations ==========
Waste Disposal Methods:RETURN USED/DMGD PHOTORECEPTOR TO XEROX/SUPPLIER. UNDER PRESENT EPA REGS, IT IS NOT CLASSIFIED AS HAZ WASTE. H OWEVER, DISP IN CHEM WASTE LANDFILL IS RECOM. ENSURE
CONFORMITY W/FEDERAL, STATE OR LOCAL REGULATIONS.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.