View NSN Online: https://aerobasegroup.com/nsn/9150-00-935-4090

EXXON CO USA, A DIV OF EXXON CORP. -- TURBO OIL 274 -- 9150-00-935-4090

Product ID:TURBO OIL 274 MSDS Date:12/02/1991 FSC:9150 NIIN:00-935-4090 **MSDS Number: BPVPR** === Responsible Party === Company Name: EXXON CO USA, A DIV OF EXXON CORP. Address:800 BELL ST Box:2180 **City:HOUSTON** State:TX ZIP:77252-2180 Country:US Info Phone Num:713-656-3424/5949 **Emergency Phone N** um:713-656-3424/800-424-9300(CHEMTREC) CAGE:29700 === Contractor Identification === Company Name: EXXON COMPANY U.S.A. Box:2180 **City:HOUSTON** State:TX ZIP:77252-2180 Country:US Phone:713-656-5949 / 713-656-3424 CAGE:29700 Ingred Name: BASE LUBRICANT OF DIESTERS Other REC Limits:NONE RECOMMENDED

Ingred Name:PROPRIETARY ADDITIVES Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5 MG/M3. Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE-EYE:MAY CAUSE IRRITATION.SKIN:PROLONGED/REPEATED CONTACT MAY CAUSE IRRITATION & DERMATITIS.INHALED:VAPORS/OIL MISTS MAY BE MILDLY IRRITATING TO THE NOSE,THROAT & RESPIRATORY TRACT.ORAL:EXPECTED TO HAVE A LOW ORDER OF TOXICITY,BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS MAY CAUSE

==

Effects of Overexposure:MAY IRRITATE EYES. PROLONGED/REPEATED SKIN CONTACT MAY CAUSE IRRITATION & DERMATITIS. VAPORS/OIL MISTS MAY BE MILDLY IRRITATING. EXPECTED TO HAVE A LOW ORDER OF ORAL TOXICITY, BUT MINUTE AMOUNTS ASPIR ATED INTO THE LUNGS MAY CAUSE LUNG INJURY. IF GREASE IS INJECTED THROUGH THE SKIN, CAN CAUSE SERIOUS TISSUE DAMAGE.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THE SUBSTANCE.

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST.INHALED:REMOVE TO FRESH AIR.PROVIDE CPR/OXYGEN IF NEEDED.EYES:FLUSH WITH WATER FOR 15 MINUTES,HOLDING EYELIDS OPEN.SKIN:WIPE OFF EXCESS & WASH SKIN WITH SOAP & WAT ER.ORAL:DO NOT INDUCE VOMITING.CALL A PHYSICIAN IMMEDIATELY.

Flash Point Method:COC Flash Point:430F ,221C MIN Autoignition Temp:Autoignition Temp Text:723F Lower Limits:1% Upper Limits:12% Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL. DO NOT USE A DIRECT STREAM OF WATER. PRODUCT WILL FLOAT & REIGNITE Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS IN + PRESSURE MODE. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard: FUMES, SMOKE, CARBON MONOXIDE, SULFUR

OXIDES, ALDEHYDES AND OTHER DECOMPOSITION PRODUCTS, IN THE CASE OF INCOMPLETE COMBUSTION.

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENTS. VENTILATE AREA. STOP LEAK. RECOVER FREE PRODUCT. CONTAIN LARGE SPILL. PUMP IT TO TRUCK. SOAK UP RESIDUE/SMALL SPILLS WITH CLAY/SAND. TRANSFER TO CONTAINER FOR DISPOSAL. REP ORT SPILLS AS REQUIRED. KEEP PRODUCT OUT OF SEWERS

=================== Handling and Stor

Handling and Storage Precautions:STORAGE-STORE IN COOL PLACE.KEEP AWAY FROM HEAT,FLAME & STRONG OXIDANTS.

Other Precautions: EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE WHICH COULD INCLUDE FLAMMABLE OR EXPLOSIVE VAPORS. CONSULT APPROPRIATE FEDERAL, STATE & LOCAL AUTHORITIES BEFORE REUSING, RECONDITIONING, RECLAIMING, RECYCLING / DISPOSING OF EMPTY

**Respiratory Protection:N** 

CONTAINERS.

ON REQUIRED UNDER NORMAL CONDITIONS. IF HIGH VAPOR OR MIST CONCENTRATIONS EXPECTED, USE NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPORS AND MISTS. WEAR SUPPLIED-AIR RESPIRATOR PROTECTION IN CONFINED OR ENCLOSED SPACES. IF NEEDED. Ventilation: USE LOCAL EXHAUST TO CAPTURE VAPOR, MISTS OR FUMES, IF NECESSARY. PROVIDE SUFFICIENT VENTILATION TO PREVENT EXPLOSION. Protective Gloves: CHEMICAL-RESISTANT, IF NEEDED Eye Protection: CHEMICAL SPLASH GOGGLES/FACE SHIELD Other Protective Equipment :EYE WASH STATION, QUICK DRENCH SHOWER AND **IMPERVIOUS CLOTHING** Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR. Supplemental Safety and Health FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PNI A UNDER THE SAME NSN. 

HCC:V6

Boiling Pt:B.P. Text: 770F,410C Melt/Freeze Pt:M.P/F.P Text:-60F,-51C Vapor Pres: 5 Spec Gravity:0.9 5 Viscosity:35 CST @ 40C Evaporation Rate & amp; Reference: