View NSN Online: https://aerobasegroup.kr/nsn/1260-01-073-5886

Product ID:11507453 NEODYMIUM DOPED YTRIUM ALUMINUM GA MSDS Date:05/01/1991 FSC:1260 NIIN:01-073-5886 MSDS Number: BPWYY === Responsible Party === Company Name: UNION CARBIDE CHEMICALS & PLASTICS CO., INC. Address:750 S 32ND STREET City:WASHOUGAL State:W А ZIP:98671 Country:US Info Phone Num:206-835-8566 Emergency Phone Num:800-822-4357 CAGE:DO713 === Contractor Identification === Company Name: UNION CARBIDE CHEM & PLASTICS CO INC Address:39 OLD RIDGEBURY RD City:DANBURY State:CT ZIP:06817-0001 Phone:203-794-6753/304-744-3487 CAGE:DO713

Ingred Name:NEODYMIUM OXIDE CAS:1313-97-9 Fraction by Wt: 0.85% Other REC Limits:NONE RECOMMENDED

Ingred Name:YTRIUM OXIDE CAS:1314-36-9 RTEC

S #:ZG3850000
Fraction by Wt: 56.88%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ALPHA-ALUMINA (ALUMINUM OXIDE) (EPA LISTS ONLY FIBROUS FORMS) (SARA III) CAS:1344-28-1 RTECS #:BD1200000 Fraction by Wt: 42.83% Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards A cute and Chronic:NO EVIDENCE OF ADVERSE EFFECTS. Effects of Overexposure:NO EVIDENCE OF ADVERSE EFFECTS. Medical Cond Aggravated by Exposure:NONE

First Aid:EYES: FLUSH WITH WATER. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: NO HARMFUL EFFECTS.

Extinguishing Media:NON-FLAMMABLE. USE EXTINGUISHING MEDIA APPROPIATE FOR

SURROUNDING FIRE.

Spill Release Procedures: BROKEN CRYSTALS HAVE SHARP EDGES. GLOVES SHOULD BE WORN WHEN CLEANING UP A BROKEN CRYSTAL.

Handling and Storage Precautions:NORMAL PRECAUTIONS COMMON TO SAFE
MANUFACTURING PRACTICES SHOULD BE FOLLOWED IN HANDLING AND STORAGE.
ALWAYS MACHINE A CRYSTAL USING WET METHODS.
Other Precautions:USE OF THIS CRYST

AL IN LASER OPERATIONS SHOULD BE SUPERVISED BY QUALIFIED, KNOWLEDGEABLE PERSONNEL, IN ACCORDANCE WITH ANSI Z 136.1, THE AMERICAN NATIONAL STANDARD FOR THE SAFE USE OF LASERS.

Respiratory Protection: IF EXCESSIVE DUSTING OCCURS WHEN MACHINING, WEAR NIOSH OR MSHA APPROVED DUST RESPIRATOR. Ventilation:LOCAL DUST PICK UP RECOMMENDED WHEN MACHINING. Protective Gloves: RECOMMENDED. Eye Protection: SAFETY GLASSES. Other Protective Equipment: NONE Work Hygienic Practices: STANDARD PRACTICES AND RECOMMENDED PROCEDURES. Supplemental Safety and Health PROLONGED CONTACT WITH DUST OR POWDER FROM MACHINING MAY CAUSE DRYING OF SKIN. *** NOTE: THIS IS AN ARTICLE. MANUFACTURER SUPPLIED MSDS

FOR MANUFACTURING OPERATIONS ***

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:3578F,1970C Spec Gravity:4.55 Solubility in Water:NEGLIGIBLE Appearance and Odor:TRANSPAR ENT, PURPLE. NO ODOR.

Stability Indicator/Materials to Avoid:YES ETHYLENE OXIDE, CHROMIUM TRIFLUORIDE. Stability Condition to Avoid:NONE Hazardous Decomposition Products:NONE

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): $\ensuremath{\mathsf{T}}$

his information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.