

SPECTRUM CHEMICAL MANUFACTURING CORP. -- PETROLATUM -- 6505-00-133-8025

===== Product Identification =====

Product ID:PETROLATUM

MSDS Date:05/10/1991

FSC:6505

NIIN:00-133-8025

MSDS Number: BPYCS

=== Responsible Party ===

Company Name:SPECTRUM CHEMICAL MANUFACTURING CORP.

Address:14422 SOUTH SAN PEDRO STREET

City:GARDENA

State:CA

ZIP:90248-2027

Country:US

Info Phone Num:213-516-8000

Emergency Phone

Num:213-516-8000

CAGE:63415

=== Contractor Identification ===

Company Name:SPECTRUM LABORATORY PRODUCTS INC

Address:14422 S SAN PEDRO ST

Box:City:GARDENA

State:CA

ZIP:90248-2027

Country:US

Phone:310-516-8000/FAX: 310-516-9843

CAGE:63415

===== Composition/Information on Ingredients =====

Ingred Name:GREASE, PETROLEUM

CAS:8009-03-8

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inha

lation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:ACUTE: INHALATION OF MIST MAY CAUSE
RESPIRATORY IRRITATION, LIPID PNEUMONIA/GRANULOMA OF LUNG. CONTACT
WITH SKIN MAY CAUSE HYSENSITIVITY REACTIONS IN SOME. CONTACT WITH
EYES MAY CAUSE IRRITATION. SWAL LOWING LARGE AMOUNTS MAY CAUSE
DIGESTIVE SYSTEM IRRITATION. CHRONIC: SKIN CONTACT MAY CAUSE
FOLLICULITIS.

Explanation of Carcinogenicity:IARC LIST MINERAL OI
LS AS IARC GROUP
3-INADEQUATE EVIDENCE.

Effects of Overexposure:INHALATION: COUGHING, SHORTNESS OF BREATH.
EYES: REDNESS, TEARING, BLURRED VISION, DISCOMFORT. SKIN: RASH,
REDNESS, DISCOMFORT. INGESTED: NAUSEA, VOMITING, DIARRHEA.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:INHALED: MOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF
BREATHING STOPPED. GIVE OXYGEN IF BREATHING DI
FFICULT. GET MEDICAL
ATTENTION. EYES: FLUSH WITH LOTS OF WATER FOR 15 MINUTES, HOLD LIDS
OPEN. SEE DOCTOR. SKIN: REMOVE CONTAMINATED CLOTHES. WASH WITH
SOAP AND WATER. INGESTED: TREAT SYMTOMATICALLY AND SUPPORTIVLY. GET
MEDICAL ATTENTION. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:>360F,>182C
Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR
REGULAR FOAM
Fi
re Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. MOVE
CONTAINER FROM FIRE IF CAN BE DONE AT NO RISK. DO NOT SCATTER
SPILLED MATERIAL WITH HIGH PRESSURE WATER.
Unusual Fire/Explosion Hazard:DIKE FIRE CONTROL WATER FOR LATER
DISPOSAL.

===== Accidental Release Measures =====

Spill Release Procedures:SWEEP UP AND PLACE IN CONTAINERS FOR LATER
DISPOSAL. DO NOT FLUSH TO SEWER OR WATERWAYS. KEEP UNECESSARY
PEOPLE AWAY.
Neutralizing Agent:

NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM INCOMPATIBLE MATERIALS.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF CONDITIONS WARRANT;
USE NIOSH/MSHA APPROVED RESPIRATOR, OR SUPPLIED AIR RESPIRATOR, OR SCBA, AS SITUATION REQUIRES. USE IN ACCORDANCE WITH 29 C

FR

1910.134.

Ventilation:USE LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW REGULATORY LIMITS IF VAPORS OR MISTS GENERATED.

Protective Gloves:RUBBER IF PROLONGED OR REPEATED CONTACT

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYE WASH STATION

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>500F,>260C

Melt/Freeze Pt:M.P/F.P Text:>100F,>38C

Vapor Pres: