View NSN Online: https://aerobasegroup.kr/nsn/6830-00-182-6315

Product ID:29547-7 METHANE MSDS Date:10/29/1987 FSC:6830 NIIN:00-182-6315 **MSDS Number: BPYDN** === Responsible Party === Company Name: ALDRICH CHEMICAL CO INC. Address:1001 W. ST. PAUL AVE Box:2060 City:MILWAUKEE State:WI ZIP:53201 Country:US Info Phone Num:414-273-3850 Emergency Phone Num:414-273-3850 CAGE:60928 === Contractor Identification === Company Name: ALDRICH CHEMICAL CO INC Address:1001 WEST ST PAUL AVE Box:355 City:MILWAUKEE State:WI ZIP:53233 Country:US Phone:414-273-3850 CAGE:60928 Ingred Name:METHANE CAS:74-82-8 RTECS #:PA1490000 Fraction by Wt: 100% Other REC Limits:NONE SPECIFIED ACGIH TLV:ASPHYXIANT; 9192

Routes of Entry: Inhalation:YES

 Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: INHALATION- ASPHYXIATION, CNS EFFECTS. CHRONIC: UNKNOWN. Explanation of Carcinogenicity:NONE Effects of Overexposure:INHALATION: DIZZINESS, HEADACHE, EXCITATION, EXCESS, SALIVATION, VOMITING, AND UNCONSCIUOSNESS. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================
First Aid:INHALATION: REM OVE TO FRESH AIR, RESUSCITATE /GIVE OXYGEN IF NEEDED. GET IMMEDIATE MEDICAL ATTENTION.
======================================
 Flash Point:-306F,-188C Lower Limits:5 % Upper Limits:15 % Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, WATER SPRAY, OR FOG. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. Unusual Fire/Explosion Hazard:COMPRESSED FLAMMABLE GAS. FORMS EXPLOSIVE MIXTURES WITH AIR AND OXIDIZERS. TOXI C FUMES MAY BE PRODUCED ON COMBUSTION.
======================================
Spill Release Procedures: EVACUATE AREA. ISOLATE AND DENY ENTRY. REMOVE ALL SOURCES OF IGNITION. STOP LEAK IF CAN BE DONE AT NO RISK. WEAR PROPER RESPIRATORY PROTECTION. VENTILATE AREA. BEFORE ENTRY CHECK COMPOSITIN OF ATMOSPH ERE. Neutralizing Agent:NONE
======================================
Handling and Storage Precautions:STORE IN ACOOL, D RY, WELL VENTILATED AREA, AWAY FROM SOURCES OF IGNITION. Other Precautions:USE SPARK PROOF TOOLS. PROPERLY GROUND AND BOND CYLINDERS.
======================================
Respiratory Protection:USE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS IF TLV IS EXCEEDED OR WHEN USING IN CONFINED SPACES. Ventilation:USE EXPLOSION-PROOF MECHANICAL VENTILATION. Protective Gloves:WORK GLOVES Eye Protection:SAFETY GLASSES Other Protective Equipment:NONE NORMAL

LY REQUIRED.

Work Hygienic Practices: WASH HANDS BEFORE EATING, DRINKING, OR SMOKING. DO NOT SMOKE IN WORK AREA.

Supplemental Safety and Health

THIS IS A COMPONENT GAS OF A GAS MIXTURE USED IN CALIBRATION DEVICES. THERE ARE A TOTAL OF 6 GASES., WHICH ARE 200 PPM METHANE, 50 PPM FREON 12, 50 PPM FREON 114, 50 PPM UCON 11, 10 PPM HEXANE, BALANC E AIR.

HCC:G3

Boiling Pt:B.P. Text:-258F,-161C Melt/Freeze Pt:M.P/F.P Text:-297F,-183C Vapor Density:0.554 @32F Solubility in Water:SLIGHT Appearance and Odor:COLORLESS, ODORLESS GAS Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS, CHLORINE, BROMINE PEANTAFLUORIDE, YELLOW
MERCURIC OXIDE, LIQUID OXYGEN, NITROGEN TRIFLUORIDE.
Stability Condition to Avoid:TEMPERATURES IN EXCESS OF 700C.
Hazardous Decomposition Products:OXIDES OF CARBON.

=====

Waste Disposal Methods:CONTACT LOCAL ENVIRONMENTAL MANAGER. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability

for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.