

DAVLIN PAINT CO INC -- COVERBRITE INTERIOR LATEX -- 8010-00-579-9199

=====  
Product Identification  
=====

Product ID:COVERBRITE INTERIOR LATEX

MSDS Date:03/09/1993

FSC:8010

NIIN:00-579-9199

MSDS Number: BPZSB

=== Responsible Party ===

Company Name:DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Preparer's Name:DGSC-SSH

CAGE:3Z268

=== Contractor Identi

fication ===

Company Name:DAVLIN PAINT CO INC

Address:700 ALLSTON WAY

Box:2308

City:BERKELEY

State:CA

ZIP:94702

Country:US

Phone:510-848-2863

CAGE:3Z268

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LITHOPONE

CAS:1345-05-7

Fraction by Wt: 9%

Other REC Limits:NONE SPECIFIED

Ingred Name:SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: 0.23%

Other REC Limits:0.05 MG/CUM NIOSH

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.1 MG/M3 RDUST;9293

===

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:NOT SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: IRRITATION OF EYES, NOSE,  
THROAT/LUNGS. SKIN: IRRITATION, DIARRHEA, RASH & DRYING. INGESTION:  
GASTROINTESTINAL IRRITATION, VOMITING, NAUSEA.

Explanation of Carcinogenicity:THIS PRODUCT CONTAINS A CHEMICAL(S)  
KNOWN TO

THE STATE OF CALIFORNIA TO CAUSE CANCER/BIRTH  
DEFECTS/REPRODUCTIVE HARM.

Effects of Overexposure:INHALATION: IRRITATION OF EYES, NOSE,  
THROAT/LUNG. SKIN: PROLONGED/REPEATED CONTACT MAY CAUSE IRRITATION,  
DRYING, DIARRHEA & RASH. INGESTION: GASTROINTESTINAL IRRITATION,  
VOMITING, & NAUSEA.

Medical Cond Aggravated by Exposure:DERMATITIS/RASH

=====  
First Aid Measures  
=====

First Aid:INHALATION: MOVE PERSON TO FRESH AIR. EYE: FLUSH W/LARGE  
QU

ANTITIES OF WATER FOR 15 MINS & CALL PHYSICIAN. SKIN: WASH  
THOROUGHLY W/SOAP & WATER. INGESTION: DRINK 1-2 GLASSES OF WATER TO  
DILUTE. DON'T INDUCE VOMITING. CONSULT PHYSICIAN.

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC

Flash Point:241F,116C

Extinguishing Media:ALCOHOL FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:IF THIS MATERIAL IS INVOLVED IN A FIRE,NIOSH  
APPROVED SELF-CONTAINED RESPIRATORY EQUIPMENT SHOULD BE WORN.

Unusual Fir

e/Explosion Hazard:ALTHOUGH THIS MATERIAL IS NON-FLAMMABLE,  
VAPORS CAN COLLECT >LIQUID IN CLOSED CONTAINERS/STORAGE VESSELS.  
CLOSED CONTAINERS MAY EXPLODE WHEN EXTREME TO HEAT.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY,  
USE CARE TO AVOID FAILING. DIKE/CONTAIN SPILL W/INERT MATERIAL.  
TRANSFER LIQUID & DIKING MATERIAL TO CONTAINERS FOR RECOVERY &  
DISPOSAL. KEEP SPILLS OUT OF SEWERS

& OPEN WATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DON'T STORE >100F. KEEP FROM FREEZING.  
DON'T TAKE INTERNALLY. KEEP CONTAINERS CLOSED WHEN NOT IN USE.  
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:WEAR MSHA/NIOSH APPROVED RESPIRATOR TO MAINTAIN  
MISTS & VAPORS