View NSN Online: https://aerobasegroup.kr/nsn/6850-01-281-5703

Product ID:CLC TONER (BLACK); F41-5101-700 MSDS Date:12/01/1991 FSC:6850 NIIN:01-281-5703 MSDS Number: BPZVX === Responsible Party === Company Name: CANON U.S.A., INC. Address:ONE CANON PLAZA City:LAKE SUCCESS State:NY ZIP:11042 Country:US Info Phone Num:516-488-6700 **Emergency Phone Num:516-**488-6700 800-424-9300(CHEMTREC) CAGE:08YZ7 === Contractor Identification === **Company Name: CANON USA INC** Address: ONE CANON PLZ Box:City:NEW HYDE PARK State:NY ZIP:11042 Country:US Phone:516-328-5000; 5600 CAGE:08YZ7

Ingred Name:BISPHENOL A PROPYLENE OXIDE FUMARATE CAS:39382-25-7 Fraction by Wt: 85-95% Other REC Limits:NONE RECOMMENDED

Ingred Name:SALICYLIC ACID CHELATE (CHROMIUM III) CAS:72869-85-3 Fraction by Wt: 1-5% Other **REC Limits:NONE RECOMMENDED**

Ingred Name:BLUE PIGMENT (PHTHALOCYANINE BLUE) CAS:147-14-8 Fraction by Wt: 3-15% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture: OSHA TWA=0.5 MG/M3 AS CHROMIUM Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: INHAL: MINIMAL RESPIRATORY TRACT IRRITANT.DUST IS NON-TOXIC.SKIN/EYES/INGEST:MANUFACTURER S TATES THAT THERE ARE NO KNOWN HEALTH HAZARDS. Explanation of Carcinogenicity: MANUFACTURER HAS PERFORMED A MUTAGENICITY TEST ON S. TYPHIMURIUM.THE RESULT IS NEGATIVE. Effects of Overexposure: INHAL: MINIMAL RESPIRATORY IRRITATION. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. First Aid:INHAL:REMOVE TO FRESH AIR.EYES:FLUSH WITH WATER,HOLDING LIDS **OPENED.IF IRRITATION PERSISTS, CALL PHYSICIAN.SKIN:** WASH WITH SOAP AND WATER.INGEST: DRINK SEVERAL GLASSES OF WATER.CALL PHYSICIAN. Extinguishing Media:WATER, DRY CHEMICAL, CARBON DIOXIDE. Fire Fighting Procedures: HMIS SUGGESTS USING A SELF CONTAINED BREATHING APPARATUS WHENEVER FIGHTING A CHEMICAL FIRE. Unusual Fire/Explosion Hazard: THIS MATERIAL IS AN EXPLOSION HAZARD IN THE DUST(POWDER) FORM. Spi II Release Procedures: SWEEP ONTO PAPER AND PLACE IN FIBER CARTON FOR DISPOSAL. Neutralizing Agent:NOT APPLICABLE.

Handling and Storage Precautions: KEEP OUT OF REACH OF CHILDREN. KEEP AWAY FROM OXIDIZING MATERIALS. Other Precautions: NONE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT. Ventilation: GENERAL VENTILATION. Protective G

loves:NONE REQUIRED. Eye Protection:NONE REQUIRED. Other Protective Equipment:NONE. Work Hygienic Practices: WASH HANDS. USE PRUDENT HYGENIC AND SANITARY PRACTICES. Supplemental Safety and Health CHROMIUM METAL IS SARA REPORTABLE >0.5WT%;CHROMIUM III COMPOUNDS >2.0WT%. HCC:N1 Melt/Freeze Pt:M.P/F.P Text:212F,100C Vapor Pres:NEGLIGIBLE Spec Gravity:1.0-1.2 Evaporation Rate & amp; Reference: NEGLIGIBLE Solubility in Water:N EGLIGIBLE Appearance and Odor: POWDER, FINE; COLOR NOT REPORTED; SLIGHT PLASTIC-LIKE ODOR Percent Volatiles by Volume:NEGLIG Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS. Stability Condition to Avoid: MAKING DUST AROUND SOURCES OF IGNITION. Hazardous Decomposition Products: CARBON DIOXIDE AND CARBON MONOXIDE. Waste Disposal Methods:MANUFACTURER STATES NO SPECIAL REQUIREMENTS.FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume res ponsibility for the suitability of this information to their particular situation.