

FLEXITALLIC GASKET CO -- ASBESTOS FILLED SPIRAL WOUND GASKET -- 5330-00-989-3322

=====
Product Identification
=====

Product ID:ASBESTOS FILLED SPIRAL WOUND GASKET

MSDS Date:07/09/1986

FSC:5330

NIIN:00-989-3322

MSDS Number: BQCTX

=== Responsible Party ===

Company Name:FLEXITALLIC GASKET CO

Address:6915 LAPORTE RD

Box:760

City:DEER PARK

State:TX

ZIP:77536

Country:US

Info Phone Num:713-479-3491

Emerg

ency Phone Num:713-479-3491

CAGE:58156

=== Contractor Identification ===

Company Name:FLEXITALLIC GASKET CO INC.

Address:6915 LAPORTE RD

Box:760

City:DEER PARK

State:TX

ZIP:77536

Country:US

Phone:713-479-3491

CAGE:58156

Company Name:FLEXITALLIC GASKET CO.INC

Address:8440 REMINGTON AVENUE

Box:286

City:PENNSAUKEN

State:NJ

ZIP:08110

Country:US

Phone:609-486-4400

CAGE:72433

=====
Composition/Information on Ingredients
=====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:

CI6478500
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.2 FIBERS/CC
ACGIH TLV:2 FIBERS/CC; A1;9293

Ingred Name:NATURAL LATEX
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:ACUTE:MINOR EYS/SKIN IRRITATION.
INGESTION- IRRITATION OF GI TRACT. INHALATION-IRRITATION OF
RESPIRATORY TRACT. CHRO
NIC: ASBESTOSIS, LUNG CANCER, &
MESOTHELIOMA, ALL OF WHICH ARE DISABLING AND FATAL D ISEASES OF THE
LUNG. INHALATION AND INGESTION OF ASBESTOS FIBERS MAY CAUSE CANCER
OF THE BOWEL.
Explanation of Carcinogenicity:THIS PRODUCT CONTAINS ASBESTOS
[12001-29-5], AN OSHA REGULATED CARCINOGEN.
Effects of Overexposure:INHALATION: FATIGUE AND SHORTNESS OF BREATH
THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING. EYES:
IRRITATION. SKIN: IRRITATION. INGESTION: MILD STOMACH D
ISTRESS.
DIARRHEA, VOMITING, AND NA USEA.
Medical Cond Aggravated by Exposure:ASTHMA, EMPHYSEMA, AND TUBERCULOSIS
ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. SEE DOCTOR. EYES: RINSE
THOROUGHLY WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH
THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEE DOCTOR.
INGESTION: DIL UTE WITH WATER. DO NOT
INDUCE VOMITING.SEE DOCTOR.

=====
===== Fire Fighting Measures =====

Flash Point:NOT REQUIRED
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====
===== Accidental Release Measures =====

=====

Spill Release Procedures:VACUUM THE MATERIAL WITH A HEPA FILTERED VACUUM. THE EQUIPMENT SHALL BE USED & EMPTIED SO AS TO MINIMIZE THE RE-ENTRY OF ASBESTOS INTO THE WORKPLACE. OTHERWISE, WET THE MATERIAL WITH WATER & SURFACTAN T AND THEN SHOVEL OR MOP UP CONTAMINATION.

===== Handling and Storage =====

Handling and Storage Precautions:ITEM IS NONFRIABLE & WILL NOT SHED FIBERS IN NORMAL USE AND STORAGE. USED ITEMS SHALL BE WETTED BEFORE, DURING & AFTER DISASSEMBLY.

Other Precautions:IF IT IS NECESSARY TO CUT OR IMPACT THE ITEM WHILE INSTALLING IT, WEAR A RESPIRATOR AND PROTECTIVE CLOTHING. USED ITEMS SHALL BE IDENTIFIED AND DISPOSED OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDE RAL REGULATIONS FOR ASBESTOS DISPOSAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF REQUIRED. WEAR SELF-CONTAINED BREATHING APPARAT US IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES.

Ventilation:LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTICULATE EMISSIONS. HEPA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN.

Protective Gloves:COTTON OR LEATHER

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:USE COVERALLS OR DISPOSABLE CLOTHING.

Work Hygienic Practices:WET WORK TO THE DEGREE POSSIBLE. WASH HANDS AFTER HANDLING ITEM. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

==

===== Physical/Chemical Properties =====

HCC:T6

Spec Gravity:2.5 (WATER=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIGHT BLUE, NO ODOR

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER. HMIS-STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, AND STRONG ALKALIS

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

HMIS-ACCUMUL

ATIONS OF DUST

Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

HMIS-ASBESTOS DUST

===== Disposal Considerations =====

Waste Disposal Methods:WET THE MATERIAL WITH WATER AND SURFACTANT.
PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS
INTO ANOTHER POLY BAG OR A SAFE PLACE UNTIL IT CAN BE SHIPPED TO AN
APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING
LABEL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.