

CAAP CO INC -- C-W4 WHITE POLYURETHANE RAIN EROSION COATIN -- 8010-01-132-2976

=====
Product Identification
=====

Product ID:C-W4 WHITE POLYURETHANE RAIN EROSION COATIN

MSDS Date:08/01/1992

FSC:8010

NIIN:01-132-2976

Kit Part:Y

MSDS Number: BQCWS

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPES FARM RD

City:MILFORD

State:CT

ZIP:06460-3670

Country:US

Info Phone Num:203-877-0375

Emergency Phone Num:203-877-0375

Preparer's Name:CHRISTINE L. SLEDGE

CAGE:60922

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENE (SARA 313)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 46.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM/STEL 150 PPM

ACGIH TLV:100 PPM/STEL 150 PPM

EPA Rpt Q

ty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYLISOBUTYLKETONE (MIBK) (SARA 313)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 16.6%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 1.9%
Other REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:RESIDUAL METHYLENE BIS(4-CYCLOHEXYLISOCYANATE)
C
AS:5124-30-1
RTECS #:NQ9250000
Fraction by Wt: 0-0.5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:0.01 PPM
ACGIH TLV:0.005 PPM

Ingred Name:ISOCYANATE TERMINATED POLYESTER PREPOLYMER
CAS:54954-83-5
Fraction by Wt: 35.0%
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: CONTACT MAY DAMAGE EYES,
IR

RITATE SKIN, & CAUSE RESPIRATORY IRRITATION UPON INHALATION.

CHRONIC: REPEAT/PROLONG EXPOSURE MAY CAUSE DEFATTING OF THE SKIN, DERMATITIS, AND POSSIBLE SENSITIZATION. INHALATION OF VERY HIGH VAPOR CONCENTRATIONS OR PROLONGED EXPOSURE MAY CAUSE NEURAL DYSFUNCTION, KIDNEY & LIVER DAMAGE.

Effects of Overexposure:VAPOR EXPOSURE: BURNING EYES, HEADACHE, DIZZINESS, THROAT IRRITATION, LOSS OF APPETITE, NAUSEA. CONTACT: MAY CAUSE IRRITATION OF SKIN, BURNING OF SKIN OR EYES.

Medi
cal Cond Aggravated by Exposure:PREEXISTING ALLERGIES, EYE, SKIN AND RESPIRATORY DISORDERS.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/WTR, GET IMMEDIATE MED ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN PROMPTLY W/ SOAP & WATER. IF SIGNS & SYMPTOMS OF EXPOSURE EXIST, GET IMMEDIATE MED ATTENTION. INHALATION: REMOVE TO FRESH AIR, GIVE ARTIFICIAL RESPIRATION IF NECESSARY, GET IMMEDIATE MED ATTENTION. INGESTION: DO NOT INDUCE VOMITING, GET IMMEDIATE MED ATTENTION. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT BREATHING VOMITUS INTO LUNGS.

===== Fire Fighting Measures =====

Flash Point Method:TOC
Flash Point:68.0F,20.0C
Lower Limits:1.0
Upper Limits:8.0
Extinguishing Media:CO2, FOAM, DRY CHEMICAL
Fire Fighting Procedures:USUAL METHODS FOR FLAMMABLE LIQUID. NOT MISCIBLE W/WATER-USE WATER TO COOL FIRE EXPOSED CONTAINERS. WEAR SCBA ALONG W/PROTECTIVE CLOTHING, SOLVENT RESISTANT COATS/BOOTS/GLOVES/HELMET
Unusual Fire/Explosion Hazard:NONE, PRODUCT IS A FLAMMABLE LIQUID.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES-DON'T SMOKE IN AREA. WEAR PROTECTIVE EQUIPMENT W/SOLVENT RESISTANT GLOVES/APRON/BOOTS/SCBA IN PRESSURE DEMAND MODE/POSITIVE PRESSURE AIR-SUPPLIED RESPIRATOR. DIKE & SOAK UP W/ABSORBENT. CLEANUP ABSORB/CONTAIN. SWEEP/WET MOP W/ SOAP & WATER. VENT AREA.

===== Handling and Storage =====

Handling and Storage

Precautions:FOR MORE COMPLETE HEALTH/SAFETY INFO
ON USE OF COATINGS CONTAINING RESIDUAL ISOCYANATE PLEASE CONSULT
MOBAYS HEALTH AND SAFETY INFORMATION BROCHURE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF VAPOR/MIST, WEAR NIOSH RESP FOR EMISSION
LEVELS AT POINT OF USE. RESP W/FULL FACEPIECE/PURIFY CARTRIDGE RESP
FOR ORGANIC VAPOR/MIST, SCBA IN PRESS DEMAND MODE/POSITIVE PRESS
AIR-SUPPLD RESP. SPRAY APPLIC, SPRAY BOOTH

Ventil

ation:EXHST VENT TO KEEP CONC BELOW PEL. VENT AIR PAST OPRATR,
VAPOR SRC, THEN EXHST. FOLLOW GUIDELINES-"INDUSTRIAL VENT".

Protective Gloves:SOLVENT RESISTANT GLOVES.

Eye Protection:SAFETY GOGGLES. DO NOT WEAR CONTACT LENS

Other Protective Equipment:SOLVENT RESISTANT APRON AND BOOTS FOR
SPILLS.

Work Hygienic Practices:EYEWASH/SAFETY SHOWER SHOULD BE NEARBY/READY TO
USE. WASH WELL WITH SOAP AND WATER AFTER HANDLING THE PRODUCT.

Supplemental Safety and Health

KEY1:F3. THE USER MUST BE

FULLY PROTECTED FROM EXPOSURE TO THE MATERIAL

DURING MIXING AND SPRAY APPLICATION. IF EXPOSURE MIGHT OCCUR A FULL
PERMEATION RESISTANT PROTECTIVE SUIT INCLUDING HEAD COVERING , FACE
SHIELD, GLOVES, AND OVERSHOES ISREQUIRED.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:241-281F

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:8

Vapor Density:3.6

Spec Gravity:(H2O=1): 1.007

pH:5.5

Viscosity:100-800CPS

Evaporation Rate & Reference:(BUTY

L ACETATE=1): 0.85

Solubility in Water:INSOLUBLE

Appearance and Odor:WHITE AROMATIC LIQUID (COATING SOLUTION).

Percent Volatiles by Volume:63.1

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:ALL IGNITION SOURCES, HOT SURFACES, AND
TEMPERATURES ABOVE 100F (38C).

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
OXIDES OF NITROGEN, AS WELL AS TRACES OF HCN

MAY BE RELEASED DURING
COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE; RCRA HAZARDOUS IGNIT WASTE. DISPOSE ACCORDING TO STATE/LOCAL/FEDERAL REG. WHEN THE C-W4, CURING AGENT, ACCELERATOR ARE MIXED TOGETHER & THE SOLVENT IS ALLOWED TO EVAPORATE, THE SOLID END P RODUCT IS A NON-HAZARDOUS LANDFILL ITEM.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use
by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.