

EXXON COMPANY, USA, A DIV OF EXXON CORP. -- PRIMOL 355 -- 9150-01-083-0300
===== Product Identification =====

Product ID:PRIMOL 355

MSDS Date:04/16/1979

FSC:9150

NIIN:01-083-0300

MSDS Number: BQFDL

=== Responsible Party ===

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Info Phone Num:713-656-5949 FAX: 713-656-36

31

Emergency Phone Num:713-656-3424/2443 (MEDICAL)

CAGE:DO850

=== Contractor Identification ===

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 FAX: 713-656-3631

CAGE:DO850

===== Composition/Information on Ingredients =====

Ingred Name:WHITE

MINERAL OIL, U.S.P.
Fraction by Wt: 100%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5 MG/M3 OIL MIST
ACGIH TLV:5 MG/M3 OIL MIST9192

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: MAY CAUSE IRRITATION. SKIN:
PROLONGED EXPOSURE MAY CAUSE IRRITATION. INHALATION: VAPOR PRESSURE
IS VERY LOW AT ROOM TEMPERATURE. INHALATION I
S NOT A PROBLEM.
INGESTION: THIS PRODUCT HAS A LOW OR DER OF ORAL TOXICITY.
Effects of Overexposure:EYES: IRRITATION. SKIN: IRRITATION. INHALATION:
NOT A PROBLEM UNDER NORMAL CONDITIONS OF USE. INGESTION: PRODUCT HAS
A LOW ORDER OF ORAL TOXICITY.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER. IF IRRITATION
PERSISTS GET MEDICAL ATTENTION. SK
IN: REMOVE CONTAMINATED CLOTHING.
WASH AREA WITH SOAP AND WATER. INHALATION: IF OVERCOME FROM VAPORS
AT HIGH TE MPERATURES, MOVE TO FRESH AIR. IF NOT BREATHING GIVE
CPR. IF BREATHING DIFFICULT GIVE OXYGEN. GET MEDICAL ATTENTION.
INGESTION: GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:430F,221C
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER FOG, OR
WATER SPRAY.
Fire Fighting Procedures:USE AIR-SUPPLIED BREATHING EQUIPMENT FOR
ENCLOSED OR CONFINED AREAS. COOL FIRE EXPOSED CONTAINERS WITH WATER
SPRAY. AVOID BREATHING VAPOR OR FUMES.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS. DO NOT MIX OR STORE
WITH STRONG OXIDANTS LIKE CHLORINE OR CONCENTRATED OXYGEN.

=====
===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SP

ILL BY DIKING. KEEP PRODUCT OUT OF SEWERS AND WATERCOURSES. RECOVER FREE LIQUID. ADD ABSORBENT TO RESIDUE. SHOVEL WASTE INTO CONTAINERS FOR DISPOSAL. ADVISE AUTHORITIES IF PRODUCT HAS OR MAY ENTER SEWERS, WATERCOURSES OR LARGE LAND AREAS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:AVOID BREATHING OIL MIST.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:LOCAL EXHAUST TO CAPTURE FUMES AND VAPORS IF NEEDED.

Protective Gloves:NONE NORMALLY REQUIRED.

Eye Protection:SAFETY GLASSES RECOMMENDED.

Other Protective Equipment:NONE NORMALLY REQUIRED.

Work Hygienic Practices:WASH AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:740F,393C

Vapor Pres:12

Spec Gravity:0.88

Evaporation Rate & Reference: