View NSN Online: https://aerobasegroup.kr/nsn/6750-01-200-8179

CLAYTON CHEMICAL CO. -- CHEMPOS KN KIT- FIXER #3 (5153-000) -- 6750-01-200-8179

============= Product Identification ===============

Product ID:CHEMPOS KN KIT- FIXER #3 (5153-000)

MSDS Date:10/02/1992

FSC:6750

NIIN:01-200-8179

Kit Part:Y

MSDS Number: BQFFP === Responsible Party ===

Company Name: CLAYTON CHEMICAL CO.

Address:13310 FIGUEROA STREET

City:LOS ANGELES

State:CA ZIP:90061 Country:US

Info Phone Num:310-538-9

530

Emergency Phone Num:310-538-9530,CHEMTREC 800-424-9300

CAGE:61803

=== Contractor Identification ===

Company Name: CLAYTON CHEMICAL CO. Address: 13310 S. FIGUEROA STREET

Box:City:LOS ANGELES

State:CA ZIP:90061 Country:US

Phone:310-538-9530/800-424-9300(CHEMTREC)

CAGE:61803

======= Composition/Information on Ingredients ========

Ingred Name: AMMONIUM THIOSULFATE

CAS:7783-18-8

RTECS #:XN6465000 Fraction by Wt: 10-15%

Other REC Limits: NONE RECOMMENDED

Ingred Name: SODIUM BISULFITE (

SASA III) CAS:7631-90-5

RTECS #:VZ2000000 Fraction by Wt: 1-2%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ACETIC ACID (SARA III)

CAS:64-19-7

RTECS #:AF1225000 Fraction by Wt: 1-2%

Other REC Limits: NONE RECOMMENDED

**OSHA PEL:10 PPM** 

ACGIH TLV:10 PPM/15 STEL; 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

========== Hazards Identification ================

Routes of Entry: Inhalation:NO Skin:YE

S Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE- EYE:MAY CAUSE IRRITATION.

SKIN-MAY CAUSE IRRITATION. INHALATION- NORMALLY NO PROBLEM, BUT INHALATION OF MIST MAY CAUSE RESPIRATORY IRRITATION. INGESTION-MAY CAUSE IRRITATION OF MUCOUS MEMBRANES OR DIGESTIVE TRACT.

CHRONIC:NONE NOTED.

Explanation of Carcinogenicity: NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexp

osure:IRRITATION OF EYES, SKIN, REDNESS OF EYES, DIARRHEA, SOTMACHACHE.

Medical Cond Aggravated by Exposure: SKIN DISEASES.

First Aid:INHALATION:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED. EYE CONTACT:FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP. SKIN CONTACT:WASH WITH SOAP AND WATER. GET MED ATTENTION IF SYMPTOMS PERSIS T. INGESTION:DRINK 1-2 GLASSES OF WATER, INDUCE VOMITING. GET MEDICAL HELP

IMMEDIATELY.
======================================
Flash Point:NOT FLAMMABLE Extinguishing Media:ANY EXTINGUISHING MEDIA APPLICABLE TO SURROUNDING AREA.
Fire Fighting Procedures:EVACUATE PERSONNEL TO A SAFE AREA. KEEP PERSONNEL REMOVED AND UPWIND OF FIRE. WEAR SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:WHEN HEATED TO DECOMPOSITION EMISSION OF TOXIC FUMES OF SULFUR DIOXIDE AND AMMONIA GAS IS POSSIBLE.
========= Acc idental Release Measures ===========
Spill Release Procedures:USE APPROPIATE PERSONAL PROTECTIVE EQUIPMENT DURING CLEANUP. DIKE SPILL. PREVENT LIQUID FROM ENTERING SEWERS, WATERWAYS OR LOW AREAS. SOAK UP WITH SAND OR OTHER ABSORBENT MATERIAL. SPILL MAY BE NEUTRA LIZIED.  Neutralizing Agent:VINEGAR OR 5% ACETIC ACID.
======================================
Handling and Storage Precautions:STORE IN WELL VENTILATED AREA. KEEP CONTAINER TIGHTLY C LOSED. DO NOT STORE WITH INCOMPATIBLE MATERIALS, OR FOOD, DRINK OR TOBACCO. Other Precautions:NONE
====== Exposure Controls/Personal Protection =======
Respiratory Protection:SUFFICIENT ROOM VENTILATION.  Ventilation:NONE SPECIFIED BY MANUFACTURER.  Protective Gloves:GLOVES.  Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES  Other Protective Equipment:SAFETY SHOWER AND EYE BATH. INDUSTRIAL TYPE  WORK CLOTHING AND APRON AS REQUIRED TO AVOID PROLONGED OR REPEATED  CONTA  CT.  Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE  EATING OR DRINKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.  Supplemental Safety and Health
THIS IS A FOUR PART KIT. PART A,B,C,D, SAME NSN. KEY 1:C3
========= Physical/Chemical Properties =========
HCC:B3 Boiling Pt:B.P. Text:>212F,>100C Vapor Pres:SAME WATER Vapor Density:SAME WATER Spec Gravity:1.100 pH:5.3 Evaporation Rate & Description of the Company of the Compa

======================================
Stability Indicator/Materials to Avoid:YES STRONG ALKALIS AND OXIDIZERS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:OXIDES OF SULFUR, CARBON DIOXIDE, CARBON MONOXIDE AND AMMONIA GAS.L
======== Disposal Considerations =============
Waste Disposal Methods:RECOVER NONUSABLE FREE LIQUID &/OR CONTAMINAT ED
WATER, & DISPOSE OF IN AN APPROVED & PERMITTED TREATMENT SYSTEM. REMOVE NONUSABLE SOLID MATERIAL &/OR CONTAMINATEDS SOIL, FOR DISPOSAL IN AN APPROVED & PERMITTED LANDFILL.FOLLLOW LOCAL, STATE,FED REGULN
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate an d
disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

 ${\tt dor:CLEAR\ AND\ COLORLESS\ LIQUID,\ SULFUR\ DIOXIDE\ ODOR.}$