View NSN Online: https://aerobasegroup.kr/nsn/9150-00-530-7368

WITCO CHEMICAL CO -- PETROLATUM VV-P-236A -- 9150-00-530-7368

Product ID:PETROLATUM VV-P-236A MSDS Date:06/20/1990 FSC:9150 NIIN:00-530-7368 MSDS Number: BQMFK === Responsible Party === Company Name:WITCO CHEMICAL CO Address:ROUTE 268 City:PETROLIA State:PA ZIP:16050-9201 Country:US Info Phone Num:412-756-2210 Emergency Phone Num:412-756-2210 Preparer's Name:ALEX ANDER COUTRAS CAGE:1F469 === Contractor Identification === Company Name: WITCO CHEMICAL CORP GOLDEN BEAR OIL CO DIVISION Address: MANOR & NORRIS ROADS Box:5446 City:OILDALE State:CA ZIP:93388-5446 Country:US Phone:805-393-7110/800-424-9300(CHEMTREC) CAGE:1F469 Company Name:WITCO CORP Box:84075 City:HOUSTON State:TX ZIP:77042-0075 Country:US Phone:713-975-5858 CAGE:5H954

Ingred Name:GREASE, PETROLEUM CAS:8009-03-8 Other REC Limi LD50 LC50 Mixture: TWA/PEL OF 5 MG/M3 OIL MIST Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NO DATA AVAILABLE. Explanation of Carcinogenicity: THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS. Effects of Overexposure:NO DATA AVAILABLE. Μ edical Cond Aggravated by Exposure:NO DATA AVAILABLE First Aid: EYES: FLUSH IMMEDIATELY WITH COLD WATER. CALL A PHYSICIAN. SKIN: FOR MOLTEN PETROLATUM, FLUSH IMMEDIATELY WITH COLD WATER. CALL A PHYSICIAN. FOR SOLIDIFIED PETROLATUM REMOVE EXCESS WITH PAPER TOWELS, WASH WITH SOAP & WATER. INHALATION: NDA. SWALLOWED: CALL A PHYSICIAN. 

Flash Po int Method:COC Flash Point:>399F,>204C Autoignition Temp:Autoignition Temp Text:NDA Lower Limits:NDA Upper Limits:NDA Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM, WATER FOG, SAND/EARTH. WATER SPRAY IS AN UNSUIATBLE EXTINGUISHING AGENT. Fire Fighting Procedures:FIREFIGHTERS SHOULD USE SELF-CONTAINED BREATHING APPARATUS TO PROTECT AGINST SMOKE INHALATION. Unusual Fire/Explosion Hazard:NONE.

**Spill Release Proce** 

## dures:SHUT OFF LEAK AND DIKE UP LARGE SPILLS. AFTER COOLING AND SOLIDIFICATION, SCRAPE AND/OR SHOVEL UP MATERIAL. FINALLY, CLEAN AREA WITH AN OIL ABSORBENT MATERIAL.

Handling and Storage Precautions:STORE AWAY FROM FLAME, HEAT (200 MAX.), AND STRONG OXIDIZING AGENTS. AVOID SKIN AND EYE CONTACT. Other Precautions:NONE

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NDA Ve ntilation:NDA Protective Gloves:WEAR IMPERVIOUS GLOVES. Eye Protection:WEAR FACE SHIELD OVER SAFETY GLASSES. Other Protective Equipment:WEAR COVERALLS. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING, DRINKING OR SMOKING. Supplemental Safety and Health UNREGULATED BY D.O.T.

HCC:V6 Boiling Pt:B.P. Text:NDA Melt/Freeze Pt:M.P/F.P Text:43-82C Vapor Pres:NDA Vapor Density:NDA Spec Gravity:0.815-0.880 pH:NA Viscosity:NDA Evaporation Rate & amp; Reference:NDA Solubility in Water:NIL Appearance and Odor:SEMI-SOLID, OIL-LIKE, OPAQUE, YELLOW TO BROWN. Percent Volatiles by Volume:NDA

Stability Indicator/Materials to Avoid:YES KEEP AWAY FROM STRONG OXIDIZING AGENTS. Stability Condition to Avoid:KEEP AWAY FROM FLAME, HEAT (200F MAX.). Hazardous Decomposition Products:UPON COMBUSTION, CARBON MONOXIDE AND CARBON DIOXIDE ARE GENER ATED.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.