

UNION OIL CO OF CALIFORNIA -- GENERIC FORD TRANSMISSION FLUID -- 9150-00-843-1636

=====
Product Identification
=====

Product ID:GENERIC FORD TRANSMISSION FLUID

MSDS Date:09/24/1987

FSC:9150

NIIN:00-843-1636

MSDS Number: BQMGX

=== Responsible Party ===

Company Name:UNION OIL CO OF CALIFORNIA

Address:461 S BOYLSTON ST

Box:7600

City:LOS ANGELES

State:CA

ZIP:90017-1443

Country:US

Info Phone Num:213-9

77-7589

Emergency Phone Num:213-977-7589

CAGE:79003

=== Contractor Identification ===

Company Name:UNION OIL CO OF CA UNION 76 DIV- WESTERN RGIION

Address:1201 W 5TH ST

Box:7600

City:LOS ANGELES

State:CA

ZIP:90017-1443

Country:US

CAGE:79003

=====
Composition/Information on Ingredients
=====

Ingred Name:TRADE SECRET COMPONENT

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:TLV: OIL M

IST IS 5.00 MG/M3

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE-THIS MATERIAL MAY CAUSE EYE

IRRITATION. SKIN-THIS MATERIAL MAY CAUSE SKIN IRRITATION.

INHALATION-EXPOSURE TO MIST, OR PROLONGED OR REPEATED EXPOSURE TO

VAPORS THAT MAY BE GENERATED WHEN THIS MATERIAL IS HEATED, MAY

CAUSE IRRITATION OF NOSE & THROAT. INGESTION-INGESTION MAY CAUSE

IRRITATION OF THE DIGESTIVE TRACT.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT
CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT
CARCINOGENS.

Effects of Overexposure:EYE-DIRECT CONTACT MAY CAUSE BURNING, TEARING
AND REDNESS. SKIN-PROLONGED OR REPEATED CONTACT MAY CAUSE REDNESS,
BURNING AND DERMATITIS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYES-FLUSH THE EYES WITH CLEAN WATER. SEEK MEDICAL ATTENTION.

SKIN-WIPE MATERIAL FROM SKIN & REMOVE CONTAMINATED CLOTHES. CLEANSE
AREA WITH SOAP & WATER. INHALATION-MOVE VICTIM AWAY FROM EXPOSURE &
IN TO FRESH AIR. IF NOT BREATHING, PERFORM CPR. IF HARD TO BREATHE,
GIVE OXYGEN. INGESTION-IF CONSCIOUS, GIVE 2-3 CUPS OF MILK OR WATER
TO DRINK. SEEK MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:320F,160C

Autoignition Temp:Autoignition Temp Text:UNKNOWN

Extinguishing Media:EXTINGUISH WITH DRY CHEMICAL, CARBON DIOXIDE, WATER
SPRAY, FOAM, SAND OR EARTH, WATER & FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:USE WATER SPRAY TO MINIMIZE VAPORS & COOL FIRE
EXPOSED CONTAINERS. AVOID SPREADING BURNING LIQUID WITH WATER USED
FOR COOLING PURPOSES. MOVE UNDAMAGED CONTAINER

Unusual Fire/Explosion Hazard:THIS MATERIAL WILL BURN, BUT WILL NOT
IGNITE READILY.

===== Accidental Release Measures =====

Spill

Release Procedures:COLLECT LEAKING LIQUID IN SEALABLE CONTAINERS.
ABSORB SPILLED LIQUID IN SAND OR INERT. CONTACT FIRE AUTHORITIES &
APPROPRIATE STATE/LOCAL AGENCIES. IF SPILL IS MADE UPON US NAVIGABLE
WATERS, NOTIFY THE COAST GAURDS NATIONAL RESPONSE CENTER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY LOCATION. KEEP
AWAY FROM INCOMPATIBLE MATERIALS. AVOID GENERATING OIL ISTS WHILE
HANDLING. AVOID
PROLONGED OR REPEATED CONTACT.

Other Precautions:DO NOT WEAR OIL-SOAKED CLOTHING OR SHOES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF AIRBORNE CONCENTRATIONS EXCEED ESTABLISHED
EXPOSURE LIMITS, A SUITABLE FILTER TYPE RESPIRATOR SHOULD BE WORN.

Ventilation:IF CURRENT VENTILATION PRACTICES ARE NOT ADEQUATE,
ADDITIONAL VENTILATION OR EXHAUST SYSTEM MAY BE REQUIRED.

Protective Gloves:USE IMPERMEABLE GLOVES.

Eye Protection:APPROVED EYE PRO
TECTION.

Other Protective Equipment:IT IS SUGGESTED THAT A SOURCE OF CLEAN WATER
BE AVAILABLE IN THE WORK AREA & BARRIER CREAMS (OIL-BASED) ARE
RECOMMENDED.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. DO NOT WEAR
OIL-SOAKED CLOTHING OR SHOES.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES.

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Vapor Density:>AIR

Spe

c Gravity:0.87-0.88

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, RED LIQUID.

Percent Volatiles by Volume:NEGL

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:EXTENDED EXPOSURE TO HIGH TEMPERATURES MAY
CAUSE DECOMPOSITION.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD MAJOR

AMOUNTS OF OXIDES OF CARBON & MINOR AMOUNTS OF OXIDES OF SULFUR & NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.